



LAIRD TECHNOLOGIES' NEW FULL-SPECTRUM MULTI-BAND ANTENNA

The patent-pending WPD136M6C-001 multi-band mobile antenna is a commercial, heavy-duty vehicular antenna. It has an omnidirectional pattern and is vertically polarized with a 50Ω match. It also has excellent quality & RF performance, and is specifically designed as a full spectrum public safety voice & data communications antenna.

FEATURES

- Frequency range: 136-174/380-520/760-870 MHz
- VSWR (at cable end) < 2.0:1 (typical), < 2.7:1 (at band edges, max)
- Unity gain
- Omnidirectional, vertically polarized
- Power: 100 W (max, PTT = 30 minutes)
- Dimensions: 2.5" Round Base, 20" tall
- Radome material: high impact PC/ABS
- Textured finish
- IP66 rated
- Heavy-duty, chrome plated, spring loaded ferrule, 17-7 ph stainless steel tempered antenna whips, spring-loaded gold plated contact, and stainless steel antenna rod spring
- NMO Style Mount


BENEFITS

- High-performance, broad-banded, multi-band coverage
- Heavy-duty design
- Injection molded housing and base
- No base radiators (all enclosed coils)
- Solid brass chrome plated ferrules with dual set screw lock


MARKETS OR APPLICATIONS

- General analog & digital voice/data communications
- VHF (high), UHF, 700/800
- Tetra PMR & P25 Public Safety
- Transportation, Utilities, Government, Military, PAMR, Commercial & Industry, Oil & Gas


ANTENNA PATTERNS




Azimuth Cut, Phi = 0°
156 MHz




Azimuth Cut, Phi = 0°
440 MHz




Azimuth Cut, Phi = 0°
815 MHz



Elevation Cut, Phi = 90°
156 MHz



Elevation Cut, Phi = 90°
440 MHz



Elevation Cut, Phi = 90°
815 MHz

SPECIFICATIONS

PARAMETER	WPD136M6C-001
Pattern	Omnidirectional
Maximum Power	100 W
Nominal Impedance	50 ohm
Polarization	Vertical
VSWR	≤ 2.5:1
Termination	NMO

ANTENNA ELECTRICAL SPECIFICATIONS

FREQUENCY BAND (MHz)	Frequency Range (MHz), (Test Frequency)	PEAK GAIN (dBi), Azimuth Cut, Phi = 0°	PEAK GAIN (dBi), Elevation Cut, Phi = 90°	ELEVATION BEAMWIDTH AT HALF-POWER	AZIMUTH BEAMWIDTH AT HALF-POWER
136-174 MHz	136, 156, 174	-0.7	0.2	90°	360°
380-520 MHz	380, 440, 520	-3.7	4.8	40°	360°
760-870 MHz	760, 815, 870	3.1	8.1	60°	360°

VHF BAND: 136-174 MHz

PEAK GAIN (DBI)	AZIMUTH PATTERN	ELEVATION PATTERN
136 MHz	-2.4	0.2
146 MHz	-2.7	-1.8
156 MHz	-0.7	-3.1
174 MHz	-3.5	-4.1

UHF BAND: 760-870 MHz

PEAK GAIN (DBI)	AZIMUTH PATTERN	ELEVATION PATTERN
760 MHz	3.1	3.1
815 MHz	-0.2	7.9
870 MHz	-8.8	8.1

UHF BAND: 380-520 MHz

PEAK GAIN (DBI)	AZIMUTH PATTERN	ELEVATION PATTERN
380 MHz	-11.3	6.1
400 MHz	-7	7.7
440 MHz	-4.1	4.8
460 MHz	-3.7	3
500 MHz	-5.5	3.3
520 MHz	-6.6	3.5

ANT-DS-WPD136M6C-001 0313

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.