

# Quad-Channel, 16-Bit CCD Signal Processor with *Precision Timing* Core

**Data Sheet** 

## ADD17015

#### FEATURES

4 independent AFE channels 1.8 V analog and digital core supply voltage Complete on-chip ISATG timing generator with 16 XV outputs and 4 general-purpose outputs (GPO) Differential analog inputs CDS or SHA (CDS bypass) with 7 gain settings 0 dB to 36 dB, 10-bit variable gain amplifier (VGA) 16-bit, 65 MSPS analog-to-digital converter (ADC) Precision Timing core with 240 ps resolution at 65 MHz 8 programmable H-clock outputs On-chip sync generator with external sync input 8 mm × 8 mm CSP\_BGA package with 0.65 pitch

#### APPLICATIONS

Industrial cameras Surveillance cameras Medical imaging Professional photography

### **GENERAL DESCRIPTION**

The ADDI7015 is a highly integrated, quad-channel, CCD signal processor for high speed digital imaging applications. Each channel is specified at pixel rates of up to 65 MHz and consists of a complete analog front end (AFE) with analog-to-digital conversion. The *Precision Timing*\* core allows adjustment of the correlated double sampler (CDS) and sample-and-hold amplifier (SHA) clocks with 240 ps resolution at 65 MHz operation. There are eight independent horizontal clock outputs to support a variety of CCD timing requirements. The ADDI7015 also features a programmable ISATG for vertical timing generation.

Each analog front end includes black level clamping, a CDS, a VGA, and a 65 MSPS, 16-bit analog-to-digital converter (ADC). Operation is programmed using a 4-wire serial interface.

Packaged in a space-saving, 8 mm  $\times$  8 mm, CSP\_BGA, the ADDI7015 is specified over an operating temperature range of  $-25^{\circ}$ C to  $+85^{\circ}$ C.



### FUNCTIONAL BLOCK DIAGRAM

For more information on the ADDI7015, email Analog Devices, Inc., at afe.ccd@analog.

#### Rev. Sp0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

 One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.

 Tel: 781.329.4700
 www.analog.com

 Fax: 781.461.3113
 ©2012 Analog Devices, Inc. All rights reserved.

## ADD17015

### NOTES

©2012 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners. D10869F-0-8/12(Sp0)



www.analog.com

Rev. Sp0 | Page 2 of 2