

America Semiconductor



"In America Semi We Trust"

MANUFACTURER OF WORLD CLASS HIGH POWER SEMICONDUCTORS

America Semiconductor

Silicon Bridge Rectifier

GBU15J thru GBU15M

$V_{RRM} = 50\text{ V} - 1000\text{ V}$
 $I_F = 15\text{ A}$

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- High surge overload rating
- High temperature soldering guaranteed: 260°C/ 10 seconds, 0.375(9.5mm) lead length
- Glass passivated chip junction
- High case dielectric strength 1500 V_{RMS}

GBU Package



Mechanical Data

Case: Molded plastic body over passivated junctions
Mounting position: Any
Terminals: Plated leads, solderable per MIL-STD-750
Method 2026 guaranteed

Maximum ratings, at $T_J = 25\text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	GBU15J	GBU15K	GBU15M	Unit
Repetitive peak reverse voltage	V_{RRM}		600	800	1000	V
RMS reverse voltage	V_{RMS}		420	560	700	V
DC blocking voltage	V_{DC}		600	800	1000	V
Continuous forward current	I_F	$T_C \leq 100\text{ }^\circ\text{C}$	15	15	15	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25\text{ }^\circ\text{C}$, $t_p = 8.3\text{ ms}$	240	240	240	A
Operating temperature	T_J		-55 to 150	-55 to 150	-55 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-55 to 150	-55 to 150	-55 to 150	$^\circ\text{C}$

Electrical characteristics, at $T_J = 25\text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	GBU15J	GBU15K	GBU15M	Unit
Diode forward voltage	V_F	$I_F = 15\text{ A}$, $T_J = 25\text{ }^\circ\text{C}$	1.1	1.1	1.1	V
Reverse current	I_R	$V_R = 50\text{ V}$, $T_J = 25\text{ }^\circ\text{C}$	5	5	5	μA
		$V_R = 50\text{ V}$, $T_J = 125\text{ }^\circ\text{C}$	500	500	500	μA

Thermal characteristics

Thermal resistance, junction - case	R_{thJC}		2.2	2.2	2.2	$^\circ\text{C/W}$
-------------------------------------	------------	--	-----	-----	-----	--------------------







www.AmericaSemi.com

1

America Semiconductor

GBU15J thru GBU15M



www.AmericaSemi.com

2

