

America Semiconductor



"In America Semi We Trust"

MANUFACTURER OF WORLD CLASS HIGH POWER SEMICONDUCTORS

America Semiconductor

Silicon Power Schottky Diode

Features

- High Surge Capability
- Types up to 100 V V_{RRM}
- Isolation Type Package

MBRT40045 thru MBRT400100R

$V_{RRM} = 20\text{ V} - 100\text{ V}$
 $I_F = 400\text{ A}$

Three Tower Package



Maximum ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	MBRT40045 (R)	MBRT40060 (R)	MBRT40080 (R)	MBRT400100 (R)	Unit
Repetitive peak reverse voltage	V_{RRM}		45	60	80	100	V
RMS reverse voltage	V_{RMS}		32	42	57	70	V
DC blocking voltage	V_{DC}		45	60	80	100	V
Continuous forward current	I_F	$T_C \leq 100^\circ\text{C}$	400	400	400	400	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25^\circ\text{C}, t_p = 8.3\text{ ms}$	3000	3000	3000	3000	A
Operating temperature	T_j		-40 to 150	-40 to 150	-40 to 150	-40 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-40 to 175	-40 to 175	-40 to 175	-40 to 175	$^\circ\text{C}$

Electrical characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	MBRT40045 (R)	MBRT40060(R)	MBRT40080 (R)	MBRT400100 (R)	Unit
Diode forward voltage	V_F	$I_F = 200\text{ A}, T_j = 25^\circ\text{C}$	0.75	0.8	0.88	0.88	V
Reverse current	I_R	$V_R = 20\text{ V}, T_j = 25^\circ\text{C}$	1	1	1	1	mA
		$V_R = 20\text{ V}, T_j = 125^\circ\text{C}$	20	20	20	20	mA

Thermal characteristics

Thermal resistance, junction - case	R_{thJC}	0.14	0.14	0.14	0.14	$^\circ\text{C/W}$
-------------------------------------	------------	------	------	------	------	--------------------







www.AmericaSemi.com

1

America Semiconductor

MBRT40045 thru MBRT400100R



www.AmericaSemi.com

2

