

America Semiconductor



"In America Semi We Trust"

MANUFACTURER OF WORLD CLASS HIGH POWER SEMICONDUCTORS

America Semiconductor


Silicon Power Schottky Diode

Features

- High Surge Capability
- Types up to 40V V_{RRM}

Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



1N5829 thru 1N5831R

$V_{RRM} = 20\text{ V} - 40\text{ V}$
 $I_F = 25\text{ A}$

DO-4 Package



Maximum ratings, at $T_j = 25\text{ }^\circ\text{C}$, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	1N5829 (R)	1N5830 (R)	1N5831 (R)	Unit
Repetitive peak reverse voltage	V_{RRM}		20	25	35	V
RMS reverse voltage	V_{RMS}		14	17	25	V
DC blocking voltage	V_{DC}		20	25	35	V
Continuous forward current	I_F	$T_C \leq 100\text{ }^\circ\text{C}$	25	25	25	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25\text{ }^\circ\text{C}, t_p = 8.3\text{ ms}$	800	800	800	A
Operating temperature	T_j		-55 to 150	-55 to 150	-55 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-55 to 175	-55 to 175	-55 to 175	$^\circ\text{C}$

Electrical characteristics, at $T_j = 25\text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	1N5829 (R)	1N5830 (R)	1N5831 (R)	Unit
Diode forward voltage	V_F	$I_F = 25\text{ A}, T_j = 25\text{ }^\circ\text{C}$	0.58	0.58	0.58	V
Reverse current	I_R	$V_R = 20\text{ V}, T_j = 25\text{ }^\circ\text{C}$ $V_R = 20\text{ V}, T_j = 125\text{ }^\circ\text{C}$	2	2	2	mA

Thermal characteristics

Parameter	Symbol	Conditions	1N5829 (R)	1N5830 (R)	1N5831 (R)	Unit
Thermal resistance, junction - case	R_{thJC}		1.8	1.8	1.8	$^\circ\text{C/W}$







www.AmericaSemi.com

1

America Semiconductor

1N5829 thru 1N5831R



www.AmericaSemi.com

2

