Rotary Potentiometer

P160 Series




Features:


- 16 mm
- Conductive plastic element
- 100,000 cycle life
- Metal shaft/bushing
- Multi-ganged available
- RoHS compliant



Model Styles

Side Adjust , Solder Lugs	P160KNP
Side Adjust , PC pins	P160KN
Side Adjust , PC Pins, Long pins	P160KN2
Rear Adjust, PC pins	P160KNPD





Rotary Potentiometer

P160 Series

Sliding Noise

Actual Electrical Travel, Nominal



100mV max.

260°

Electrical Specifications		
Resistance Range, Ohms	500-1M	
Standard Resistance Tolerance	± 20%	
Residual Resistance	20 ohms max.	
Power rating Input Voltage, maximum	200 Vac max.	
Power Rated, Watts	0.2W- B taper, 0.1W-others	
Dielectric Strength	500Vac, I minute	
Insulation Resistance, Minimum	100M ohms at 250Vdc	

Mechanical Specifications

Total Mechanical Travel	300°± 10°
Static Stop Strength	90 oz-in
Rotational Torque	0.5 to 1.25 oz-in

Environmental Specifications


Operating Temperature Range	-20°C to +70°C
Rotational Life	100,000 cycles

Rotary Potentiometer

P160 Series




Shaft Types



Shaft Position (F-Type Shaft)


Dashed lines on Type "C" and Type "A" shows position of adjustment slot for E-Type and Q-Type shafts



Standard Resistance Values, Ohms

100 200 500 1K 2K 5K 10K 20K 50K 100K 200K 500K 1MEG


Circuit Diagram






Outline Drawings

Model P160KNP (Side Adjust, Solder Lugs)




Model P160KN (Side Adjust, PC pins)






Outline Drawings

Model P160KN2 (Side Adjust, PC Pins, Long pins)



Model P160KNPD (Rear Adjust, PC Pins)



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.