

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0191640017](#)  
**Status:** **Active**  
**Description:** Perma-Seal™ Female Quick Disconnect Receptacle for 18-22 AWG Wire, Tab Size 6.35mm (.250") x .081mm (.032")

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Product Literature \(PDF\)](#)

**General**

Product Family Quick Disconnects  
 Series [19164](#)  
 Product Name Perma-Seal™  
 Type Quick Disconnect

**Physical**

Barrel Type Closed  
 Color - Resin Natural  
 Flammability 94V-0  
 Gender Female  
 Glow-Wire Compliant No  
 Insulation NiAc™  
 Lock to Mating Part None  
 Material - Metal Brass  
 Material - Resin Nylon  
 Orientation Straight  
 Packaging Type Bag  
 Tab Thickness 0.81mm (.032")  
 Tab Width 6.35mm (.250")  
 Temperature Range - Operating -55°C to +125°C  
 Wire Insulation Diameter 4.32mm (.170") max.  
 Wire Size AWG 18  
 Wire Size AWG 20  
 Wire Size AWG 22  
 Wire Size mm² 0.25 - 1.50

**Electrical**

CSA LR18689  
 UL E79133  
 Voltage - Maximum 600V

**Material Info**

Old Part Number SAA-9261



Series image - Reference only

**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC**  
**Contains SVHC: No**  
**Halogen-Free**  
**Status**

**China RoHS**



**Not Reviewed**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**  
[19164 Series](#)

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
Crimp Head for the AT-200™ Pneumatic Hand Tool	<a href="#">0640054500</a>
Crimp Head for the AT-200™ Pneumatic Hand Tool	<a href="#">0640054700</a>
Hand Crimp Tool	<a href="#">0640014500</a>
Hand Crimp Tool	<a href="#">0640014700</a>