



2802/2804




2802-X-00-XX-00-00-07-0
Swage mount in .118 hole



2804-X-00-XX-00-00-07-0
Swage mount in .118 hole

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1 | .031 | .078 |
| 2 | .062 | .109 |
| 3 | .094 | .140 |
| 4 | .125 | .171 |


2805



2805-X-00-XX-00-00-07-0
Swage mount in .116 hole

| - X - | Board Thickness | Length V | Depth D |
|-------|-----------------|----------|---------|
| 1 | .031 | .074 | .068 |
| 2 | .062 | .105 | .098 |
| 3 | .094 | .135 | |
| 4 | .125 | .165 | |


2801



2801-X-00-XX-00-00-07-0
Swage mount in .116 hole

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1 | .031 | .078 |
| 2 | .062 | .109 |
| 3 | .094 | .141 |
| 4 | .125 | .172 |
| 5 | .188 | .234 |


2806



2806-X-00-XX-00-00-07-0
Swage mount in .116 hole

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1 | .031 | .078 |
| 2 | .062 | .109 |
| 3 | .094 | .141 |
| 4 | .125 | .172 |

2811



2811-X-00-XX-00-00-07-0
Swage mount in .116 hole

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1 | .031 | .075 |
| 2 | .062 | .105 |
| 3 | .094 | .135 |
| 4 | .125 | .165 |

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
Swage pins are annealed

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: ±.005
DIAMETERS: ±.002
ANGLES: ± 2°

ORDER CODE: 28XX - X - 00 - XX - 00 - 00 - 07 - 0

BASIC PART #



SPECIFY PIN FINISH:

- 01 200μ" TIN/LEAD OVER NICKEL
- 80 200μ" TIN OVER NICKEL ◇
- 44 300μ" SILVER OVER COPPER ◇
- 50 300μ" ELECTRO-SOLDER (60/40 SnPb)