

Product Specification

108-5478

DIN 47297 Series 1.0/2.3 Type "D"

108-5478

NUMBER:

CUSTOMER  
RELEASE

SECURITY  
CLASSIFICATION:

1. Scope :

1.1 Contents

This specification covers the requirements for product performance, test methods and quality assurance provisions of DIN 47297 Series 1.0/2.3 Type "D".

Applicable product descriptions and part numbers are as shown in Appendix 1 :

2. Applicable Documents :

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.

2.1 AMP Specifications :

A. 109-5000 Test Specification, General Requirements for Test Methods

B. 114- Application Specification

B. 501- 5143 Test Report :

2.2 Commercial Standard and Specifications :

A. DIN 47297

B. DIN 47275

C. DIN 40046

D. DIN IEC 68

DR. *April 11, 1995*

CHK. *2 Apr '95*

APP. *12. Apr 95*

SHEET  
1  
OF  
6

**AMP**  
AMP (Japan), Ltd.  
Kawasaki, Japan

LOC	LOC	NO.	REV.
J	A	108-5478	0

NAME  
DIN 47297 Series 1.0/2.3 Type "D"

PRINT  
DST.

O	ECN FJ00-2308-95	H.T	K.S	4-12-95
LTR	REVISION RECORD	DR	CHK	DATE

*04/12/95*

## 3. Requirements :

## 3.1 Design and Construction :

Product shall be of the design, construction and physical dimensions specified in the applicable product drawing.

## 3.2 Materials :

- A. Contact: Male : Brass  
 Female : Bellum Copper Alloy
- B. Housing: Non
- C. Other : Shell : Brass  
 Inner Guide : Bellum Copper Alloy  
 Ferrule : Brass

## 3.3 Ratings :

- A. Voltage Rating : 350 V AC (50 Hz)
- B. Temperature Rating : - 40 °C to 85 °C
- C. Character Impedance : 50 Ω

## 3.4 Performance and Test Descriptions :

The product shall be designed to meet the electrical, mechanical and environmental performance requirements specified in Fig. 2. All tests shall be performed in the room temperature unless otherwise specified.

SHEET	<b>AMP</b> AMP (Japan), Ltd. Kawasaki, Japan		
2 OF 6	LOC J	LOC A	NO. 108-5478
			REV. 0
NAME DIN 47297 Series 1.0/2.3 Type "D"			

108-5478

Customer Release

CLASSIFICATION:

108-5478

NUMBER:

Customer  
ReleaseSECURITY  
CLASSIFICATION:

## 3.5 Test Requirements and Procedures Summary :

Para.	Test Items	Requirements	Procedures	
3.5.1	Confirmation of Product	Product shall be conforming to the requirements of applicable product drawing and Application Specification.	Visually, dimensionally and functionally inspected per applicable quality inspection plan.	
<b>Electrical Requirements</b>				
3.5.2	Termination Resistance (Low Level)	Outer Conductor 3 mΩ Max. Inner Conductor 10 mΩ Max.	Subject mated connector to 20 mV Max. open circuit at 10 mA.	
3.5.3	Insulation Resistance	1000 MΩ Min. (Initial) 200 MΩ Min. (Final)	Impressed voltage 500 V DC. Test between adjacent circuits of unmated connectors. AMP Spec. 109-5302	
3.5.4	Dielectric withstanding Voltage	No creeping discharge nor flashover shall occur.	750 VAC for 5 minute. Test between adjacent circuits of unmated connectors. AMP Spec. 109-5301	
3.5.5	Retain Low	DC~2 GHz : 0.1 Max.		
<b>Mechanical Requirements</b>				
3.5.6	Crimp Tensile Strength	Wire size	Crimp Tensile (min.)	
		mm <sup>2</sup>	(RG)	N (kgf)
		4.08	179/U 316/U	25 (2.55)
		Apply an axial pull-off load to crimped wire of contact secured on the tester, AMP Spec. 109-5205 Condition		
3.5.7	Contact Retention Force	0.2 N (0.02 kgf) Min.	Apply an axial pull-off load to crimped wire. AMP Spec. 109-5212	

Fig.2 (to be continued)

SHEET	<b>AMP</b>			AMP (Japan), Ltd.	
				Kawasaki, Japan	
3 OF 6	LOC	LOC	NOS3	108-5478	REV.
	J	A			0
NAME					
DIN 47297 Series 1.0/2.3 Type "D"					

108-5478

Customer Release

Customer Release

CLASSIFICATION:

Para.	Test Items	Requirements	Procedures
3.5.8	Connector Mating Force	10 N (0.2kgf) Max.	Operation Speed : 100 mm / min. Measure the force required to mate connectors.
3.5.9	Connector Unmating Force	0.9 N (0.09 kgf) Min.	Operation Speed : 100 mm/min. Measure the force required to unmate connectors.
3.5.10	Durability (Repeated Mate / Unmating)	200 mΩ Max. (Final)	Operation Speed : 1500 cycles/hr No. of Cycles : 500 cycles. AMP Spec. 109-5213
3.5.11	Vibration (High Frequency)	200 mΩ Max. (Final)	Vibration Frequency : 10~2000/15 min. Vibration Direction : X-Y-Z Duration : 2 hours each

Fig.2 (End)

SHEET 4 OF 6	<b>AMP</b> AMP (Japan), Ltd. Kawasaki, Japan		
	LOC J	LOC A	NO. 108-5478
NAME			REV. 0
DIN 47297 Series 1.0/2.3 Type "D"			

NUMBER: 108-5478

SECURITY CLASSIFICATION: Customer Release

3.6 Product Qualification Test Sequence

Test of Examination	Test Group	
	1	2
	Test Sequence (a)	
Confirmation of Product	1	1
Termination Resistance (Low Level)	2, 9	3
Dielectric Strength	4	
Insulation Resistance	3	
Retain Low	5	
Vibration (High Frequency)		2
Connector Mating Force	6	
Connector Unmating Force	7	
Contact Unmating Force	//	
Crimp Tensile Strength	/0	
Durability (Repeater mate/Unmate)	8	

(a) Numbers indicate sequence in which tests are performed.

SHEET 5 OF 6	<b>AMP</b>		AMP (Japan), Ltd. Kawasaki, Japan	
	LOC J	LOC A	NO. 108-5478	REV. 0
NAME DIN 47297 Series 1.0/2.3 Type "D"				

108-5478

NUMBER:

Customer  
ReleaseSECURITY  
CLASSIFICATION:

The applicable product descriptions and part numbers are as shown Appendix 1

Product Part No.	Description
100080-2	DIN 47297, 1.0/2.3 Siemence Type Male "D"
100094-2	DIN 47297, 1.0/2.3 Siemence Type Female "D"
100096-1	DIN 47297, 1.0/2.3 Siemence Type R/A "D"

Appendix 1

SHEET 6 OF 6	<b>AMP</b>		AMP (Japan), Ltd. Kawasaki, Japan	
	LOC J	LOC A	NO. 108-5478	REV. 0

NAME

DIN 47297 Series 1.0/2.3 Type "D"