



REV. 0  
DCO 64122

COIL: @ 25°C ±		OHMS
SET		RESET
254 OHMS 10% @ 25° C		254 OHMS ±10% @ 25° C
6.5 VDC NOMINAL VOLTAGE		6.5 VDC NOMINAL VOLTAGE
12.0 VDC MUST OPERATE		12.0 VDC MUST OPERATE
ENVIRONMENT:		
VIBRATION	10 Hz	2500 Hz 30 g's
SHOCK	100 g's	6 MS. DURATION
TEMPERATURE	-65 °C	+125 °C
NOTES: OTHER SPECIFICATIONS IN ACCORDANCE WITH MIL-R-39016/45		
SET/RESET TIME 5MS MAX.		
CONTACT STABILIZATION 2.5MS MAX.		

CUSTOMER DATA SHEET

TERMINAL VIEW

CONTACT RATING: \_\_\_\_\_  
LOW LEVEL TO 2 AMPS 28 VDC  
RESISTIVE 100,000 OPERATIONS

DR. BSH 8-03-01 CK. *8/30/88*

**CII Technologies**  
advanced control electronic solutions

CUST. COMM. EQUIVALENT	TYPE "LS" RELAY	LS-9517M
CUST. NO. M39016/45-017M		