

REV. 0  
DCO 141222

|                 |                            |
|-----------------|----------------------------|
| COIL: @ 25°C    |                            |
| RESISTANCE      | 50 OHMS ±10%               |
| NOMINAL VOLTAGE | 5.0 VDC                    |
| MUST OPERATE    | 2.7 VDC                    |
| MUST RELEASE    | 1.4 VDC MAX, 0.22 VDC MIN. |


ENVIRONMENT:

|             |     |        |      |              |    |     |
|-------------|-----|--------|------|--------------|----|-----|
| VIBRATION   | 10  | CPS TO | 3000 | CPS @        | 30 | g's |
| SHOCK       | 75  | g's    | 6    | MS. DURATION |    |     |
| TEMPERATURE | -65 | °C TO  | +125 | °C           |    |     |

NOTES:

|                |            |
|----------------|------------|
| OPERATE TIME   | 2.0 MS MAX |
| RELEASE TIME   | 4.0 MS MAX |
| CONTACT BOUNCE | 1.5 MS MAX |

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1 AMP  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 8/2/99 EK. *[Signature]* 8/2/99



CUST. C.I.  
CUST. NO. COTS STD. REV. \_\_\_\_\_

'PRMGAD' RELAY

PRMGACD-5XW