


REV. 0  
DCO 143136

COIL: @ 25°C  
 RESISTANCE \_\_\_\_\_ 50 OHMS ±10%  
 NOMINAL VOLTAGE \_\_\_\_\_ 5.0 VDC  
 MUST OPERATE \_\_\_\_\_ 2.7 VDC  
 \_\_\_\_\_  
 MUST RELEASE \_\_\_\_\_ 1.4 VDC MAX, 0.22 VDC MIN.

ENVIRONMENT:  
 VIBRATION \_\_\_\_\_ 10 \_\_\_\_\_ CPS TO \_\_\_\_\_ 3000 \_\_\_\_\_ CPS @ \_\_\_\_\_ 30 \_\_\_\_\_ g's  
 SHOCK \_\_\_\_\_ 75 \_\_\_\_\_ g's \_\_\_\_\_ 6 \_\_\_\_\_ MS. DURATION  
 TEMPERATURE \_\_\_\_\_ -65 \_\_\_\_\_ °C TO \_\_\_\_\_ +125 \_\_\_\_\_ °C

NOTES: \_\_\_\_\_ OPERATE TIME 2.0 MS MAX  
 \_\_\_\_\_ RELEASE TIME 1.5 MS MAX  
 \_\_\_\_\_ CONTACT BOUNCE 1.5 MS MAX

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: \_\_\_\_\_ LOW LEVEL TO 1 AMP  
 \_\_\_\_\_ 28. VDC RESISTIVE 100,000 OPERATIONS

DR. BSH 8/03/01

*Handwritten signature and date: 8/3/01*

**CII Technologies**  
 advanced control electronic solutions

CUST. \_\_\_\_\_ C. I. I.  
 CUST. NO. \_\_\_\_\_ COTS. STD. \_\_\_\_\_ REV. \_\_\_\_\_

"PRMGA" RELAY

PRMGAP - 5X