


Splices (Continued)

**Side Feed Splices —
Non-Insulation Support**



Type	Wire Range		Stock Thickness	Crimp Width	Dim. L	Material	Part Number	
	CMA	mm ²						
A	400-1300	0.20-0.66	.016	.070	.100	Brass	62759-1	
			0.41	1.78	2.54	Tin Plated Brass	62759-2	
						Steel	62759-5	
	500-2200	0.25-1.11	.030	.110	.100	Brass	485016-1	
			0.76	2.79	2.54			
	1200-2600	0.61-1.32	.020	0.51	.090	.120	Brass	61769-1
					2.29	3.05	Nickel Plated Steel	61769-2
						.190	4.83	Brass
	1500-5000	0.76-2.53	.020	0.51	.110	.155	Brass	63130-2
					2.79	3.94	Tin Plated Brass	63130-3
							Tin Plated Phos. Bz.	63130-4
	4000-9000	2.03-4.56	.020	0.51	.140	.250	Brass	485043-1
3.56					6.35	Tin Plated Brass	485043-2	
						Nickel Plated Steel	485043-4	
7000-12500	3.55-6.33	.031	0.79	.180	.265	Tin Plated Steel	61299-1	
				4.57	6.73	Tin Plated Brass	61299-2	
						Brass	61299-3	
8500-14000	4.31-7.10	.025	0.64	.180	.265	Brass	1217967-1	
				4.57	6.73	Tin Plated Brass	1217967-2	
14000-30000	7.10-15.20	.030	0.76	.280	.310	Brass	62754-1	
				7.11	7.87	Tin Plated Brass	62754-2	

Splices