



High Accuracy, Ultralow I_q , 500 mA, anyCAP[®] Low Dropout Regulator

ADP3335

FEATURES

High accuracy over line and load: $\pm 0.9\%$ @ 25°C ,
 $\pm 1.8\%$ over temperature
Ultralow dropout voltage: 200 mV (typ) @ 500 mA
Requires only $C_O = 1.0\ \mu\text{F}$ for stability
anyCAP = stable with any type of capacitor
(Including MLCC)
Current and thermal limiting
Low noise
Low shutdown current: $< 10\ \text{nA}$ (typ)
2.6 V to 12 V supply range
 -40°C to $+85^\circ\text{C}$ ambient temperature range

APPLICATIONS

PCMCIA cards
Cellular phones
Camcorders, cameras
Networking systems, DSL/cable modems
Cable set-top box
MP3/CD players
DSP supplies

GENERAL DESCRIPTION

The ADP3335 is a member of the ADP333x family of precision, low dropout, anyCAP voltage regulators. It operates with an input voltage range of 2.6 V to 12 V, and delivers a continuous load current up to 500 mA. The ADP3335 stands out from conventional low dropout regulators (LDOs) by using an enhanced process enabling it to offer performance advantages beyond its competition. Its patented design requires only a $1.0\ \mu\text{F}$ output capacitor for stability. This device is insensitive to output capacitor equivalent series resistance (ESR), and is stable with any good quality capacitor—including ceramic (MLCC)




Figure 1.




Figure 2. Typical Application Circuit

types for space-restricted applications. The ADP3335 achieves exceptional accuracy of $\pm 0.9\%$ at room temperature and $\pm 1.8\%$ over temperature, line, and load.

The dropout voltage of the ADP3335 is only 200 mV (typical) at 500 mA. This device also includes a safety current limit, thermal overload protection, and a shutdown feature. In shutdown mode, the ground current is reduced to less than $1\ \mu\text{A}$. The ADP3335 has a low quiescent current of $80\ \mu\text{A}$ (typical) in light load situations.

Rev. A

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700
Fax: 781.326.8703
www.analog.com
© 2004 Analog Devices, Inc. All rights reserved.

TABLE OF CONTENTS

| | | | |
|--|----|--|----|
| Specifications..... | 3 | Noise Reduction | 10 |
| Absolute Maximum Ratings..... | 4 | Thermal Overload Protection | 10 |
| Pin Configuration and Function Descriptions..... | 5 | Calculating Junction Temperature..... | 10 |
| Typical Performance Characteristics | 6 | Printed Circuit Board Layout Considerations..... | 11 |
| Theory of Operation | 9 | LFCSP Layout Considerations..... | 11 |
| Application Information..... | 10 | Shutdown Mode | 11 |
| Output Capacitor Selection..... | 10 | Outline Dimensions | 12 |
| Input Bypass Capacitor | 10 | Ordering Guide | 13 |

REVISION HISTORY

1/04 changed from Rev. 0 to Rev. A

| | |
|--|-----------|
| Format updated..... | Universal |
| Renumbered figures | Universal |
| Removed Figure 22..... | 6 |
| Change to Printed Circuit Board | |
| Layout Considerations section..... | 11 |
| Added LFCSP Layout Considerations section..... | 11 |
| Added Package Drawing..... | Universal |
| Changes to Ordering Guide | 16 |

SPECIFICATIONS

All limits at temperature extremes are guaranteed via correlation using standard statistical quality control (SQC) methods. Ambient temperature of 85°C corresponds to a junction temperature of 125°C under pulsed full-load test conditions. Application stable with no load. $V_{IN} = 6.0\text{ V}$, $C_{IN} = C_{OUT} = 1.0\text{ }\mu\text{F}$, $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$, unless otherwise noted.

Table 1.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-------------------------------|----------------------|---|------|------|------|-------------------|
| OUTPUT | | | | | | |
| Voltage Accuracy ¹ | V_{OUT} | $V_{IN} = V_{OUT(NOM)} + 0.4\text{ V}$ to 12 V $I_L = 0.1\text{ mA}$ to 500 mA $T_A = 25^\circ\text{C}$ | -0.9 | | +0.9 | % |
| | | $V_{IN} = V_{OUT(NOM)} + 0.4\text{ V}$ to 12 V $I_L = 0.1\text{ mA}$ to 500 mA $T_A = 85^\circ\text{C}$ | -1.8 | | +1.8 | % |
| | | $V_{IN} = V_{OUT(NOM)} + 0.4\text{ V}$ to 12 V $I_L = 0.1\text{ mA}$ to 500 mA $T_J = 150^\circ\text{C}$ | -2.3 | | +2.3 | % |
| Line Regulation ¹ | | $V_{IN} = V_{OUT(NOM)} + 0.4\text{ V}$ to 12 V $I_L = 0.1\text{ mA}$ $T_A = 25^\circ\text{C}$ | | 0.04 | | mV/V |
| Load Regulation | | $I_L = 0.1\text{ mA}$ to 500 mA $T_A = 25^\circ\text{C}$ | | 0.04 | | mV/mA |
| Dropout Voltage | V_{DROP} | $V_{OUT} = 98\%$ of $V_{OUT(NOM)}$ $I_L = 500\text{ mA}$ | | 200 | 370 | mV |
| | | $I_L = 300\text{ mA}$ | | 140 | 230 | mV |
| | | $I_L = 50\text{ mA}$ | | 30 | 110 | mV |
| | | $I_L = 0.1\text{ mA}$ | | 10 | 40 | mV |
| Peak Load Current | I_{LDPK} | $V_{IN} = V_{OUT(NOM)} + 1\text{ V}$ | | 800 | | mA |
| Output Noise | V_{NOISE} | $f = 10\text{ Hz}$ to 100 kHz, $C_L = 10\text{ }\mu\text{F}$ $I_L = 500\text{ mA}$, $C_{NR} = 10\text{ nF}$ | | 47 | | $\mu\text{V rms}$ |
| | | $f = 10\text{ Hz}$ to 100 kHz, $C_L = 10\text{ }\mu\text{F}$ $I_L = 500\text{ mA}$, $C_{NR} = 0\text{ nF}$ | | 95 | | $\mu\text{V rms}$ |
| GROUND CURRENT | | | | | | |
| In Regulation | I_{GND} | $I_L = 500\text{ mA}$ | | 4.5 | 10 | mA |
| | | $I_L = 300\text{ mA}$ | | 2.6 | 6 | mA |
| | | $I_L = 50\text{ mA}$ | | 0.5 | 2.5 | mA |
| | | $I_L = 0.1\text{ mA}$ | | 80 | 110 | μA |
| In Dropout | I_{GND} | $V_{IN} = V_{OUT(NOM)} - 100\text{ mV}$ $I_L = 0.1\text{ mA}$ | | 120 | 400 | μA |
| In Shutdown | I_{GNDSD} | $\overline{SD} = 0\text{ V}$, $V_{IN} = 12\text{ V}$ | | 0.01 | 1 | μA |
| SHUTDOWN | | | | | | |
| Threshold Voltage | V_{THSD} | ON | 2.0 | | | V |
| | | OFF | | | 0.4 | V |
| \overline{SD} Input Current | $I_{\overline{SD}}$ | $0 \leq \overline{SD} \leq 5\text{ V}$ | | 1.2 | 3 | μA |
| Output Current in Shutdown | $I_{\overline{OSD}}$ | $V_{IN} = 12\text{ V}$, $V_{OUT} = 0\text{ V}$ | | 0.01 | 5 | μA |

¹ $V_{IN} = 2.6\text{ V}$ to 12 V for models with $V_{OUT(NOM)} \leq 2.2\text{ V}$.

ABSOLUTE MAXIMUM RATINGS

Table 2.

| Parameter | Rating |
|---|--------------------|
| Input Supply Voltage | −0.3 V to +16 V |
| Shutdown Input Voltage | −0.3 V to +16 V |
| Power Dissipation | Internally Limited |
| Operating Ambient Temperature Range | −40°C to +85°C |
| Operating Junction Temperature Range | −40°C to +150°C |
| θ_{JA} , 2-layer MSOP-8 | 220°C/W |
| θ_{JA} , 4-layer MSOP-8 | 158°C/W |
| θ_{JA} , 2-layer LFCSP-8 | 62°C/W |
| θ_{JA} , 4-layer LFCSP-8 | 48°C/W |
| Storage Temperature Range | −65°C to +150°C |
| Lead Temperature Range (Soldering 10 sec) | 300°C |
| Vapor Phase (60 sec) | 215°C |
| Infrared (15 sec) | 220°C |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although this product features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.



PIN CONFIGURATIONS AND FUNCTIONAL DESCRIPTIONS




Figure 3. 8-Lead MSOP




Figure 4. 8-Lead LFCSP

Table 3. Pin Function Descriptions

| Pin No. | Mnemonic | Function |
|---------|-----------------|---|
| 1, 2, 3 | OUT | Output of the Regulator. Bypass to ground with a 1.0 μ F or larger capacitor. All pins must be connected together for proper operation. |
| 4 | GND | Ground Pin. |
| 5 | NR | Noise Reduction Pin. Used for further reduction of output noise (see the Noise Reduction section for further details). |
| 6 | \overline{SD} | Active Low Shutdown Pin. Connect to ground to disable the regulator output. When shutdown is not used, this pin should be connected to the input pin. |
| 7, 8 | IN | Regulator Input. All pins must be connected together for proper operation. |

TYPICAL PERFORMANCE CHARACTERISTICS

$T_A = 25^\circ\text{C}$, unless otherwise noted




Figure 5. Line Regulation Output Voltage vs. Supply Voltage




Figure 8. Ground Current vs. Load Current




Figure 6. Output Voltage vs. Load Current




Figure 9. Output Voltage Variation vs. Junction Temperature




Figure 7. Ground Current vs. Supply Voltage




Figure 10. Ground Current vs. Junction Temperature




Figure 11. Dropout Voltage vs. Output Current




Figure 14. Line Transient Response




Figure 12. Power-Up/Power-Down




Figure 15. Line Transient Response




Figure 13. Power-Up Response




Figure 16. Load Transient Response




Figure 17. Load Transient Response




Figure 20. Power Supply Ripple Rejection




Figure 18. Short-Circuit Current




Figure 21. RMS Noise versus C_L (10 Hz to 100 kHz)




Figure 19. Turn On/Turn Off Response




Figure 22. Output Noise Density

APPLICATION INFORMATION

OUTPUT CAPACITOR SELECTION

As with any micropower device, output transient response is a function of the output capacitance. The ADP3335 is stable over a wide range of capacitor values, types, and ESR (anyCAP). A capacitor as low as 1 μF is all that is needed for stability; larger capacitors can be used if high output current surges are anticipated. The ADP3335 is stable with extremely low ESR capacitors ($\text{ESR} \approx 0$), such as multilayer ceramic capacitors (MLCC) or organic semiconductor electrolytic capacitors (OSCON). Note that the effective capacitance of some capacitor types may fall below the minimum at extreme temperatures. Ensure that the capacitor provides more than 1 μF over the entire temperature range.

INPUT BYPASS CAPACITOR

An input bypass capacitor is not strictly required, but is advisable in any application involving long input wires or high source impedance. Connecting a 1 μF capacitor from IN to ground reduces the circuit's sensitivity to PC board layout. If a larger value output capacitor is used, then a larger value input capacitor is also recommended.

NOISE REDUCTION

A noise reduction capacitor (C_{NR}) can be used, as shown in Figure 24, to further reduce the noise by 6 dB to 10 dB (Figure 22). Low leakage capacitors in the 100 pF to 1 nF range provide the best performance. Since the noise reduction pin, NR, is internally connected to a high impedance node, any connection to this node should be made carefully to avoid noise pickup from external sources. The pad connected to this pin should be as small as possible, and long PC board traces are not recommended.

When adding a noise reduction capacitor, maintain a minimum load current of 1 mA when not in shutdown.

It is important to note that as C_{NR} increases, the turn-on time will be delayed. With NR values greater than 1 nF, this delay may be on the order of several milliseconds.




Figure 24. Typical Application Circuit

THERMAL OVERLOAD PROTECTION

The ADP3335 is protected against damage from excessive power dissipation by its thermal overload protection circuit, which limits the die temperature to a maximum of 165°C. Under extreme conditions (i.e., high ambient temperature and power dissipation) where die temperature starts to rise above 165°C, the output current is reduced until the die temperature has dropped to a safe level. The output current is restored when the die temperature is reduced.

Current and thermal limit protections are intended to protect the device against accidental overload conditions. For normal operation, device power dissipation should be externally limited so that junction temperatures will not exceed 150°C.

CALCULATING JUNCTION TEMPERATURE

Device power dissipation is calculated as follows:

$$P_D = (V_{IN} - V_{OUT})I_{LOAD} + (V_{IN})I_{GND}$$

Where I_{LOAD} and I_{GND} are load current and ground current, and V_{IN} and V_{OUT} are input and output voltages, respectively.

Assuming $I_{LOAD} = 400 \text{ mA}$, $I_{GND} = 4 \text{ mA}$, $V_{IN} = 5.0 \text{ V}$, and $V_{OUT} = 3.3 \text{ V}$, device power dissipation is

$$P_D = (5 \text{ V} - 3.3 \text{ V})400 \text{ mA} + 5.0 \text{ V}(4 \text{ mA}) = 700 \text{ mW}$$

The junction temperature can be calculated from the power dissipation, ambient temperature, and package thermal resistance. The thermal resistance is a function not only of the package, but also of the circuit board layout. Standard test conditions are used to determine the values published in this data sheet, but actual performance will vary. For an LFCSP-8 package mounted on a standard 4-layer board, θ_{JA} is 48°C/W. In the above example, where the power dissipation is 700 mW, the temperature rise above ambient will be approximately equal to

$$\Delta T_{JA} = 0.700 \text{ W} \times 48^\circ\text{C/W} = 33.6^\circ\text{C}$$

To limit the maximum junction temperature to 150°C, the maximum allowable ambient temperature will be

$$T_{AMAX} = 150^\circ\text{C} - 33.6^\circ\text{C} = 116.4^\circ\text{C}$$

In this case, the resulting ambient temperature limitation is above the maximum allowable ambient temperature of 85°C.

PRINTED CIRCUIT BOARD LAYOUT CONSIDERATIONS

All surface-mount packages rely on the traces of the PC board to conduct heat away from the package. Use the following general guidelines when designing printed circuit boards to improve both electrical and thermal performance.

1. Keep the output capacitor as close as possible to the output and ground pins.
2. Keep the input capacitor as close as possible to the input and ground pins.
3. PC board traces with larger cross sectional areas will remove more heat from the ADP3335. For optimum heat transfer, specify thick copper and use wide traces.
4. It is not recommended to use solder mask or silkscreen on the PCB traces adjacent to the ADP3335's pins, since doing so will increase the junction-to-ambient thermal resistance of the package.
5. Use additional copper layers or planes to reduce the thermal resistance. When connecting to other layers, use multiple vias, if possible.

LFCSP LAYOUT CONSIDERATIONS

The LFCSP package has an exposed die paddle on the bottom, which efficiently conducts heat to the PCB. In order to achieve the optimum performance from the LFCSP package, special consideration must be given to the layout of the PCB. Use the following layout guidelines for the LFCSP package.




Figure 25. 3 mm x 3 mm LFCSP Pad Pattern
(Dimensions shown in millimeters)

1. The pad pattern is given in Figure 25. The pad dimension should be followed closely for reliable solder joints, while maintaining reasonable clearances to prevent solder bridging.
2. The thermal pad of the LFCSP package provides a low thermal impedance path (approximately 20°C/W) to the PCB. Therefore, the PCB must be properly designed to effectively conduct heat away from the package. This is achieved by adding thermal vias to the PCB, which provide a thermal path to the inner or bottom layers. See Figure 25 for the recommended via pattern. Note that the via diameter is small to prevent the solder from flowing through the via and leaving voids in the thermal pad solder joint.

Also, note that the thermal pad is attached to the die substrate, so the thermal planes to which the thermal vias connect must be electrically isolated or tied to V_{IN} . Do NOT connect the thermal pad to ground.
3. The solder mask opening should be about 120 μ (4.7 mils) larger than the pad size, resulting in a minimum 60 μ (2.4 mils) clearance between the pad and the solder mask.
4. The paste mask opening is typically designed to match the pad size used on the peripheral pads of the LFCSP package. This should provide a reliable solder joint as long as the stencil thickness is about 0.125 mm. The paste mask for the thermal pad needs to be designed for the maximum coverage to effectively remove the heat from the package. However, due to the presence of thermal vias and the size of the thermal pad, eliminating voids may not be possible.
5. The recommended paste mask stencil thickness is 0.125 mm. A laser cut stainless steel stencil with trapezoidal walls should be used. A “No Clean” Type 3 solder paste should be used for mounting the LFCSP package. Also, a nitrogen purge during the reflow process is recommended.
6. The package manufacturer recommends that the reflow temperature should not exceed 220°C and the time above liquidus is less than 75 seconds. The preheat ramp should be 3°C/second or lower. The actual temperature profile depends on the board density and must be determined by the assembly house as to what works best.

SHUTDOWN MODE

Applying a TTL high signal to the shutdown (\overline{SD}) pin or tying it to the input pin, turns the output ON. Pulling \overline{SD} down to 0.4 V or below, or tying it to ground, turns the output OFF. In shutdown mode, quiescent current is reduced to a typical value of 10 nA.

OUTLINE DIMENSIONS





Figure 26. 8-Lead Frame Chip Scale Package [LFCSP]
(CP-8)

Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MO-187AA

Figure 27. 8-Lead Mini Small Outline Package [MSOP]
(RM-8)

Dimensions shown in millimeters

ORDERING GUIDE

| Model | Output Voltage¹ | Package Option | Branding Information |
|----------------------------------|-----------------------------------|-----------------------|-----------------------------|
| ADP3335ARM-1.8-RL | 1.8 V | RM-8 (MSOP-8) | LFA |
| ADP3335ARM-1.8-RL7 | 1.8 V | RM-8 (MSOP-8) | LFA |
| ADP3335ARM-2.5-RL | 2.5 V | RM-8 (MSOP-8) | LFC |
| ADP3335ARM-2.5-RL7 | 2.5 V | RM-8 (MSOP-8) | LFC |
| ADP3335ARMZ-2.5-RL7 ² | 2.5 V | RM-8 (MSOP-8) | LFC ³ |
| ADP3335ARM-2.85-RL | 2.85 V | RM-8 (MSOP-8) | LFD |
| ADP3335ARM-2.85-R7 | 2.85 V | RM-8 (MSOP-8) | LFD |
| ADP3335ARMZ-2.85-R7 ² | 2.85 V | RM-8 (MSOP-8) | LFD ³ |
| ADP3335ARM-3.3-RL | 3.3 V | RM-8 (MSOP-8) | LFE |
| ADP3335ARMZ-3.3-RL ² | 3.3 V | RM-8 (MSOP-8) | LFE ³ |
| ADP3335ARM-3.3-RL7 | 3.3 V | RM-8 (MSOP-8) | LFE |
| ADP3335ARM-5-REEL | 5 V | RM-8 (MSOP-8) | LFF |
| ADP3335ARM-5-REEL7 | 5 V | RM-8 (MSOP-8) | LFF |
| ADP3335ACP-1.8-RL | 1.8 V | CP-8 (LFCSP-8) | LFA |
| ADP3335ACP-1.8-RL7 | 1.8 V | CP-8 (LFCSP-8) | LFA |
| ADP3335ACP-2.5-RL | 2.5 V | CP-8 (LFCSP-8) | LFC |
| ADP3335ACP-2.5-RL7 | 2.5 V | CP-8 (LFCSP-8) | LFC |
| ADP3335ACP-2.85-R7 | 2.85 V | CP-8 (LFCSP-8) | LFD |
| ADP3335ACP-3.3-RL | 3.3 V | CP-8 (LFCSP-8) | LFE |
| ADP3335ACP-3.3-RL7 | 3.3 V | CP-8 (LFCSP-8) | LFE |
| ADP3335ACP-5-REEL | 5 V | CP-8 (LFCSP-8) | LFF |
| ADP3335ACP-5-REEL7 | 5 V | CP-8 (LFCSP-8) | LFF |

¹ Contact the factory for other output voltage options.² Z = Pb-free part.³ Pb-free devices have a "#" marked on the device.

ADP3335

NOTES

NOTES

ADP3335

NOTES