

Radiation Hardened Ultra High Frequency NPN/PNP Transistor Arrays

ISL73096RH, ISL73127RH, ISL73128RH

The ISL73096RH, ISL73127RH and ISL73128RH are radiation hardened bipolar transistor arrays. The ISL73096RH consists of three NPN transistors and two PNP transistors on a common substrate. The ISL73127RH consists of five NPN transistors on a common substrate. The ISL73128RH consists of five PNP transistors on a common substrate. One of our bonded wafer, dielectrically isolated fabrication processes provides an immunity to Single Event Latch-up and the capability of highly reliable performance in any radiation environment.

The high gain-bandwidth product and low noise figure of these transistors make them ideal for use in high frequency amplifier and mixer applications. Monolithic construction of the NPN and PNP transistors provides the closest electrical and thermal matching possible. Access is provided to each terminal of the transistors for maximum application flexibility.

Specifications for Rad Hard QML devices are controlled by the Defense Supply Center in Columbus (DSCC). The SMD numbers listed here must be used when ordering.

Detailed Electrical Specifications for these devices are contained in SMD 5962-07218. A "hot-link" is provided on our website for downloading.

Features

- Electrically Screened to SMD # 5962-07218
- QML Qualified per MIL-PRF-38535 Requirements
- Radiation Environment
 - Gamma Dose (γ) 3 x 10⁵RAD(Si)
 - SEL Immune. . Bonded Wafer Dielectric Isolation
- NPN Gain Bandwidth Product (F_T) . . . 8GHz (Typ)
- NPN Current Gain (h_{FE})..... 130 (Typ)
 NPN Early Voltage (V_A).... 50V (Typ)
- PNP Gain Bandwidth Product (F_T)...5.5GHz (Typ)
- PNP Current Gain (h_{FE}) 60 (Typ)
- PNP Early Voltage (V_A) 20V (Typ)
- Noise Figure (50Ω) at 1GHz..... 3.5dB (Typ)
- Collector-to-Collector Leakage <1pA (Typ)
- Complete Isolation Between Transistors

Applications

- High Frequency Amplifiers and Mixers
 Refer to Application Note AN1503
- High Frequency Converters
- Synchronous Detector

| ORDERING NUMBER | PART NUMBER | TEMP. RANGE (°C) | PACKAGE (Pb-free) |
|--------------------|---------------------------|---------------------|----------------------|
| 5962F0721801V9A | ISL73096RHVX | -55 to +125 | DIE |
| 5962F0721801VXC | ISL73096RHVF (Notes 1, 2) | -55 to +125 | 16 LD FLATPACK |
| 5962F0721802V9A | ISL73127RHVX | -55 to +125 | DIE |
| 5962F0721802VXC | ISL73127RHVF (Notes 1, 2) | -55 to +125 | 16 LD FLATPACK |
| 5962F0721803V9A | ISL73128RHVX | -55 to +125 | DIE |
| 5962F0721803VXC | ISL73128RHVF (Notes 1, 2) | -55 to +125 | 16 LD FLATPACK |
| ISL73096RHF/PROTO | ISL73096RHF/PROTO | -55 to +125 | |
| ISL73096RHX/SAMPLE | ISL73096RHX/SAMPLE | -55 to +125 | DIE |
| ISL73127RHF/PROTO | ISL73127RHF/PROTO | -55 to +125 | |
| ISL73127RHX/SAMPLE | ISL73127RHX/SAMPLE | -55 to +125 | DIE |

Ordering Information

1

Ordering Information (Continued)

| ORDERING NUMBER | PART NUMBER | TEMP. RANGE (°C) | PACKAGE (Pb-free) |
|--------------------|--------------------|---------------------|----------------------|
| ISL73128RHF/PROTO | ISL73128RHF/PROTO | -55 to +125 | |
| ISL73128RHX/SAMPLE | ISL73128RHX/SAMPLE | -55 to +125 | DIE |

NOTES:

1. These Intersil Pb-free Hermetic packaged products employ 100% Au plate - e4 termination finish, which is RoHS compliant and compatible with both SnPb and Pb-free soldering operations.

2. For Moisture Sensitivity Level (MSL), please see device information page for <u>ISL73096RH, ISL73127RH, ISL73128RH</u>. For more information on MSL please see techbrief <u>TB363</u>.

Pin Configurations





ISL73127RH (16 LD FLATPACK) CDFP4-F16 TOP VIEW



ISL73128RH (16 LD FLATPACK) CDFP4-F16 TOP VIEW



Die Characteristics

DIE DIMENSIONS:

52.8 mils x 52.0 mils x 14 mils ± 1 mil 1340µm x 1320µm x 355.6µm $\pm 25.4\mu m$

INTERFACE MATERIALS:

Glassivation:

Type: Nitride Thickness: 4kÅ ±0.5kÅ

Top Metallization:

Type: Metal 1: AlCu (2%)/TiW Thickness: Metal 1: 8kÅ ±0.5kÅ Type: Metal 2: AlCu (2%) Thickness: Metal 2: 16kÅ ±0.8kÅ

Substrate:

UHF-1X Bonded Wafer, DI

Backside Finish:

Silicon

Metallization Mask Layout

ASSEMBLY RELATED INFORMATION:

Substrate Potential:

Floating

ADDITIONAL INFORMATION:

Worst Case Current Density: $3.04 \times 10^5 \text{A/cm}^2$

Transistor Count:

5



FIGURE 1. ISL73096RH, ISL73127RH

For additional products, see www.intersil.com/product_tree

Intersil products are manufactured, assembled and tested utilizing ISO9000 quality systems as noted in the quality certifications found at <u>www.intersil.com/design/quality</u>

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com



Metallization Mask Layout (Continued)



FIGURE 2. ISL73128RH

Revision History

The revision history provided is for informational purposes only and is believed to be accurate, but not warranted. Please go to web to make sure you have the latest Rev.

| DATE | REVISION | CHANGE |
|----------|----------|---|
| 11/12/09 | FN6475.3 | Converted to new Intersil template. Changed App Note Reference from "AN9315" to "AN1503" to reflect new app note for the radiation hardened product. Updated ordering information with package column, notes to match lead finish and MSL note. |
| 03/23/09 | FN6475.2 | Under Pinouts, changed DIP symbols to flatpack symbols. Changed (16 LD SBDIP) CDIP2-T16 to (16 LD Flatpack) CDFP4-F16. Under Ordering Information, added the following flatpack device types: 5962F0721801VXC (ISL73096RHVF), 5962F0721802VXC (ISL73127RHVF) and 5962F0721803VXC (ISL73128RHVF). |
| 12/2007 | FN6475.1 | Added ISL73127RH & ISL73128RH device types. |
| 03/29/07 | FN6475.0 | Initial Release. |

Products

Intersil Corporation is a leader in the design and manufacture of high-performance analog semiconductors. The Company's products address some of the industry's fastest growing markets, such as, flat panel displays, cell phones, handheld products, and notebooks. Intersil's product families address power management and analog signal processing functions. Go to <u>www.intersil.com/products</u> for a complete list of Intersil product families.

*For a complete listing of Applications, Related Documentation and Related Parts, please see the respective device information page on intersil.com: <u>ISL73096, ISL73127RH, ISL73128RH</u>

To report errors or suggestions for this datasheet, please go to www.intersil.com/askourstaff

FITs are available from our website at http://rel.intersil.com/reports/search.php

4