



Notes:

- Material and Finish:
 - Receptacle Housing & Protective Cover: Zinc Die-Cast, Nickel Plated
 - Ball Chain Assembly: Copper Alloy and Stainless Steel, Nickel Plated
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicon, Color: White
 - Duplex LC Adaptor Assembly:
 - Housing: Mod. PPO, UL94 V-0, Color: SM Blue/MM Beige/APC SM Green
 - Alignment Sleeves: SM Ceramic/MM Phosphor Bronze
 - Dust Cap: PP, Color: Neutral transparent
 - Operating Temperature: -40°C to +85°C
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- IP67 rated when covered or fully mated with the appropriate mating connector

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Nickel Plated Die-Cast Duplex LC Single Mode Receptacle + Cover Assembly	17-300380
Nickel Plated Die-Cast Duplex LC Multi Mode Receptacle Cover Assembly	17-300390
Nickel Plated Die-cast Duplex LC APC Single Mode Receptacle Cover Assembly	17-300400

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified			Scale:	Dim. in mm
	Name	Title	Approval Date	0 PLC ± 0.30	1 PLC ± 0.20		Autodesk Inventor	Material: See Notes
				2 PLC ± 0.10	3 PLC ± 0.05	2011 Date Name Draw. Nov. 09 Vincent Ke Appd. Nov. 09 J. Chaudry	Title: IP67 Industrial Duplex LC Receptacle + Cover Assembly Kit Nickel Plated Die-Cast Version	
				ANGLES ± 1°		Norm	Drawing No.: 17K1A302	
				D-old			Part No.: SEE PART NUMBER TABLE	
	a	original						DIN A3
Rev.	Changes	Date	Name					Sheet 1/1