



NOTES:

1. METALSHELLS.STELL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. FRAME: STEEL; NICKEL PLATED
4. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
5. RIVETED INSERT: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
6. COLLAR: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
7. CONNECTOR IS PART MARKED: DSS3XSXXB01X CONEC ABC

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name
a	Origin		

tolerance			scale: 2:1 (5:1)
dim. in mm			
drawn	19.06.07	Lehmenkühler	title: D-SUB FEMALE 25pos. CRIMP STYLE with frame, float for blind mating system
appd.	19.06.07	Mickenbecker	
norm			
d-old			
dwg no:		Inventor 10	DIN-A3
part no:		16K1A2090	sh: 1
part no:		DSS3XSXXB01X	

