





| SWITCH FUNCTION |        |          |
|-----------------|--------|----------|
| POS. 1          | POS. 2 | POS. 3   |
|                 |        |          |
| ON              | NONE   | ON       |
| 2-3; 5-6        | NONE   | 2-1; 5-4 |



PCB LAYOUT



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACTS: GOLD PLATED
5. RATING: 0.4 VA max. @ 20V AC OR DC max.
6. CONTACT RESISTANCE: <100 MILLI-OHM
7. ELECTRICAL LIFE: 6,000 MAKE-AND-BREAK CYCLES.
8. INSULATION RESISTANCE: 500 MEGA-OHM min.
9. DIELECTRIC STRENGTH: 500 V RMS @SEA LEVEL.
10. OPERATING TEMP.: -30°C to 85°C
11. ▲ DENOTES CRITICAL PARAMETER.
12. SEAL RATING: IP67
13. 2002/95/EC (ROHS) COMPLIANT



TITLE 400UDP1L1BLKM7RE

|     |        |             |         |    |
|-----|--------|-------------|---------|----|
| A   | 21954  | NEW RELEASE | 8/14/15 | rc |
| REV | PCR NO | DESCRIPTION | DATE    | BY |

|                |                   |          |                |          |
|----------------|-------------------|----------|----------------|----------|
| SCALE<br>2.5:1 | DATE<br>8/11/2015 | DR<br>rc | DWG<br>T480005 | REV<br>A |
|----------------|-------------------|----------|----------------|----------|

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED