

12-Bit, 170 MHz Video and Graphics Digitizer with 3D Comb Filter Decoder and Quad HDMI Receiver

ADV7840

FEATURES

Video and graphics digitizer

Four 170 MHz, 12-bit ADCs

12-channel analog input mux

525i-/625i-component analog input

525p-/625p-component progressive scan support

720p-/1080i-/1080p-component HDTV support

Digitizes RGB graphics up to 1600 × 1200 at 60 Hz (UXGA)

HDMI®/graphics and composite processing

Simultaneous HDMI and graphics synchronization processing

NTSC/PAL/SECAM color standards support

NTSC/PAL 3D comb filter

3D digital noise reduction (DNR)

Advanced time-base correction (TBC) with frame synchronization

Interlaced-to-progressive conversion for 525i and 625i

Advanced VBI data slicer, including teletext, CC, and V-chip

IF compensation filter

Analog monitor output

SCART fast blank support, including slow switch detect

Programmable internal antialias filters

Support for weak, poor time base and nonstandard input signals

Vertical peaking, horizontal peaking, CTI, and LTI

Quad HDMI® receiver

HDMI 1.3a support

36-/30-/24-bit deep color support

Flexible audio interface (DSD, DST, Dolby® TrueHD, DTS®-

HD master audio, and DTS-HD high resolution audio)

225 MHz HDMI receiver

Repeater support

High-bandwidth Digital Content Protection (HDCP 1.3)

36-/30-bit Deep Color and 24-bit color support

HDMI 1.3-compatible audio interface

S/PDIF (IEC90658-compatible) digital audio output

Programmable equalizer for cable lengths up to 30 meters

Internal EDID RAM

General

Highly flexible output interface

36-bit 4:4:4 pixel output interface

Dual STDI function support standard identification

2 any-to-any, 3 \times 3 color space conversion (CSC) matrices

3 programmable interrupt request output pins

Advanced synchronization processing for robust synchronization extraction for poor video sources

APPLICATIONS

Advanced TVs

PDP HDTVs

LCD TVs (HDTV ready)

LCD/DLP® rear projection HDTVs

CRT HDTVs

LCoS™ HDTVs

AVR video receivers

LCD/DLP front projectors

HDTV STBs with PVR

CRT HDTV

Projectors

DVD recorders with progressive scan input support

FUNCTIONAL BLOCK DIAGRAM




Figure 1.

For more information about the ADV7840, contact your local Analog Devices, Inc., FAE or sales office.



NSV

Precision Video
by Analog Devices

Rev. SpC

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

ADV7840* PRODUCT PAGE QUICK LINKS

Last Content Update: 02/23/2017

COMPARABLE PARTS 🖵

View a parametric search of comparable parts.

DOCUMENTATION

Application Notes

 AN-1050: A Method for Compressing I²C Scripts for the ADV74xx/ADV75xx/ADV76xx/ADV78xx

Data Sheet

 ADV7840: 12-Bit, 170 MHz Video and Graphics Digitizer with 3D Comb Filter Decoder and Quad HDMI Receiver Data Sheet

DESIGN RESOURCES 🖵

- · ADV7840 Material Declaration
- · PCN-PDN Information
- · Quality And Reliability
- · Symbols and Footprints

DISCUSSIONS

View all ADV7840 EngineerZone Discussions.

SAMPLE AND BUY 🖳

Visit the product page to see pricing options.

TECHNICAL SUPPORT

Submit a technical question or find your regional support number.

DOCUMENT FEEDBACK 🖳

Submit feedback for this data sheet.

| ADV7840 |
|---|
| NOTES |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| I ² C refers to a communications protocol originally developed by Philips Semiconductors (now NXP Semiconductors). |
| HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. |
| |
| |

