



P1	P2
1 WHITE	1
2 BLACK	2
3 RED	3
4 GREEN	4
5 YELLOW	5
6 BLUE	6



Note for plug:

- Material: Housing-polycarbonate, clear.
- Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/W-5/R	A	1,525±20(5ft)	White	1,525-1,535mm
AT-S-26-6/6/W-7/R	B	2,135±30(7ft)	White	2,135-2,145mm
AT-S-26-6/6/W-10/R	C	3,050±60(10ft)	White	3,050-3,060mm
AT-S-26-6/6/W-12/R	D	3,660±60(12ft)	White	3,660-3,670mm
AT-S-26-6/6/W-14/R	E	4,270±60(14ft)	White	4,270-4,280mm
AT-S-26-6/6/W-25/R	F	7,625±100(25ft)	White	7,625-7,635mm
AT-S-26-6/6/W-50/R	G	15,250±150(50ft)	White	15,250-15,260mm

Unit: mm



Scale	Free				Date	Name
TOLERANCE					Drawn	27.06.13 Wilson
X.	±X				Approved	27.06.13 Groll
X.X	±X					
X.XX	±X					
DIM	TOL					
X.°	±X°					
X.X°	±X°					
Angle	TOL	Id.	Modification	Date	Name	



Title		Modular cable - Straight/Reversed	
		6P6C 50µ", 26AWG, White, 5-50 feet	
ASSMANN WSW-No.		AT-S-26-6/6/W-xx/R	
Drawing-No.			
Replace		rev00	
		Sheet 1/1	