



2.4 ± 0.2
SEC: A=A

P1	P2
1 WHITE	1
2 ORANGE	2
3 BLACK	3
4 RED	4
5 GREEN	5
6 YELLOW	6
7 BLUE	7
8 BROWN	8



A, B, C, D



E, F, G

Note for plug:

- Material: Housing-polycarbonate, clear.
- Terminal-0.36[.014] thick phosphor bronze.
- Thick gold in localized gold plate.
- Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-8/8/B-5/R	A	1,525±20(5ft)	Black	1,525-1,535mm
AT-S-26-8/8/B-7/R	B	2,135±30(7ft)	Black	2,135-2,145mm
AT-S-26-8/8/B-10/R	C	3,050±60(10ft)	Black	3,050-3,060mm
AT-S-26-8/8/B-12/R	D	3,660±60(12ft)	Black	3,660-3,670mm
AT-S-26-8/8/B-14/R	E	4,270±60(14ft)	Black	4,270-4,280mm
AT-S-26-8/8/B-25/R	F	7,625±100(25ft)	Black	7,625-7,635mm
AT-S-26-8/8/B-50/R	G	15,250±150(50ft)	Black	15,250-15,260mm

Unit: mm



Scale	Free	Date	Name
TOLERANCE		Drawn	28.06.13 Wilson
X.	±X	Approved	28.06.13 Groll
X.X	±X		
X.XX	±X		
DIM	TOL		
X.°	±X°		
X.X°	±X°		
Angle	TOL		



Title	
Modular cable - Straight/Reversed 8P8C 50µ", 26AWG, Black, 5-50 feet	
ASSMANN WSW-No.	
AT-S-26-8/8/B-xx/R	
Drawing-No.	
Replace	rev00
Sheet	1/1

1

2

3

4

5

6

7