



2.4 ± 0.2
SEC: A=A

P1		P2
1	WHITE	1
2	ORANGE	2
3	BLACK	3
4	RED	4
5	GREEN	5
6	YELLOW	6
7	BLUE	7
8	BROWN	8



A, B, C, D



E, F, G

Note for plug:

- Material: Housing-polycarbonate, clear.
- Terminal-0.36[.014] thick phosphor bronze.
- Thick gold in localized gold plate.
- Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-8/8/S-5/R	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-8/8/S-7/R	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-8/8/S-10/R	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-8/8/S-12/R	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-8/8/S-14/R	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-8/8/S-25/R	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-8/8/S-50/R	G	15,250±150(50ft)	Silver	15,250-15,260mm

Unit: mm



Scale	Free					Date	Name
TOLERANCE						Drawn	28.06.13
X.	±X					Approved	28.06.13
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name		

Title	
Modular cable - Straight/Reversed	
8P8C 50µ", 26AWG, Silver, 5-50 feet	
ASSMANN WSW-No.	
AT-S-26-8/8/S-xx/R	
Drawing-No.	
rev00	
Replace	Sheet
	1/1

1

2

3

4

5

6

7