

Technical specification:

Rated voltage: 3pos 4pos
IEC 61076-2-104 60 V 30 V

Current rating: 3 A bei 40°C
IEC 61076-2-104

Insulation resistance: >=100 MΩ
IEC 60512

Pollution degree: 3/2
IEC 60664-1

Degree of protection: IP 67, in mated condition
IEC 60529

Temperature range: -30°C ... +85°C
IEC 60664-1

Mating cycles: >=100
IEC 60512-9a

Materials:


Contact: CuZn

Contact plating: Nickel, gold plated

Contact carrier: PA , UL 94

Socket housing: CuZn, nickel plated

Part no:	Description:	Pos
42-01008	SAL - 8 - ESVM3 - L	3
42-01009	SAL - 8 - ESVM4 - L	4

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 02.03.11 fro Ä3914 Data sheet revised	 dim. in mm	title: Male socket M8x1 with soldering version	
				date name
		drawn 15.10.08 Fromm		dwg no: 42K1A112
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	