

**Technical specification:**

Rated voltage: 3pos 4pos  
IEC 61076-2-104 60 V 30 V

Current rating: 3 A bei 40°C  
IEC 61076-2-104

Insulation resistance: >=100 MΩ  
IEC 60512

Pollution degree: 3/2  
IEC 60664-1

Degree of protection: IP 67, in mated condition  
IEC 60529

Temperature range: -30°C ... +85°C  
IEC 60664-1



Mating cycles: >=100  
IEC 60512-9a

**Materials:**

Contact: CuZn

Contact plating: Nickel, gold plated

Contact carrier: PA GF, UL 94



Part no:	Description:	Pos
42-01012	SAL - 8 - ESP3 - P	3
42-01014	SAL - 8 - ESP4 - P	4

DO NOT ALTER CAD DRAWING BY HAND  
Directive 2002/95/EC RoHS compliant

Index: d 02.03.11 fro Ä3914  
Data sheet revised

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

dim. in mm		
	date	name
drawn	15.10.08	Fromm
appd.	15.10.08	Mankopf



title:  
**Male socket M8x1 with dip solder**

dwg no:  
**42K1A113**

part no: