

Technical specification :

Rated voltage: IEC 61076-2-104	60 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut/ screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:


Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

Contact assignment:

- 1) brown
- 3) blue
- 4) black

Part no:	Description:	Length L:	Cable:
42-10141	SAL - 8 - RK3 - RS3 - 0,3 / A1	0,3m	PVC, grey, 3x0,25mm ² Cable: 781-A12300
42-10142	SAL - 8 - RK3 - RS3 - 0,6 / A1	0,6m	
42-10143	SAL - 8 - RK3 - RS3 - 1,5 / A1	1,5m	
42-10144	SAL - 8 - RK3 - RS3 - 3 / A1	3,0m	
42-xxxxx	SAL - 8 - RK3 - RS3 - ... / A1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND	Directive 2002/95/EC RoHS compliant	Index: a 16.03.11 VF Ä3945 Coupling nut/ screw modified, spanner flats added, data sheet modified	 dim. in mm	title: Connecting cable M8x1, female connector axial - male connector axial dwg no: 42K1A035 part no: see table						
		tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td>date</td> <td>name</td> </tr> <tr> <td>drawn 13.12.07</td> <td>Franz</td> </tr> <tr> <td>appd. 13.12.07</td> <td>Mankopf</td> </tr> </table>	date	name	drawn 13.12.07	Franz	appd. 13.12.07
		date	name							
		drawn 13.12.07	Franz							
appd. 13.12.07	Mankopf									
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	