



Technical specification :

Rated voltage: IEC 61076-2-104	60 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	≥100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	≥100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut/ screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

Contact assignment:

- 1) brown
- 3) blue
- 4) black

Part no:	Description:	Length L:	Cable:
42-10153	SAL - 8 - RKW3 - RS3 - 0,3 / K1	0,3m	TPU, UL 20549, black, 3x0,25mm ² Cable: 781-K12300
42-10154	SAL - 8 - RKW3 - RS3 - 0,6 / K1	0,6m	
42-10155	SAL - 8 - RKW3 - RS3 - 1,5 / K1	1,5m	
42-10156	SAL - 8 - RKW3 - RS3 - 3 / K1	3,0m	
42-xxxxx	SAL - 8 - RKW3 - RS3 - ... / K1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 17.03.11 VF Ä3945 Coupling nut/ screw modified, spanner flats added, data sheet modified	dim. in mm <table border="1"> <tr> <td>date</td> <td>name</td> </tr> <tr> <td>drawn 13.12.07</td> <td>Franz</td> </tr> <tr> <td>appd. 13.12.07</td> <td>Mankopf</td> </tr> </table>	date	name	drawn 13.12.07	Franz	appd. 13.12.07	Mankopf	title: Connecting cable M8x1, female connector angled - male connector axial
	date		name						
	drawn 13.12.07	Franz							
	appd. 13.12.07	Mankopf							
tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%	dwg no:								
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		42K1A038							
		part no: see table							