

**Technical specification :**

Rated voltage: IEC 61076-2-104	60 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100


**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut/ screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

**Installation specification:**

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

**Contact assignment:**



Part no:	Description:	Length L:	Cable:
42-10879	SAL - 8S - RK3 - RS3 - 0,3 / G2	0,3m	TPU, UL 20549, black, 3x0,25mm <sup>2</sup> Cable: 781-G22300
42-10880	SAL - 8S - RK3 - RS3 - 0,6 / G2	0,6m	
42-10881	SAL - 8S - RK3 - RS3 - 1,5 / G2	1,5m	
42-10882	SAL - 8S - RK3 - RS3 - 3 / G2	3,0m	
42-xxxxx	SAL - 8S - RK3 - RS3 - ... / G2	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 23.03.11 VF Ä3945 Coupling nut/ screw modified, spanner flats added, data sheet modified	dim. in mm	title: <b>Connecting cable M8x1, 360°-shielding, female connector axial - male connector axial</b>		
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			date	name
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	drawn		27.10.09	Franz
		appd.		27.10.09	Burschik
<b>CONEC</b> ®		dwg no: <b>42K1A185</b>			
		part no: <b>see table</b>			