



Technical specification:

Rated voltage: IEC 61076-2-101	5pos 60 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 65, in mated condition
Temperature range: IEC 60664-1	+100°C - 30.000 h +125°C - 8.000 h +150°C - 2.000 h
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn, CuBe
Contact plating:	Nickel, gold plated
Contact carrier:	PBT GF, UL 94
Sealing:	FPM
Coupling nut:	CuZn, nickel plated
Moulding body:	Thermoplastic, elastomere, grey

Installation specification:

Recommended torque:	0,6 Nm
---------------------	--------

Contact assignment:

- 1) brown
- 2) white
- 3) blue
- 4) black
- 5) green-yellow

Part no:	Description:	Length L:	Cable:
43-10500	SAL - HT - 12 - RKW5 - 2 / S1	2m	TPE, black, 5x0,34mm ² Cable: 781-S13500
43-10501	SAL - HT - 12 - RKW5 - 3 / S1	3m	
43-10502	SAL - HT - 12 - RKW5 - 5 / S1	5m	
43-10503	SAL - HT - 12 - RKW5 - 10 / S1	10m	
43-xxxxx	SAL - HT - 12 - RKW5 - ... / S1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 14.02.11 VF Ä3909 technical specification changed, part no. cable in table added, data sheet modified	dim. in mm		title: Female connector M12x1 angled, HT	
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%	drawn 08.03.07 Burschik appd. 08.03.07 Mankopf	dwg no: 43K1A073		
	general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm			part no: see table	
	<small>THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH</small>				