



SECTION A-A

11.6	7.5	14.3	5055960801	8
9.1	5.0	11.8	5055960601	6
6.6	2.5	9.3	5055960401	4
C	B	A	製品番号 MATERIAL NO.	極数 CIRCUIT

注記  
**NOTES**  
 1.適合端子 :5055979\*00,561348\*00,561349\*00,593708\*00  
 APPLICABLE TERMINAL:5055979\*00,561348\*00,561349\*00,593708\*00  
 2.適合リテーナー :505594 シリーズ  
 APPLICABLE RETAINER:505594 SERIES  
 3.材料 MATERIAL  
 ハウジング:ポリアミド(PA66 UL94V-0 黒)  
 HOUSING :POLYAMIDE(PA66 UL94V-0 BLACK)  
 ピン:黄銅,ニッケル下地 1μm Min. 錫メッキ(半光沢)1μm Min.  
 PIN :BRASS,Sn(MATTE) 1 MICROMETER MINIMUM  
 OVER Ni PLATING 1 MICROMETER MINIMUM

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC NO: 117526 DRWN: HKOBAYASHI CHK'D: SAKIYAMA APPR: TKANEKO	2017/06/08	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION UNITS	SCALE		
	2017/06/28	ANGULAR TOL ± 3.0 °		MM	5:1		
	2017/06/29	4 PLACES ± 0.2	3 PLACES ± 0.2	DRWN BY	DATE		
	2 PLACES ± 0.2	1 PLACE ± 0.2	0 PLACES ± 0.2	HKOBAYASHI	2017/06/08		
A REV	EC NO: 117526 DRWN: HKOBAYASHI CHK'D: SAKIYAMA APPR: TKANEKO	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRAWING SIZE	THIRD ANGLE PROJECTION	MUO 2.5 WW DUAL ROW CONNECTOR HOUSING ASSEMBLY PRODUCT CUSTOMER DRAWING	
				A3			
				505596	SEE CHART		GENERAL MARKET
				5055960000-SD	PSD		000