



NOTES

- 適合ハウジング アッセンブリ : 505596****
APPLICABLE HOUSING ASS'Y : 505596****
- 使用材料 : 銅合金 (t=0.15),
錫めっき 0.7 MICROMETER MINIMUM
MATERIAL : COPPER ALLOY
PRE-TINNED 0.7 MICROMETER MINIMUM
- △3 トレードマーク : MXプラス1文字の製造工場を示す。
アルファベットにて表示。
但し"J"はJAPANを示す。(例:MXJ)
FORMED BY MX AND 1 MORE LETTER OF ALPHABET
WHICH MEAN THE MANUFACTORY.
BUT "J" MEANS JAPAN. (TO TRADE MARK) (e.g. MXJ)
- 適用電線 : SHKV0.3-0.5 , AWG #22 ~ #20
APPLICABLE WIRE : SHKV0.3-0.5 , AWG#22 ~ #20
- 被覆外径 : φ1.25-2.0
INSULATION OUTSIDE DIAMETER : φ1.25-2.0
- 製品仕様及び取り扱いについては、製品仕様書'5055960000-PS-000'及び、
コネクタ取扱説明書'5055960000-AS-00*'を参照願います。
PLEASE REFER TO PRODUCTS SPECIFICATION '5055960000-PS-000'
AND USER'S MANUAL '5055960000-AS-00*'.
- 圧着仕様については、圧着仕様書'5055970000-CS-000'を
参照願います。
PLEASE REFER TO CRIMPING SPECIFICATION
'5055970000-CS-000'.
- ATS-57427-0000 圧着視覚教材を参照願います。
PLEASE REFER TO CRIMPING VISUAL AND
ATS-57427-0000.

φ1.25-2.0mm	SHKV0.3-0.5	5055979100	バラ状 LOOSE
	AWG #22-20	5055979000	連鎖状 CAHIN
絶縁被覆外径範囲 INS. RANGE	適用電線範囲 WIRE RANGE	製品番号 MATERIAL NO.	端子形状 FORM

QUALITY SYMBOLS ▽A = 0 ▽E = 0 ▽F = 0 ▼ = 0 ▽C = 0 ⊠ = 0 ■ = 0 ▽ = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				QUALITY SYMBOLS ▽A = 0 ▽E = 0 ▽F = 0 ▼ = 0 ▽C = 0 ⊠ = 0 ■ = 0 ▽ = 0		DIMENSION UNITS MM		SCALE 10:1										
	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 3.0 °		DRWN BY HKOBAYASHI		DATE 2017/06/08		PRODUCT CUSTOMER DRAWING												
	4 PLACES ± 0.2 3 PLACES ± 0.2 2 PLACES ± 0.2 1 PLACE ± 0.2 0 PLACES ± 0.2		CHK'D BY SAKIYAMA		DATE 2017/06/28						SERIES 505597		MATERIAL NUMBER SEE TABLE		CUSTOMER GENERAL				
	EC NO: 117526 DRWN: HKOBAYASHI CHK'D: SAKIYAMA APPR: TKANEKO		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPR BY TKANEKO		DATE 2017/06/29		DRAWING SIZE A3		THIRD ANGLE PROJECTION		DOCUMENT NUMBER 5055970000-SD		DOC TYPE PSD		DOC PART 000		SHEET NUMBER 1 OF 1