




Bluetooth® AT Data Module

BTM430/431



The BTM430 and BTM431 Bluetooth® modules from Laird Technologies have been designed to meet the needs of developers who wish to add robust, short range Bluetooth data connectivity to their products. They are based on the market leading Cambridge Silicon Radio BC04 chipset, providing exceptionally low power consumption with outstanding range.

With a footprint as small as 12.5 mm x 18.0 mm for the BTM430 and best of class, low-power operation, these modules are the ideal choice for applications where designers need both performance and minimum size. For maximum flexibility in systems integration, the modules are designed to support a separate power supply for I/O.

To aid product development and integration, Laird Technologies has integrated a complete Bluetooth protocol stack within the modules, including support for the Bluetooth Serial Port Profile. The modules are fully qualified as Bluetooth End Products, allowing designers to integrate them within their own products with no further Bluetooth Qualification. They can then list and promote their products on the Bluetooth website free of charge.

A comprehensive AT command or Multipoint Packet Protocol is included, which simplifies firmware integration. This ensures that the choice of Laird Technologies Bluetooth modules guarantees the fastest route to market.

Features and Benefits

- Bluetooth v2.0+EDR
- Adaptive frequency hopping to cope with interference from other wireless devices
- External or internal antenna options
- Comprehensive AT interface for simple programming
- Multipoint Packet Protocol supporting up to 3 connections
- Bluetooth End Product Qualified
- Compact size
- Class 2 output – 4 dBm
- Low power operation
- UART interface
- PCM and SCO for external codec
- GPIO lines under AT control
- Wi-Fi co-existence

Application Areas

- Embedded devices
- Phone accessories
- Security devices
- Medical and telehealth devices
- Aftermarket automotive applications
- Bluetooth advertising
- ePOS

global solutions: local support.

USA: +1.800.492.2320
Europe: +44.1628.858.940
Asia: +852.2268.6567

wirelessinfo@lairdtech.com
www.lairdtech.com/wireless



Bluetooth® AT Data Module

BTM430/431

CATEGORIES	FEATURE	IMPLEMENTATION
Wireless Specification	Bluetooth®	Version 2.0+EDR
	Frequency	2.402 – 2.480 GHz - Class 2
	Max Transmit Power	+4 dBm (at antenna pad – BTM430) +4 dBm (from integrated antenna – BTM431)
	Receive Sensitivity	Better than -84 dBm
	Range	Up to 30 meters
	Data Rates	Up to 2.1 Mbps (over the air)
Host Interface	UART	Supports CTS, RTS, DTR, DSR, DCD and RI
User Interface	GPIO	8 lines (shared)
Profiles		SPP –Serial Port Profile FTP Client OBEX Client HSP (partial) HFP (partial) DUN
Supply Voltage	Supply	3.0 V to +3.3 V
	I/O	1.7 V to +3.6 V (independent of V _{CC})
Power Consumption	Current Consumption	Less than 40 mA during SCO transmission Idle (sleep) < 1 mA
Coexistence / Compatibility	802.11 (Wi-Fi)	2 wire and 3 wire schemes supported
Connections	External Antenna	50 Ohm matched SMT pad BTM430
	Internal Antenna	Multilayer ceramic – BTM431
Protocols		AT Command Set
Physical	Dimensions	12.5 mm x 18.0 mm x 3.4 mm (external antenna – BTM430)
		12.5 mm x 22.0mm x 3.4 mm (integrated antenna – BTM431)
Environmental	Operating Temperature	-40° C to +85° C
	Storage Temperature	-40° C to +85° C
Miscellaneous	Lead Free	Lead-free and RoHS compliant
	Warranty	1 Year
Developmental Tools	Development Kit	Development board and software tools
Approvals	Bluetooth	End Product Approved
	FCC/IC & CE	BTM430 – Limited Modular Approval BTM431 – Full Modular Approval

Ordering Information

BTM430	Bluetooth AT Data Module (external antenna)
BTM431	Bluetooth AT Data Module (with integrated antenna)
DVK-BTM430	Development Kit (external antenna)
DVK-BTM431	Development Kit (with integrated antenna)

The details contained within the document are subject to change. Download the product specification from www.lairdtech.com/wireless for the most current specification.

LWS-DS-BTM430-431 0313

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.