

Innovative **Technology** for a **Connected** World

900 & 1800 MHz MicroSphere Antenna



900 & 1800 MHz OMNI-DIRECTIONAL IN-BUILDING ANTENNA

The widespread use of cellular phones and wireless network applications inside buildings has increased the need for antenna systems that can provide considerable gain over traditional dipole antennas.

Laird Technologies' in-building wireless antennas are particularly applicable in environments where aesthetics and wide angle coverage are necessary for successful wireless deployment. Their surprisingly small size allow the antennas to be hidden almost anywhere, providing an invisible solution for most applications.

FEATURES

- Surprisingly small size allows it to be hidden almost anywhere, providing an invisible solution for many applications.
- The field pattern is toroidal, providing omni-directional coverage in any plane around the long axis of the antenna, and two lobes in any plane parallel to the long axis.

MARKETS

 The omni-directional pattern is suited to a variety of uses, including handheld devices, in-building systems or other applications where mobility is a factor.

SPECIFICATIONS		
Element Type	Microstrip	
Frequency Range	880 – 960 MHz 1710 – 1880 MHz	
Peak Gain	3 dBi	
Polarization	Linear	
Impedance	50 ohms	
Maximum Input Power	50 watts	
VSWR (Min. Performance)	1.5:1	
Dimensions (L x W x H)	12.9 x 15.6 x 0.25 cm	
Housing	Acrylic	
Operating/Storage Temperature	-40° to +70°C	

MODEL#	REFERENCE #	CONNECTOR
IF9018-SF00	CAF94126	SMA Female Panel

MOUNTING OPTIONS

• Includes nylon screws for mounting to ceiling tile of finished ceiling

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Innovative **Technology** for a **Connected** World

900 & 1800 MHz MicroSphere Antenna

