

## **S888P Series Single Patch Antenna**







## **GSM LINEARLY AND DUAL POLARIZED ANTENNA**

Laird S888P series of GSM microcell antennas both employ a single broadband microstrip patch to provide a minimum of 8 dBi gain and a nominal 55 by 60° pattern

The S888HVP12NF is designed for polarization diversity applications with separate coaxial feeds provided for both horizontal and vertical polarization. Isolation between polarization is nominal 15 dB. These antennas are housed in a rugged low profile, UV stable polycarbonate radome which is weather resistant for outdoor applications.

This antenna is available in grey, beige, or white radomes; although they can be painted as required. Mounting configurations include a standard wall mount or articulating version.

## **MARKETS**

WiMAX

PARAMETER	SPECIFICATION
Frequency (MHz)	880 - 960
VSWR	1.5:1
Gain (dBi)	8
E-Plane (3 dB beamwidth)	65°
H-Plane (3 dB beamwidth)	70°
Impededance (Ohms)	50
Weight lb (kg)	2.2 (1.0)
RF Connector (f)	N, 25 cm low loss coaxial pigtail provided
Dimensions in (cm)	12 x 12 x 1.75 (30.5 x 30.5 x 4.4)
Polarization	S888P12NF vertical S888HVP12NF horizontal and vertical

Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia:

IAS-AsiaSales@lairdtech.com

Middle East & Affrica: +44.1628.858941 IAS-MEASales@lairdtech.com

www.lairdtech.com

ANT-DS-S888P 0317

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable, All specifications are subject to change without notice. Responsibility for the use and application of Laira Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies and its not be liable for into the liable for into