



tolerances according to DIN ISO 2768 m

| Magnetic properties                  | Conditions   | Min    | Typ | Max | Unit |
|--------------------------------------|--|--------|-----|-----|------|
| Pull-In excitation (Reference value) | Reed switch unmodified<br>measured in coil- "define operation" | 25     |     | 30  | AT   |
| Test-Coil                            | Reed switch unmodified   | KMS-01 |     |     |      |

| Contact data 52            | Conditions   | Min     | Typ | Max | Unit |
|----------------------------|--|---------|-----|-----|------|
| Contact-No.                |  | 52      |     |     |      |
| Contact-form               |  | A       |     |     |      |
| Contact-material           |  | Rhodium |     |     |      |
| Contact rating             | consider any combination of V & A<br>AC RMS 70 VA    |         |     | 50  | W    |
| Switching voltage          | DC or Peak AC  |         |     | 350 | V    |
| Switching current          | DC or Peak AC  |         |     | 0,5 | A    |
| Carry current              | DC or Peak AC  |         |     | 2,5 | A    |
| Contact resistance static  | Measured with 40% overdrive<br>Start Value           |         |     | 150 | mOhm |
| Contact resistance dynamic | Maximum value 1,5 ms after excitation<br>Start Value |         |     | 200 | mOhm |
| Insulation resistance      | RH <45 %, 100 V test voltage                         | 10      |     |     | GOhm |
| Breakdown voltage (<36 AT) | according to IEC 255-5                               | 500     |     |     | VDC  |
| Operate time incl. bounce  | measured with 40% overdrive                          |         |     | 1,1 | ms   |
| Release time               | measured with no coil excitation                     |         |     | 0,1 | ms   |
| Capacity                   | @ 10 kHz across open switch                          |         | 0,5 |     | pF   |

| Contact dimensions | Conditions                     | Min | Typ  | Max | Unit |
|--------------------|--------------------------------|-----|------|-----|------|
| Overall length     | Tolerance according to drawing |     | 55,4 |     | mm   |
| Glass body length  | Tolerance according to drawing |     | 21   |     | mm   |

| Environmental data    | Conditions                  | Min | Typ | Max | Unit |
|-----------------------|-----------------------------|-----|-----|-----|------|
| Shock                 | 1/2 sine wave duration 11ms |     |     | 50  | g    |
| Vibration             | from 10 - 2000 Hz           |     |     | 20  | g    |
| Operating temperature |                             | -40 |     | 130 | °C   |
| Storage temperature   |                             | -55 |     | 130 | °C   |
| Soldering temperature | wave soldering max. 5 sec   |     |     | 260 | °C   |