



DEUTSCH CTJ SERIES COMMON TERMINATION SYSTEM

AS81714 Series II Qualified Products Offer Robust and Highly Reliable Wire Termination in Demanding Environments

DEUTSCH CTJ SERIES

Common Termination Systems — AS81714 Series II

Contents

INTRODUCTION	3
<hr/>	
MODULES	
CTD and CTJ1 Power Distribution and Feedback Modules	6
CTJ4 Series Electronic Component Modules	9
CTJ5 Series Board-Mount/Pluggable Modules	20
CTJ6 and CTJ9 Series Plug and Receptacle Connectors	23
CTJ7 and CTG Series Grounding Modules and Junctions	27
CTL, CTM, and CTN Series In-Line Junctions	30
Composite In-line Junctions	33
Adapter Junctions	36
<hr/>	
RAILS	
CTJ2 Series Metallic Single-Module Rails	38
CTJ3 Series Metallic Rails	39
DCR Series Composite Rails	41
<hr/>	
CONTACTS AND TOOLING	
Socket Contacts	43
CTJ Series Tooling	44
<hr/>	
CROSS REFERENCE	
DEUTSCH CTJ to AS8171	47



RUGGED

- Meets SAE-AS81714 and MIL-T-81714 requirements
- Single integrated bus bar helps ensure long mechanical and electrical life

ENVIRONMENTALLY SEALED

- Resists fluids commonly found in aerospace and defense applications
- Helps prevent foreign object debris issues

EASY TO USE

- Insertable modules that can be easily removed and reinserted into rails with tools

APPLICATIONS

- Commercial Air
- Space
- Military Ground
- Military Aerospace



The DEUTCH CTJ Series common termination system from TE Connectivity (TE) is a system of wires and components that are interconnected to one another by the use of a standard AS39029 socket contact only. This eliminates the need for pin contacts which are located in the mating components. Our single-pin bus bar design makes this connector series the most ruggedized in the industry. There are multiple design options available to customize the modules, junctions, splices and rails available in Mil Spec-approved AS81714 Series II.


TE Advantage

DEUTSCH AS39029 Contacts. All assemblies—modules, splices, etc.—are supplied with DEUTSCH AS39029 socket contacts, which are designed to meet AS39029 standard for ruggedness and vibration resistance.

Customization. Products can be customized to help meet your specific needs.

Single Rail Assembly. We offer rail assemblies for single-mount components.

Easy Assembly. We offer easy insertion and removal of single rails inside multimodule assemblies.



Environmentally Sealed Grommet Assembly

Housing

Wire-Applied AS39029 Socket Contact

Integral Pin Contact

Integrated Bus Bar (Customizable and Single-Pin Bus Bar Design)

CTD Bussing Modules for power distribution.

CTJ1 Feedback Modules with various bussing arrangements.

CTJ4 Electronic Component Modules designed to the electronic requirements of MIL-T-81714/62. Modules are available with a variety of diodes, resistors, capacitors, and fuses, with both M81714/62 equivalents and additional configurations.

CTJ5 Board-Mount Modules include solder pin contacts for direct mounting to pc boards and flex cable. By eliminating the need for a mounting rail, CTJ5 modules provide a flexible and compact solution.

CTJ6 Plug and CTJ9 Receptacle Connectors provide a small, lightweight method of connecting/disconnecting multiple wires. Available in flange-mount and in-line versions.

CTJ7 Grounding Modules, using either flange mount or stud mount, provide sealed multiwire grounding solutions.

CTJ2 Metallic Rails are aluminum alloy and designed to hold one single module or two half-size modules.

CTJ3 Metallic Rails use aluminum alloy and stainless steel clips. They are available with a variety of finishes and sizes ranging from 2 to 40 inches.

DCR Composite Rails are a lightweight alternative to CTJ3 rails, offering up to 48% weight savings and available in lengths from 2 to 20 inches.

Junctions and Splices

CTL, CTM and CTN In-Line Junctions connect two to four wires in-line and multijunctions for housing and sealing individual components. The CTL is an in-line junction for single wires. The CTM connects and buses two, three, or four wires. The CTN series connects contacts electrically with diodes, capacitors, fuses, resistors, or integrated circuits.

Composite In-Line Junctions are composite versions of the CTL, CTM, and CTN series.

CTG Grounding Junctions provide a simple method of terminating wire to ground using standard AS39029 contacts.



CTJ Series General Specifications

The CTJ series meets the requirements of SAE-AS81714.

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 110,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Physical Shock: 78 g in each of the 3 mutually perpendicular planes

Vibration: Maintains continuity to minimize mechanical or physical damage during or after vibration following vibration levels

Level 1—34 minutes per axis

20–90 Hz at 6 dB/oct. rise
90–300 Hz at 1.0 g²/Hz
300–2000 Hz at 6 dB/oct. fall

Level 2—14 minutes per axis

20–40 Hz at 6 dB/oct. rise
40–350 Hz at 0.5 g²/Hz
350–2000 Hz at 6 dB/oct. fall
No discontinuities greater than 1 microsecond

Corrosion: 48 hours of salt spray

Magnetic Permeability: 2.0 μ max.

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline

Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Metal Rails (CTJ2 and CTJ3): Aluminum alloy, nickel plated (standard). Also available with anodized, olive drab cadmium, or clear finishes. Stainless steel clips

DCR Rails: Composite

Contact Resistance (at 25°C)

Meets AS39029 paragraph 3.5.4

Wire Size	Test Current	Voltage Drop
22 AWG	5 A	73 mV
20 AWG	7.5 A	55 mV
16 AWG	13 A	50 mV
12 AWG	23 A	42 mV

Usable Wire Size

Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26–22	5 A
Size 20	24–20	7.5 A
Size 16	16–20	13 A
Size 12	14–12	3 A

Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109
12	0.097	0.142



DEUTSCH CTD and CTJ1 Power Distribution and Feedback Modules

EASY TO USE


- Busses 6 to 20 contacts in a small area
- Internal bus bars are configured to allow connections of various combinations of wires

RUGGED

- Uses a rugged A39029 socket contact mated to one-piece (cold-headed) internal pin bus bars
- Excellent vibration resistance
- Environmentally sealed

CONVENIENT

- Modules fit in single, multiple, composite or metal rails with multiple mounting options
- CTD distribution modules accommodate different sizes of contacts within the same bus



CTD power distribution and CTJ feedback modules for rugged, environmentally sealed bussing of wires.

Specifications

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 110,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Vibration: Maintains continuity to minimize mechanical or physical damage during or after vibration levels stated in tested specifications

Corrosion: 48 hours of salt spray

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline

Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Gold over copper

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed



Contact Resistance (at 25°C)

Meets AS39029 paragraph 3.5.4

Wire Size	Test Current	Voltage Drop
22 AWG	5 A	73 mV
20 AWG	7.5 A	55 mV
16 AWG	13 A	50 mV
12 AWG	23 A	42 mV

Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109




Usable Wire Size

Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26-22	5 A
Size 20	24-20	7.5 A
Size 16	16-20	13 A
Size 12	14-12	3 A


CTD Series

Distribution Bussing Arrangements




Part No.	CTD126E01A	CTD160E01F	CTD126E02E	CTD1062E05A
No. of Busses	1	1	2	5
Contacts per Bus	2 Size 12 6 Size 16 —	2 Size 16 6 Size 20 —	1 Size 12 3 Size 16 —	1 Size 12 1 Size 20 1 Size 22
Distribution Bus	26	60	26	062
Bussing Arrangement	01A	01F	02E	05A

CTD Outline Dimensions



Part Numbering System





CTJ1 Series

Feedback Bussing Arrangements


Size 22 Contacts Quantity: 20						
	No. of Busses	1	2	5	6	10
Bus Code	01C	02D	05E	06B	10A	04F

Size 20 Contacts Quantity: 12					
	No. of Busses	1	2	3	4
Bus Code	01B	02C	03D	04A	06E


Size 16 Contacts Quantity: 6			
	No. of Busses	1	2
Bus Code	01D	02B	03A

Size 12 Contacts Quantity: 6			
	No. of Busses	1	2
Bus Code	01E	02A	03B

CTJ1 Outline Dimensions



Part Numbering System



Ordering Information

Module	Part No.
Size 22	CTJ122Exxx-yyy
Size 20	CTJ120Exxx-yyy
Size 16	CTJ116Exxx-yyy
Size 12	CTJ112Exxx-yyy

xxx = bussing arrangements
yyy = modification codes



DEUTSCH CTJ4 Series Electronic Component Modules

CONVENIENT

- May be placed near transient suppression devices that they are designed to protect
- Each module houses small printed circuit boards incorporating diodes and resistors
- Uses crimp-tool terminations and a housing system for discrete components and circuits
- Lightweight composite technology for weight-saving solutions

ROBUST

- Fluid resistant in most military or aerospace environments
- Input/output wiring is sealed with silicone rubber grommet to help protect against environmental hazards
- Designed to the electronic requirements of MIL-T-81714/62

VERSATILE

- Available with a variety of diodes, resistors, capacitors, and fuses, with both M81714/62 equivalents and additional configurations



CTJ4 electronic component modules are designed to the electronic requirements of MIL-T-81714/62. Modules are available with a variety of diodes, resistors, capacitors and fuses, with both M81714/62 equivalents and additional configurations.

Specifications

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 100,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Thermal Shock (AS81714 paragraph 3.5.5): After cycling the module between -55°C and +200°C, they will meet all applicable electrical and mechanical requirements

Vibration (AS81714 paragraph 3.5.8): items furnished under this specification shall not be damaged and there shall be no loosening of parts due to vibration and no interruption of electrical continuity longer than one microsecond in duration during vibration testing

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline

Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Gold over copper

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Common Termination Systems



Usable Wire Size


Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 20	24-20	7.5 A
Size 12	14-12	3 A

Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
20	0.040	0.083
12	0.097	0.142

Part Numbering System



513 To Mil Standard to Withstand Fluid Immersion to MS55

090 Less Contacts

6148 MS55 Resilient Material, Omit Contacts, Sealing Plugs, and Insertion/Removal Tool

4010 Vacuum Bake


7065 Insert Material (18D) Methyl Vinyl Fluoro Silicone, Color (16) Contact Cavity ID to Be Yellow per MIL-T-81714

Ordering Information

Module	Part No.
Size 20	CTJ420E-xxx
Size 12	CTJ412E-xxx


xxx = modification code electronic circuits.

Outline Dimensions







CTJ4 Circuit Configurations




CTJ412E001
One 15 A, 125 V Fuse




CTJ420E002
Five 150 Ohm Resistors, 1/4 W




CTJ420E003
Two 150 Ohm Resistors, 1/4 W
One 10 uF Capacitor, 35 WVDC




CTJ420E004
One W110 VARO Rectifier




CTJ420E005
Five JANTX 1N4246 or
JANTX 1N5616 Diodes




CTJ420E006
Three JANTX 1N6054A
Zener Diodes




CTJ420E007
Three JAN 1N3613 Diodes
Two JAN 1N645 Diodes




CTJ420E008
Four JANTX 1N3613 Diodes




CTJ420E009
Six JANTX 1N5618 Diodes




CTJ420E010
Four JANTX 1N5618 Diodes
Four JANTX 1N4478 Zener Diodes




CTJ420E011
Five JANTX 1N5618 Diodes




CTJ420E012
Five 10 k Ohm Resistors, 1/10 W



CTJ420E013
Four JANTX 1N5618 Diodes
One 200 Ohm Resistor, 1/8 W




CTJ420E014
Two JANTX 1N5618 Diodes
Two 10 k Ohm Resistors, 1/10 W




CTJ420E015
Two JANTX 1N5618 Diodes
One 10 k Ohm Resistor, 1/10 W
One 110 Ohm Resistor, 1/10 W




CTJ4 Circuit Configurations




CTJ420E016
Five JANTX 1N5618 Diodes




CTJ420E017
One JANTX 1N5618 Diode
One JANTX 1N4478 Zener Diode




CTJ420E019
One 1.10 k Resistor, 1/10 W
One 1.40 k Resistor, 1/10 W
One 20 k Resistor, 1/10 W
Two 10 k Resistors, 1/10 W




CTJ420E020
Two 3.6 k Resistors, 1/10 W
One 100 k Resistor, 1/10 W
Two 1 μ F Capacitors, 50 WVDC




CTJ420E021
Three JANTX 1N5550 Diodes




CTJ420E022
Six JANTX 1N5809 Rectifiers




CTJ420E026
Five JANTX 1N5620 Diodes




CTJ420E027
Two 66099-108 or
66139-101 ISO Cubes
One Zero Ohm Molded
Jumper Wire




CTJ420E028
Eight JANTX 1N5550 Diodes




CTJ420E029
Two 10 k Resistors, 1/10 W
Two 1.43 k Resistors, 1/10 W
One JANTX1N4954 Zener Diode




CTJ420E030
One 10 k Resistor, 1/10 W
Four 20 k Resistors, 1/10 W




CTJ420E031
Two 10 k Resistors, 1/10 W
Two 20 k Resistors, 1/10 W



CTJ420E032
Two 10 k Resistors, 1/10 W
One 1430 Resistor, 1/10 W
One 1110 Resistor, 1/10 W




CTJ420E033
One 2 k Resistor, 1/10 W
One 357 k Resistor, 1/10 W
One 196 k Resistor, 1/10 W




CTJ420E034
Five 150 Resistors, 1/10 W




CTJ4 Circuit Configurations




CTJ420E035
Five 10.2 k Resistors, 1/10 W




CTJ420E036
Five 2.8 k Resistors, 1/10 W




CTJ420E037
Five 23.2 k Resistors, 1/20 W




CTJ420E038
Five 24.9 k Resistors, 1/20 W




CTJ420E039
Five 41.2 k Resistors, 1/20 W




CTJ420E040
Five 49.9 k Resistors, 1/20 W




CTJ420E041
Five JANTX 1N5550 Diodes




CTJ420E042
Five JANTX 1N5418 Diodes




CTJ420E043
Five JANTX 1N827 Zener Diodes




CTJ420E044
Five JANTX 1N5552 Diodes




CTJ420E045
Two 40 k Resistors, 1/10 W
Two 50 k Resistors, 1/10 W




CTJ420E047
Three 60.4 Resistors, 2 W



CTJ420E051
Three JANTX 1N5618 Diodes




CTJ420E052
Three JANTX 1N5618 Diodes




CTJ420E054
Four JANTXV 1N5416 Diodes




CTJ4 Circuit Configurations




CTJ420E055
Two 3.3 k Resistors, 1/4 W
Two 5.1 k Resistors, 1/4 W




CTJ420E056
One 2 A Fuse
Two JANTXV 1N4965
Zener Diodes
Four JANTXV 1N5416 Diodes




CTJ420E059
Four 150 Resistors, 1/4 W




CTJ420E060
One JANTX 1N5618 Diode




CTJ420E061
Four JANTXV 5416 Diodes




CTJ420E100
Six JANTX 1N5618 Diodes




CTJ420E101
Six JANTX 1N3613 Diodes




CTJ420E102
Two 20 k Resistors, 1/4 W
Two 8.45 k Resistors, 1/4 W




CTJ420E109
One MIL-T-27/172-45 (2 A)
Transformer




CTJ420E112
Five 150 Resistors, 1/4 W




CTJ420E113
Six 4.7 k Resistors, 1/4 W




CTJ420E114
Five JANTX 1N4247 Diodes



CTJ420E115
Five 6.2 k Resistors, 1/4 W




CTJ420E116
Five 3 k Resistors, 1/4 W




CTJ420E117
Five 5 A Fuses, 125 V




CTJ4 Circuit Configurations




CTJ420E126
Two 49.9 k Resistors, 1/4 W
Two 28.7 k Resistors, 1/4 W




CTJ420E128
Two JANTX 1N6052A
Zener Diodes




CTJ420E129
One JANTX 1N5618 Diode
Three 10 k Resistors, 1/8 W




CTJ420E132
Five 150 Resistors, 1/2 W




CTJ420E134
Three 150 Resistors, 1/2 W
One 51 Resistor, 1/2 W
One 820 Resistor, 2 W




CTJ420E135
Four JANTX 1N5551 Diodes




CTJ420E136
Four JANTX 1N5619 Diodes
One 200 k Resistor, 1/2 W




CTJ420E137
Six JANTX 1N6419-1 Diodes




CTJ420E138
Five JANTX 1N5618 Diodes




CTJ420E139
One 1 k Resistor, 1 W
One JANTXV 1N5550 Diode




CTJ420E140
Five 5.1 k Resistors, 1/10 W




CTJ420E145
Two 100 k Resistors, 1/4 W
Two 7.5 k Resistors, 1/4 W



CTJ420E146
Five JANTX 1N5618 Diodes




CTJ420E149
Three JANTX 1N5616 Diodes
Two JANTX 1N4461 Zener Diodes




CTJ420E155
Two 1 k Resistors, 1/4 W




CTJ4 Circuit Configurations




CTJ420E157
Two 120 Resistors, 1/4 W




CTJ420E161
Two JANTX 1N6059A
Zener Diodes




CTJ420E162
Two JANTX 1N6067A
Zener Diodes




CTJ420E163
Two JANTX 1N6045A
Zener Diodes




CTJ420E164
One JANTX 2N2323A SCR




CTJ420E166
Two ON Semiconductor
MR756 Diodes




CTJ420E167
Five JANTX 1N5351B Zener Diodes




CTJ420E170
Five 249 Resistors, 1/4 W




CTJ420E172
Two TELEDYNE M93F-1 ISO Cubes




CTJ420E173
Five JANTX 1N5418 Diodes




CTJ420E174
Five 100 k Resistors, 1/10 W




CTJ420E176
Five 470 Resistors, 1/2 W



CTJ420E177
Six JANTX 1N4454-1 Diodes




CTJ420E184
One 1 μF Capacitor, 50 VDC




CTJ420E186
Two TELEDYNE M92F-3 ISO
Cubes




CTJ4 Circuit Configurations




CTJ420E187
Five 7 A Fuses, 125 V




CTJ420E189
Two JANTX 1N5618 Diodes




CTJ420E191
One INTERSIL HA-5002/883
Current Buffer




CTJ420E192
Five 1 k Resistors, 1/4 W




CTJ420E196
Five 127 Resistors, 1/8 W




CTJ420E197
Five 5 A Fuses, 125 V




CTJ420E301
Four 2.7 k Resistors, 1/4 W
One 56 Resistor, 1/2 W




CTJ420E302
Four 2.7 k Resistors, 1/4 W
One 3.9 k Resistor, 1/4 W




CTJ420E303
One 2.7 k Resistor, 1/4 W
One 1.8 k Resistor, 1/4 W
One 5.1 k Resistor, 1/4 W
One 3.3 k Resistor, 1/4 W
Three JANTX 1N5711 Diodes




CTJ420E304
Two 120 Resistors, 1/2 W
Two 2.7 k Resistors, 1/4 W




CTJ420E305
Two 2.7 k Resistors, 1/4 W
Two 3.9 k Resistors, 1/4 W




CTJ420E306
Two 5.1 k Resistors, 1/4 W
Two 8.2 k Resistors, 1/4 W
Two JANTX 1N5711 Diodes



CTJ420E311
Six JANTX 1N649-1 Diodes




CTJ420E313
Five 100 k Resistors, 1/4 W




CTJ420E314
Six JANTX 1N4007 Diodes




CTJ4 Circuit Configurations




CTJ420E316
Two 1 k Resistors, 1/2 W
Two JANTX 1N4007 Diodes




CTJ420E317
Five JANTX 1N4007 Diodes




CTJ420E320
Three JANTX 1N5550 Diodes




CTJ420E321
Four JANS 1N5811 Diodes




CTJ420E322
Five 4.7 k Resistors, 1/2 W




CTJ420E326
One 100 Resistor, 1/4 W
One 300 Resistor, 1/4 W
One 573 Resistor, 1/4 W
One 10 μ F Capacitor, 35 WVDC




CTJ420E330
One 1000 pF Capacitor, 100 VDC




CTJ420E332
Five 10 k Resistor, 1/10 W




CTJ420E333
Two 2 k Resistors, 1/4 W
Two JANTX 1N6677-1 Diodes




CTJ420E334
Two 10 k Resistors, 1/8 W
Two 3 k Resistors, 1/8 W




CTJ420E336
Two PIV = 600 V, $I_{FSM} = 200$ A Diodes




CTJ420E337
One 1 k Resistor, 1/4 W
Three 10 k Resistors, 1/4 W
One 300 k Resistor, 1/4 W



CTJ420E338
Four JANTX 1N3613 Diodes




CTJ420E339
One 100 Resistor, 1/2 W
Four JANTX 1N3613 Diodes




CTJ420E340
Two 2.2 k Resistors, 1/2 W
Two 240 k Resistors, 1/2 W




CTJ4 Circuit Configurations



CTJ420E341
Two CTJ420E341 Resistors, 1 W



CTJ420E342
Four 1.5 k Resistors, 1 W



CTJ420E347
Twelve 4.99 k Resistors, 1/8 W



DEUTSCH CTJ5 Series Board-Mount/Pluggable Modules

CONVENIENT


- Mounts on pc board or flat flex cable
- Uses AS39029 socket contacts to accept wiring and connect through to straight solder pin contacts
- Uses a standard insertion/removal tool
- Light weight

RUGGED

- Fluid resistant in most aerospace environments
- Available to operate in hydraulic fluid immersion

EASY TO USE

- Straight solder pin contacts allow modules to be soldered to pc boards or plugged into specialized components
- All contacts are discrete, mainly used to take single leads from a PC board out to wire



Fast, cost-effective termination of pc boards, flat flex cable, and electromechanical components.

Specifications

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 110,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11):

5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Physical Shock: 78 g in each of the 3 mutually perpendicular planes

Vibration: Maintains continuity to minimize mechanical or physical damage during or after vibration following vibration levels

Level 1—34 minutes per axis

20–90 Hz at 6 dB/oct. rise
90–300 Hz at 1.0 g²/Hz
300–2000 Hz at 6 dB/oct. fall

Level 2—14 minutes per axis

20–40 Hz at 6 dB/oct. rise
40–350 Hz at 0.5 g²/Hz
350–2000 Hz at 6 dB/oct. fall
No discontinuities greater than 1 microsecond

Corrosion: 48 hours of salt spray

Magnetic Permeability: 2.0 μ max.

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline



Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Gold over copper

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Contact Resistance (at 25°C)

Meets AS39029 paragraph 3.5.4

Wire Size	Test Current	Voltage Drop
22 AWG	5 A	110 mV
20 AWG	7.5 A	83 mV
16 AWG	13 A	74 mV

Usable Wire Size


Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26-22	5 A
Size 20	24-20	7.5 A
Size 16	16-20	13 A


Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109


Modules



Size 22
20 Size 22 Contacts




Size 20
12 Size 20 Contacts




Size 16
6 Size 16 Contacts

Pin Arrangements






Outline Dimensions



Part Numbering System



Ordering Information

Module	Part No.
Size 22	CTJ522E20-xxx
Size 20	CTJ520E12-xxx
Size 16	CTJ516E6-xxx

xxx = modification code.



DEUTSCH CTJ6 and CTJ9 Series Plug and Receptacle Connectors

SAVE SPACE AND WEIGHT

- Small, lightweight modules
- Flange mounting or in-line mounting for simultaneous connect/disconnect of many wires

VERSATILE

- Flange or in-line mountable
- Backpack configurations available for receptacle connectors
- Available with optional strain relief
- PCB tail contacts or with crimp backpack

RELIABLE

- Cork in bottle interfacial seal between the mating halves
- Environmentally resistant

EASY MATING/UNMATING

- Audible click indicates proper mating
- Simple tool allows unmating



Small, lightweight modules designed for flange mounting or in-line mounting for simultaneous connect/disconnect of many wires.

Specifications

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 100,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Thermal Shock (AS81714 paragraph 3.5.5): After cycling the modules between -55°C and +200°C, they will meet all applicable electrical and mechanical requirements

Vibration: Maintains continuity to minimize mechanical or physical damage during or after vibration following vibration levels

Level 1—34 minutes per axis

20-90 Hz at 6 dB/oct. rise
90-300 Hz at 1.0 g²/Hz
300-2000 Hz at 6 dB/oct. fall

Level 2—14 minutes per axis

20-40 Hz at 6 dB/oct. rise
40-350 Hz at 0.5 g²/Hz
350-2000 Hz at 6 dB/oct. fall
No discontinuities greater than 1 microsecond

Corrosion: No decrease in performance or exposure of base metal up to 48 hours of salt spray

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline



Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Gold over copper

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Strain Relief: Brass, nickel plated


Usable Wire Size

Meets AS39029 paragraph 3.4.2


Contact	Wire Range (AWG)	Current Rating
Size 20	24-20	7.5 A
Size 12	14-12	3 A

Layout Arrangements


(Viewed from grommet side of plug module)



Layout 02
2 Size 12 Contacts




Layout 06
6 Size 20 Contacts



Layout 12
12 Size 20 Contacts


CTJ9 Receptacle Configurations

(Shown with rear environmental assembly)






Part Numbering System



CTJ9 Receptacle Outline and Mounting Dimensions


Flange Mount Receptacle In-Line Receptacle
 Order Part No. 65002*** for standard extended pins
 Order Part No. 65003*** for rear environmental assembly



Layout	A	B	C	D	E	F	G	H	J	K	L
02	0.770	0.620	0.750	0.200	0.100	0.670	0.510	1.000	1.300	0.750	0.530
06	0.650	0.470	0.750	0.200	0.100	0.550	0.380	1.000	1.180	0.600	0.380
12	0.770	0.620	0.750	0.200	0.100	0.670	0.510	1.000	1.300	0.750	0.530




CTJ6 Plug Outline Dimensions




Layout	A	B	Part No.
02	0.652	0.510	CTJ612E02
06	0.530	0.360	CTJ620E06
12	0.652	0.510	CTJ620E12

Clocking Options




Keying Position	45° Angle Location
N	1, 2
1	3, 4
2	1, 3
3	2, 4

Strain Relief



Used with Layout	A	B	Part No.
06	0.320	0.490	1629-011-06117
12	0.470	0.630	1629-011-12117


CTJ6/CTJ9 Mating Procedure



Step 1. With the plug's engaging surface facing the receptacle's mating face and the angled keying surfaces aligned, insert the plug into the receptacle.

Step 2. Press the plug and receptacle firmly together until you hear an audible click that indicates the plug is fully seated and locked in position.

CTJ6/CTJ9 Unmating Procedure



Step 1. Place extraction tool CTJ-R06 over the plug module and insert it into the slots on both sides of the receptacle. Push the tool in until the module's locking fingers disengage.

Step 2. Pressing the legs of the tool to hold the module tight, pull back to remove the plug module.



DEUTSCH CTJ7 and CTG Series Grounding Modules and Junctions

CONVENIENT

- Small rugged devices
- Environmentally sealed
- Simple assembly

FLEXIBLE

- Stud and flange mounting
- Threaded stud can replace the screw terminals

RUGGED ONE-PIECE CONSTRUCTION

- Resistant to shock and vibration
- Light weight
- Dissipates heat well



CTJ7 grounding modules for multiwire grounding applications that need a small, rugged device that also offers sealing and assembly ease.

CTG grounding junctions provide a simple method of terminating a wire to ground. Wires with crimp type contacts inserted into the grounding junctions can then be attached to any grounding surface. Junctions are available for size 22, 20, 16, and 12 contacts.

Specifications

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 110,000 Ft: 200 VAC_{rms}

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Operating Temperature: -65°C to +200°C

Physical Shock: 78 g in each of the 3 mutually perpendicular planes

Thermal Shock (AS81714 paragraph 3.5.5): After cycling the module between -55°C and +200°C, it will meet all applicable electrical and mechanical requirements

Vibration: Maintains continuity to minimize mechanical or physical damage during or after vibration following vibration levels

Level 1—34 minutes per axis

20-90 Hz at 6 dB/oct. rise
90-300 Hz at 1.0 g²/Hz
300-2000 Hz at 6 dB/oct. fall

Level 2—14 minutes per axis

20-40 Hz at 6 dB/oct. rise
40-350 Hz at 0.5 g²/Hz
350-2000 Hz at 6 dB/oct. fall

No discontinuities greater than 1 microsecond



Corrosion: 48 hours of salt spray
Magnetic Permeability: 2.0 μ max.
Fluid Resistance:
 MIL-PRF-5606: Hydraulic fluid
 MIL-DTL-83133: JP-8 aviation fuel
 MIL-PRF-7808: Lubricating oil
 MIL-PRF-23699: Lubricating oil
 MIL-A-8243: Deicing/defrosting fluid
 MIL-C-25769: Aircraft cleaning compound
 MIL-PRF-87937: Aircraft cleaning compound
 MIL-G-3056: Gasoline

Materials

Housing: Composite
Bus Bar/Pins: Copper alloy, plated gold
Pin Contacts: Gold over copper
Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Contact Resistance (at 25°C) Meets AS39029 paragraph 3.5.4

Wire Size	Test Current	Voltage Drop
22 AWG	5 A	73 mV
20 AWG	7.5 A	55 mV
16 AWG	13 A	50 mV
12 AWG	23 A	42 mV

Usable Wire Size Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26-22	5 A
Size 20	24-20	7.5 A
Size 16	16-20	13 A
Size 12	14-12	3 A

Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109
12	0.097	0.142


CTJ7 Modules




Size 22
01C Bussing Code
 20 Size 22 Contacts



Size 20
01B Bussing Code
 12 Size 20 Contacts




Size 16
01D Bussing Code
 6 Size 16 Contacts






Size 12
01E Bussing Code
 6 Size 12 Contacts

CTJ7 Module Outline Dimensions



Type K: Flange Mount



Type K: Flange Mount

Part Numbering System

CTJ7 22 K 01C - 513

Basic Identifier

Module Size

- 22 Size 22 Contact
- 20 Size 20 Contacts
- 16 Size 16 Contacts
- 12 Size 12 Contacts

Flange Mounting Style

- K Flange Mount
- E Stud Mount (Not available for size 12)


Bus Arrangement

- 01C 20 Size 22 Contacts Bussed
- 01B 12 Size 20 Contacts Bussed
- 01D 6 Size 16 Contacts Bussed
- 01E 6 Size 12 Contacts Bussed

Modifications

- 513 To Mil Standard to Withstand Fluid Immersion to MS55
- 090 Less Contacts
- 6144 Replace Standard Hardware with MS21042I3 Self-Locking Nut and MS55 Resilient Material; Replace Standard Contacts with High-Reliability Contacts
- 6148 MS55 Resilient Material, Omit Contacts, Sealing Plugs, and Insertion/Removal Tool
- 7067 Gold-Over-Nickel Plating, MVFS Insert Material, Add Washer, Rotate Insert Marking
- 4010 Vacuum Bake

CTG Junction Outline Dimensions



Contacts Size	A	B	Part No.
22	1.316 (33.43)	0.188 (4.78)	CTG-22-08
20	1.240 (31.50)	0.188 (4.78)	CTG-20-08
16	1.246 (31.65)	0.250 (6.35)	CTG-16-08
12	1.370 (34.80)	0.313 (7.95)	CTG-12-08



DEUTSCH CTL, CTM, and CTN Series In-Line Junctions

VERSATILE

- Options to connect up to 4 wires in-line and bussed configurations
- Houses and seals individual components
- Replacement for “Y” splices and terminal strips
- Special configurations and designs available

RUGGED

- Resistant to shock and vibration, per Mil AS39029, paragraph 3.5.9
- Extreme temperature range: -55°C to +200°C
- Resistant to harsh fluids, per Mil AS-81714

EASY TO USE

- In-line mountable
- Uses AS39029 crimp contacts



CTL series in-line junctions connect two wires in-line using crimp-type contacts. The junctions can then be placed in a wire bundle without being mounted.

CTM series multi-junctions connect and bus four wires. They can be used to replace “Y” splices and terminal strips.

CTN Series electronic multi-junctions are in-line devices that houses and shields passive or active components, including fuses, resistors, diodes, capacitors, or integrated circuits.

Dielectric Withstanding Voltage (AS81714):

At Sea Level: 1500 VAC_{rms}
At 110,000 Ft: 200 VAC_{rms}

Operating Temperature: -55°C to +200°C

Physical Shock (AS39029, paragraph 3.5.9): Items shall not be damaged, there shall be no loosening of parts due to shock, and no interruption of electrical continuity longer than one microsecond during exposure to mechanical shock.

Fluid Resistance:

MIL-PRF-5606: Hydraulic fluid
MIL-DTL-83133: JP-8 aviation fuel
MIL-PRF-7808: Lubricating oil
MIL-PRF-23699: Lubricating oil
MIL-A-8243: Deicing/defrosting fluid
MIL-C-25769: Aircraft cleaning compound
MIL-PRF-87937: Aircraft cleaning compound
MIL-G-3056: Gasoline

Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Gold over copper

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed

Common Termination Systems



Usable Wire Size


Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26-22	5 A
Size 20	24-20	7.5 A
Size 16	16-20	13 A
Size 12	14-12	3 A


Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109

CTL Outline Dimensions



SIZE 12, 16, 20 & 22



Part No.	Size	A Max.	B ± .030
CTL-22	22	1.280	0.200
CTL-20	20	1.452	0.260
CTL-16	16	1.400	0.300
CTL-12	12	1.680	0.360

Part Numbering System

CTL 22 - 513

Basic Identifier

Contact Size

Modifications



513 To Mil Standard to Withstand Fluid Immersion to MS55

090 Less Contacts

6148 MS55 Resilient Material, Omit Contacts, Sealing Plugs, and Insertion/Removal Tool

4010 Vacuum Bake

CTM Outline Dimensions



Terminals (contact)


Terminals Bussed Together

Part No.	Size	A ± .060	B ± .030	C ± .030
CTM 22	22	1.262	0.354	0.210
CTM 20	20	1.368	0.451	0.241
CTM 16	16	1.368	0.518	0.274
CTM 12	12	1.644	0.644	0.337




Part Numbering System


CTM 22 - 513



CTN Layout Arrangements




CTN Outline Dimensions



Part Numbering System

CTN 20 D XXX - 513





DEUTSCH Composite In-line Junctions

RUGGED

- Rugged composite housing
- Fluid resistant: hydraulic fluid, jet fuel, and other fluids common in aerospace and defense applications
- Environmentally sealed
- No exposed discrete components

EASY TO USE

- Reliable and quick termination
- No mounting required
- Light weight

CONVENIENT

- Field serviceable AS39029 socket contacts
- Accommodates a wide range of common gauge wire, from 22 to 12 AWG
- Hand crimp socket contacts

VERSATILE

- Design options for discrete components available



Designed to AS81714 requirements, DEUTSCH in-line termination junctions are composite versions of the CTL, CTM, and CTN series.

Dielectric Withstanding Voltage (AS81714 paragraph 3.5.6):

At Sea Level: 1500 VAC_{rms}
At 100,000 Ft: 200 VAC_{rms}

Operating Temperature: -65°C to +200°C

Insulation Resistance (AS81714 paragraph 3.5.11): 5000 M min. at 25°C

Electrical Continuity:

Shock Exposure: <1 μs @ 300 g sine/2 3 ms
Vibration: <1 μs @ 30 g peak

Materials

Housing: Composite

Bus Bar/Pins: Copper alloy, plated gold

Pin Contacts: Copper, plated gold

Sealing Grommet: Elastomer, fluid resistant and environmentally sealed



Usable Wire Size


Meets AS39029 paragraph 3.4.2

Contact	Wire Range (AWG)	Current Rating
Size 22	26-22	5 A
Size 20	24-20	7.5 A
Size 16	16-20	13 A
Size 12	14-12	3 A


Grommet Sealing Range

Contact Size	Wire OD	
	Min.	Max.
22	0.030	0.060
20	0.040	0.083
16	0.065	0.109

Single In-line Junction



Part Numbering System



Ordering Information

65409-20x-xxx


Typical Components

XXX	Value	Manufacturer Part No.
With Resistors: 65049-20R-XXX (R = Resistor)		
004	5.1 k , 1/4 W, 2%	RLR07C5101GS
009	510 , 1/4 W, 5%	RCR07G511JS
010	390 , 1/4 W, 5%	RCR07G391JS
011	150 k , 1/4 W, 5%	RLR07C1500JS
016	1540 k , 1/4 W, 1%	RLR07C1541FS
017	100 k , 1/8 W, 1%	RNR55C1003F* (* = R or S)
018	10 k , 1/4 W, 1%	RLR07C1002FS
019	2.7 k , 1/4 W, 2%	RLR07C2701GS
022	430 k , 1/4 W, 1%	RWR81S4300FR
024	1 k , 1/2 W, 1%	PPC1.00KXCT-ND
025	1.25 k , 1/4 W, 1%	RNF55-125UR,-1%-5PPM-1
026	100 k , 1/4 W, 1%	RLR05C3161FS
With Diodes: 65049-20D-XXX (D = Diode)		
016	600 Vrms @ 1 A	JANTX 1N5619
018	700 Vrms @ 3 A	JANTX 1N5554
With Fuses: 65049-20F-XXX (F = Fuse)		
004	125 V, 1/2 A	FMO8A (Tinitron Fuse)

Please contact TE for any customized specifications (based on discrete passive requirements).




Dual In-line Junctions



Part Numbering System

65053 - 20 D - 201



Typical Components

XXX	Component Type	Value	Manufacturer Part No.
With Diodes: 65053-20D-XXX (D = Diode)			
201	Diode	36 V _{wm} @ 23 A, Bi-Dir	1N6388
202	Diode	420 V _{rms} @ 3 A	1N5406
203	Dual Diodes	420 V _{rms} @ 3 A	1N5406
204	Zener Diode	14 V _z @ 6.7 AZS	1N5351B
208	Dual Diodes	700 V _{rms} @ 10A peak	1N4007
214	Dual Diodes	600 V _{rms} @ 1A	1N5618
With Resistors: 65053-20R-XXX (R = Resistor)			
215	Resistor	120 , 1/2 W	RCR20G121JS
With Fuses: 65053-20F-XXX (F = Fuse)			
205	Dual Fuses	125 V, 0.5 A	FM08A125V1/2A
219	Fuse	125 V, 2 A	FM08A125V1/2A
220	Fuse	125V, 7 A	PICO II SLO-BLW 473
224	Fuse	125 V, 1 A	PICO II SLO-BLW 473
226	Resistor	1 , 1 W	Ohmite WHB1ROFE

Please contact TE for any customized specifications (based on discrete passive requirements).



DEUTSCH Adapter Junctions

CONVENIENT


- Easily convert devices with screw terminals to use DEUTSCH contacts

FLEXIBLE

- Two thread sizes
- Environmental and nonenvironmental versions

RELIABLE

- Low-cost contact insertion/removal tool protects converted device by breaking before it can damage junction or device




Adapter junctions provide a quick and easy way to convert electrical components with screw terminals to the CTJ system. The junction attaches to and becomes part of the device to be converted. The adapter junctions are available in two thread sizes (8/32 and 6/32) and in environmental and nonenvironmental versions.

The adapter junctions meet all applicable requirements of MIL-C-26482.




JTA Series Nonenvironmental Adapter Junctions



Contact Size	Part No.		Dimensions				Weight (Lb., Approx.)
	8-32 Thread	6-32 Thread	A ±.020	B ±.020	C ±.020	E (Ref)	
22	JTA-22-01	JTA-22-02	0.553	0.187	0.096	0.216	0.0036
20	JTA-20-01	JTA-20-02	0.551	0.187	0.096	0.216	0.0036
16	JTA-16-01	JTA-16-02	0.561	0.250	0.096	0.289	0.0059
12	JTA-12-01	—	0.605	0.312	0.096	0.360	0.0099

JTE Series Environmental Adapter Junctions



Contact Size	Part No.		Dimensions				Weight (Lb., Approx.)
	8-32 Thread	6-32 Thread	A ±.020	B ±.020	C ±.020	E (Ref)	
22	JTE-22-01	JTE-22-02	0.838	0.187	0.096	0.216	0.0039
20	JTE-20-01	JTE-20-02	0.745	0.187	0.096	0.216	0.0039
16	JTE-16-01	JTE-16-02	0.773	0.250	0.096	0.289	0.0063
12	JTE-12-01	—	0.842	0.312	0.096	0.360	0.0106



DEUTSCH CTJ2 Series Metallic Single-Module Rails

VERSATILE

- Designed to hold up to 50 variations
- Elongated mounting holes for easy installation
- Available in sizes ranging from 2" to 40"


LIGHT WEIGHT

- Extruded aluminum alloy rail
- Stainless steel metal clip




CTJ2 metallic rails are aluminum alloy and designed to hold one single module or two half-size modules.

Outline Dimensions



Part Numbering System





DEUTSCH CTJ3 Series Metallic Rails

VERSATILE

- Designed to hold up to 50 variations
- Elongated mounting holes for easy installation
- Available in sizes ranging from 2" to 40"

LIGHT WEIGHT

- Extruded aluminum alloy rail
- Stainless steel metal clip



CTJ3 metallic rails from TE Connectivity (TE) use aluminum alloy and stainless steel clips. They are available with a variety of finishes and sizes ranging from 2 to 40 inches.


Frame Capacity

Longer rail sizes available; consult TE

Length* (Inch)	Frame Capacity		A ± .015	B ± .010	Weight, Lb.
	Sizes 22, 20, 16	Size 12			
02	2	1	1.036	0.518	0.022
03	3	1*	1.554	1.036	0.033
04	4	2	2.072	1.554	0.043
05	5	2*	2.590	2.072	0.054
06	6	3	3.108	2.590	0.065
07	7	3*	3.626	3.108	0.075
08	8	4	4.144	3.626	0.086
09	9	4*	4.662	4.144	0.097
10	10	5	5.180	4.662	0.108
12	12	6	6.216	5.698	0.130


*Size includes room for one or more Size 22, 20, or 16 modules.

Part Numbering System





Outline Dimensions





DEUTSCH DCR Series Composite Rails

LIGHT WEIGHT

- 48% lighter than comparable aluminum rails
- Composite version of CTJ3 rail

VERSATILE

- Intermounts with MIL-T-81714 Series II rails
- Accepts MIL-T-8174M Series II modules
- Simple removal tooling

HIGH PERFORMANCE

- Wide temperature range: -65°C to +175°C
- Environmentally sealed, fluid resistant
- Corrosion resistant




DEUTSCH DCR composite rails provide a lightweight, corrosion-resistant mounting system for electronic feedback and distribution modules. It is designed to allow hand insertion of each individual module. A positive lock retains the modules in the rails. Modules can be individually unlocked and removed by using a simple tool.

Frame Capacity and Outline Dimensions


No. of Modules	A ± .015	B + .010	Weight, Oz. (g)
02	1.036	0.518	0.19 (5.30)
03	1.554	1.036	0.28 (7.95)
04	2.072	1.554	0.37 (10.60)
05	2.590	2.072	0.47 (13.25)
06	3.108	2.590	0.56 (15.90)
07	3.626	3.108	0.65 (18.55)
08	4.144	3.625	0.75 (21.20)
09	4.662	4.144	0.84 (23.85)
10	5.180	4.662	0.93 (26.50)
11	5.698	5.180	1.03 (29.25)
12	6.216	5.698	1.12 (31.80)
13	6.734	6.216	1.21 (34.45)
14	7.252	6.734	1.31 (37.10)
15	7.770	7.252	1.40 (39.75)
16	8.288	7.770	1.50 (42.40)
17	8.806	8.288	1.59 (45.05)
18	9.324	8.806	1.68 (47.70)
19	9.842	9.324	1.68 (50.35)
20	10.350	9.842	1.87 (53.00)



Outline Dimensions




Part Numbering System





Socket Contacts




Part Numbers and Outline Dimensions

Contact Size	Part No.	Mil Equivalent	A. Max.	B. Dia.	C. Max.	D. Min.	E. Max.	Weight
22	CTS-S22/22	M39039/22-191	0.336	0.033/0.031	0.0615	0.033	0.048	0.00011
20	CTS-S20/20	M39039/22-192	0.358	0.044/0.042	0.0940	0.046	0.070	0.00027
16	CTS-S16/16	M39039/22-193	0.358	0.064/0.066	0.1300	0.066	0.103	0.00050
12	CTS-S12/12	M39039/22-605	0.455	0.100/0.097	0.17100	0.096	0.152	0.00145

Application Information

Contact Size	Part No.	Color Bands	Wire Strip Length	Wire Range (AWG)
22	CTS-S22/22	Brown-White-Brown	0.207 ±0.030	26-22
20	CTS-S20/20	Brown-White-Red	0.207 ±0.030	24-20
16	CTS-S16/16	Brown-White-Orange	0.207 ±0.030	20-16
12	CTS-S12/12	Blue-Black-Green	0.225 ±0.020	14-12

Reduced Diameter Contact Information



Part Numbers and Outline Dimensions

Contact Size	Part No.	A. Max.	B. Dia.	C. Max.	D. Min.	E. Max.	Weight (Lb.)
20	1662-202-2031	0.358	0.044/0.042	0.0940	0.033	0.050	0.00027
16	1662-202-1631	0.358	0.064/0.066	0.1300	0.046	0.070	0.00050
12	1662-202-1231	0.460	0.100/0.097	0.17100	0.066	0.103	0.00145

Application Information

Contact Size	Part No.	Color Bands	Wire Strip Length	Wire Range (AWG)
20	1662-202-2031	Red-Green	0.207 ±0.030	26-22
16	1662-202-1631	Blue-Red	0.207 ±0.030	24-20
12	1662-202-1231	Yellow-Blue	0.225 ±0.020	20-16

Contact Tooling and Sealing Plug

Contact Size	Crimp Tool		Ins/Ext Tool	Unwired Removal Tool	Sealing Plug	
	Tooling	Positioner			Part No.	Color
22	MH860 (M22520/7-01)	86-19 (M22520/7-11)	M81969/14-01	81517-23	MS27488-22	Black
20	MH860 (M22520/7-01)	86-20 (M22520/7-12)	M81969/14-10	M15574-20	MS27488-20	Red
16	MH860 (M22520/7-01)	86-21 (M22520/7-13)	M81969/14-03	M15574-16	MS27488-16	Green
12	AF8 (M22520/1-01)	M22520/1-16	M81969/16-03	M15574-16	MS27488-12	Orange



DEUTSCH CTJ Series Tooling

Contact Insertion/Removal Tool



Contact Size	Part No.	Color	Unwired Removal Tool
22	M81969/14-01	Green/White	81517-23
20	M81969/14-10	Red/Orange	M15574-20
16	M81969/14-03	Blue/White	M15574-16
22	M81969/16-03	Yellow/White	M15574-16

Contact Crimping Tool



Contact Size	Contact Part No.		Crimp Tool Part No.	
	TE	MIL	Tooling	Positioner
22	CTS-S22/22	M39029/22-191	MH860 (M22520/7-01)	86-19 (M22520/7-11)
20	CTS-S20/20	M39029/22-192	MH860 (M22520/7-01)	86-20 (M22520/7-12)
16	CTS-S16/16	M39029/22-193	MH860 (M22520/7-01)	86-21 (M22520/7-13)
22	CTS-S12/12	M39029/22-605	AF8 (M22520/1-01)	M22520/1-16


CTJ Module Removal Tools

The removal tools make it fast and simple to remove modules from a rail or to unmate CTJ6 and CTJ9 plug and receptacle connectors.


Part Numbers



CTJ-R06
(Use with CTJ6 and CTJ9 Series)



CTJ-R12
(Use with Rail-Mounted Modules)





Terminating CTJ AS39029 Contacts

Make sure you have the proper tool and positioner for the contact being crimped.



Contact Size	Crimp Tool	
	Tooling	Positioner
22	MH860 (M22520/7-01)	86-19 (M22520/7-11)
20	MH860 (M22520/7-01)	86-20 (M22520/7-12)
16	MH860 (M22520/7-01)	86-21 (M22520/7-13)
22	AF8 (M22520/1-01)	M22520/1-16



Strip the wire to the proper dimension using an appropriate tool and method.



Insert the contact into the tool with the crimp barrel facing up.

Contact Size	Strip Length
22, 20, 16	0.207 ±0.030 (5.26 ±0.76)
12	0.225 ±0.030 (5.72 ±0.76)



Insert the stripped conductor into the contact's crimp barrel.



Cycle the crimping tool by squeezing the handles. The handles will not release until the tool has fully cycled.



Remove the wire and inspect the termination.

A proper termination has:

- 8 indent markings
- Wire observable through the contact side hold
- No loose or nicked wire strands



Inserting and Removing Contacts

The colored end is used for insertion. The white or orange end is used for withdrawal.



Contact Size	Tool Part No.	Color
22	M81969/14-01	Green/White
20	M81969/14-10	Red/Orange
16	M81969/14-03	Blue/White
12	M81969/16-03	Yellow/White

Inserting Contacts



Insert the wire into the tool's slot. Pull back gently on the wire until the contact's retention shoulder seats against the tip of the tool.



Insert the contact in the proper module cavity. Push the contact completely in. Then remove the tool. Lightly pull the wire back to make sure the contact is correctly seated.

Removing Contacts



Wrap the tool's slot around the wire. Slide the tool into the cavity until it butts against the contact shoulder.



Press the wire between your fingers and the tool. Pull the wire and tool back together.

Note: When using minimum diameter wire, the tool may have a tendency to stop against the rear of the contact crimp barrel. If this should occur, careful manipulation of the tool will permit it to ride over the crimp barrel and into the proper position to unlock the contact.



Installing Sealing Plugs

Sealing plugs are installed with the head towards the mating end of connector. Use the contact insertion tool if needed.



Cross Reference DEUTSCH CTJ to AS81714

Modules

DEUTSCH Part No.	Mil Spec
CTJ112E01E-513	M81714/60-12-01
CTJ112E02A-513	M81714/60-12-02
CTJ112E03B-513	M81714/60-12-03
CTJ116E01D-513	M81714/60-16-01
CTJ116E02B-513	M81714/60-16-02
CTJ116E03A-513	M81714/60-16-03
CTJ120E01B-513	M81714/60-20-01
CTJ120E02C-513	M81714/60-20-02
CTJ120E03D-513	M81714/60-20-03
CTJ120E04A-513	M81714/60-20-04
CTJ120E06E-513	M81714/60-20-06
CTJ122E01C-513	M81714/60-22-01
CTJ122E02D-513	M81714/60-22-02
CTJ122E04F-513	M81714/60-22-04
CTJ122E05E-513	M81714/60-22-05
CTJ122E06B-513	M81714/60-22-06
CTJ122E10A-513	M81714/60-22-10
CTD1062E05A-513	M81714/61-0W
CTD126E02E-513	M81714/61-0X
CTD160E01F-513	M81714/61-0Y
CTD126E01A-513	M81714/61-0Z
CTJ716K01D-7067	M81714/63-16F
CTJ716E01D-7067	M81714/63-16S
CTJ720K01B-7067	M81714/63-20F
CTJ720E01B-7067	M81714/63-20S
CTJ722K01C-7067	M81714/63-22F
CTJ722E01C-7067	M81714/63-22S

Module Removal Tool

DEUTSCH Part No.	Mil Spec
CTJ-R06	M81714/69-01
CTJ-R12	M81714/69-02

Junctions

DEUTSCH Part No.	Mil Spec
CTL-12-513	M81714/65-12-1
CTM-12-513	M81714/65-12-2
CTL-16-513	M81714/65-16-1
CTM-16-513	M81714/65-16-2
CTL-20-513	M81714/65-20-1
CTM-20-513	M81714/65-20-2
CTL-22-513	M81714/65-22-1
CTM-22-513	M81714/65-22-2

Rails

DEUTSCH Part No.	Mil Spec
CTJ-3A-02-4032	M81714/67-02
CTJ-3A-03-4032	M81714/67-03
CTJ-3A-04-4032	M81714/67-04
CTJ-3A-05-4032	M81714/67-05
CTJ-3A-06-4032	M81714/67-06
CTJ-3A-07-4032	M81714/67-07
CTJ-3A-08-4032	M81714/67-08
CTJ-3A-09-4032	M81714/67-09
CTJ-3A-10-4032	M81714/67-10
CTJ-3A-12-4032	M81714/67-12
CTJ-3A-13-4032	M81714/67-13
CTJ-3A-14-4032	M81714/67-14
CTJ-3A-15-4032	M81714/67-15
CTJ-3A-16-4032	M81714/67-16
CTJ-3A-18-4032	M81714/67-18
CTJ-3A-19-4032	M81714/67-19
CTJ-3A-20-4032	M81714/67-20
CTJ-3A-21-4032	M81714/67-21
CTJ-3A-25-4032	M81714/67-25
CTJ-3A-30-4032	M81714/67-30
CTJ-3A-40-4032	M81714/67-40

For More Information

TE Technical Support Center

North America	+1 800 522 6752
Asia Pacific	+86 0 400 820 6015
Austria	+43 1 905 601 228
Baltic Regions	+46 8 5072 5000
Benelux	+31 73 6246 999
Czech Republic	+420 800 701 462
France	+33 1 34 20 86 86
Germany	+49 6251 133 1999
Hungary	+36 809 874 04
Italy	+39 011 401 2632
Nordic	+46 8 5072 5000
Poland	+48 800 702 309
Russia	+7495 790 790 2
Spain/Portugal	+34 93 2910366
Switzerland	+41 52 633 66 26
United Kingdom	+44 800 267 666

Follow us on Twitter for all the latest product news
@TEConnectivity, and on Facebook, TEConnectivity.

te.com/deutsch

© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773867-9 ADM/RRD 1.5M 12/2015

DEUTSCH, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other product or company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.