

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
00	HC	C	REV PER OS14-0222-04	06-10-04	JDP JGH

Technical drawing showing dimensions and features of the jack receptacle. Key dimensions include: overall width .450 [11.4], mounting surface offset .060 [1.5], center contact diameter $\phi .248$ [6.3], and outer contact diameter $\phi .253^{+.002}_{-.000}$ OVER STRAIGHT KNURL. A chamfered edge is specified as $\phi .020$ [0.5].

RECOMMENDED MOUNTING HOLE technical drawing showing dimensions: chamfer $.005/.010 \times 45^\circ$, hole diameter $\phi .046 \pm .001$ [1.2], hole depth $.250 \pm .001$ [6.4], and reference diameter $.250$ [6.4] REF.

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
NOMINAL IMPEDANCE (OHMS): 50	INTERFACE DIMENSIONS PER MIL-STD-348, FIG. 321.2	TEMPERATURE RATING: -65°C TO +125°C
FREQUENCY RANGE (GHz): DC TO 18.	MATING CHARACTERISTICS: INSERTION MAX (LBS.): 3 WITHDRAWAL MIN (OZ.): 1	VIBRATION PER MIL-STD-202, METHOD 204 CONDITION D.
VOLT RATING (VRMS MAX) @ SEA LEVEL: 335	FORCE: TO ENGAGE (LBS MAX): 3 TO DISENGAGE (LBS MAX): 1.5	SHOCK PER MIL-STD-202, METHOD 213, CONDITION I
VSWR: 1.05 + .005f(GHz)	CENTER CONTACT CAPTIVATION AXIAL (LBS): 6	THERMAL SHOCK PER MIL-STD-202 METHOD 107, CONDITION B.
INSERTION LOSS (dB MAX): $.03\sqrt{f(\text{GHz})}$	WEIGHT (GRAMS): 2.3	MOISTURE RESISTANCE PER MIL-STD-202, METHOD 106.
RF LEAKAGE (dB MIN): -(65-f(GHz))		CORROSION PER MIL-STD-202, METHOD 101, CONDITION B.
CORONA, 70,000 FT. (VRMS MIN): 335	1 MATERIAL: HOUSING/ BUSHING: STAINLESS STEEL PER ASTM A484 AND ASTM A582, TYPE 303 DIELECTRIC: PTFE PER ASTM-D-1457 CENTER CONTACT: BeCu PER ASTM B 196, CONDITION H CONTACT SLEEVE: BeCu PER ASTM B 196, CONDITION H CONTACT RING / SHIM: BeCu PER ASTM B 194, CONDITION H	
DIELECTRIC WITHSTANDING VOLTAGE: (VRMS MIN) @ SEA LEVEL: 1000		
CONTACT RESISTANCE (MILLIOHMS MAX): CENTER CONTACT: 2.0 OUTER CONTACT: 2.0	2 FINISH: HOUSING/ BUSHING: PASSIVATE PER ASTM-A380 CENTER CONTACT: GOLD PLATE PER MIL-G-45204 OVER COPPER PER MIL-C-14550 CONTACT SLEEVE: GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290 CONTACT RING / SHIM: GOLD PLATE PER MIL-G-45204 OVER COPPER PER MIL-C-14550	
RF HIGH POTENTIAL @ SEA LEVEL (VRMS MIN @ 5 MHz): 1000		
I.R. (MEGOHMS MIN): 5,000	3. REF M/A-COM 4558-1154-02.	

RECOMMENDED MOUNTING HOLE

1059654-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. BURKHOLDER 23OCT02	Tyco Electronics Corporation Middletown, PA 17057	
DIMENSIONS: INCHES		CHK J. HAVENER 23OCT02	NAME J. HAVENER	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. HAVENER 23OCT02	PRODUCT SPEC	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ± 1 ANGLES ± 1		APPLICATION SPEC		SIZE A2
MATERIAL	FINISH	408-8679	CAGE CODE 00779	DRAWING NO C=1059654-1
		WEIGHT -	RESTRICTED TO -	
CUSTOMER DRAWING			SCALE 6:1	SHEET 1 OF 1 REV C

AMP 1471-9 REV 31MAR2000