



- .040 DIA HOLE IS RECOMMENDED FOR P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 44 POSN RECEPTACLE
- REPLACEMENT PIN AMP# 207683-8
- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- CLINCH NUT(QTY = 2) IS USED ON 208868-3 ONLY.
- FINISH: CADMIUM PER QQ-P-416
- FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 7	5-208868-1
5, PLATED PER 6	208868-3
PLATED PER 6	208868-2
PLATED PER 6	208868-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	1-7-88	Tyco Electronics Corporation	
		C.C. THOMAS	1-26-88	Harrisburg, Pa 17105-3608	
		CHK		F.C. BALLEW III	
		APVD		NAME	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	
0 PLC ± .005		1 PLC ± .005		APPLICATION SPEC	
1 PLC ± .005		2 PLC ± .005		SIZE	
2 PLC ± .005		3 PLC ± .005		CAGE CODE	
3 PLC ± .005		4 PLC ± .005		DRAWING NO	
4 PLC ± .005		ANGLES ± .005		RESTRICTED TO	
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS		WEIGHT	
				A1 00779 C=208868	
				CUSTOMER DRAWING	
				SCALE 4:1 SHEET 1 OF 1 REV	