



- .040 DIA HOLE IS RECOMMENDED FOR P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 26 POSN PLUG
- REPLACEMENT SOCKET AMP# 207684-4
- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- FINISH: CADMIUM PER QQ-P-416
- FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 6	5-208873-1
PLATED PER 5	208873-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	1-6-88	Tyco Electronics Corporation Harrisburg, Pa 17105-3608
DIMENSIONS: INCHES		CHK	1-25-88	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		AMPLIMITE 26 POSN. RCPT. ASSY., W/ LOADED POSTED CONTACTS SIZE 2, SERIES 90
0 PLC ± .005		APVD		
1 PLC ± .005		PRODUCT SPEC		
2 PLC ± .005		APPLICATION SPEC		
3 PLC ± .005		SIZE		RESTRICTED TO
4 PLC ± .005		CAGE CODE		A1
FINISH		DRAWING NO.		00779
SEE CALLOUTS		WEIGHT		208873
		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV H