



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
- MATERIAL:
HOUSING & COVER - THERMOPLASTIC, BLACK.
TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE; .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE; .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
2. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
3. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
4. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
5. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
6. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
7. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

REVIS		REVISIONS		DATE	BY
GP	00	1	1	1/7/83	BM/WM
H					

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		SCALE	
DIMENSIONS INCHES		16/MAY/07		2:1	
TERMINAL SPACINGS		16/MAY/07		SHEET 1 OF 1	
APPLICATOR		16/MAY/07		REV H	
MATERIAL		16/MAY/07			
DRAWN		16/MAY/07			
CHECKED		16/MAY/07			
APPROVED		16/MAY/07			
APPLICATION SPEC		16/MAY/07			
CUSTOMER DRAWING		16/MAY/07			

AS SHOWN 553602-1
DESCRIPTION PART NUMBER

Yeo Electronics Corporation
Hunting Park 17105-4088

PLUG ASSEMBLY, 50 POSITION
SCREW LOCK, LOW PROFILE,
STAMP LATCH

SIZE 100779
REV 002
553602

RESTRICTED TO

AMP 1471-4-REV 3/10/00

553602