

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			DS	EL
P	LTR	DESCRIPTION	DATE	DWN	APVD	
HM	00	D	REV ECO-08-012703	11JUL12	JB	JG

1. DIMENSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.

2. MATERIAL: HOUSING- POLYCARBONATE, BLUE
 TERMINAL- PHOSPHOR BRONZE, PLATED WITH 1.27 μ m [.000050] MINIMUM THICK GOLD IN LOCALIZED GOLD PLATE AREA OVER 2.54 μ m [.000100] MINIMUM THICK NICKEL UNDERPLATE.

3. PLUG WILL ACCEPT 26 OR 28 AWG SOLID WIRE, 0.74-0.86 [.029-.034] DIAMETER, WITH AN OVAL CABLE JACKET OF 2.29 X 4.83 [.090 X .190] MAXIMUM.

4. TERMINATED DIMENSION 6.15 [.242] MAXIMUM.

5. 1000 ASSEMBLIES PER PACKAGE.

6. 100 ASSEMBLIES PER PACKAGE.

6	5-557965-3
5	5-557965-2
PACKAGE	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	03MAR2008	TE Connectivity	
DIMENSIONS: MM [INCHES]		CHK	L. HALL 04MAR2008		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	B. MCNEILL 04MAR2008		
0 PLC ± -		PRODUCT SPEC	108-1163		
1 PLC ± -		APPLICATION SPEC	114-6016		
2 PLC ± -		WEIGHT	-	SIZE	A2
3 PLC ± -		CUSTOMER DRAWING		CAGE CODE	00779
4 PLC ± -		SCALE 4:1		DRAWING NO	C=557965
ANGLES ± -		SHEET 1 of 1		RESTRICTED TO	-
FINISH		REV D			

1471-9 (3/11)

557965

A