



- CONNECTOR MATES WITH ANY 9 POSN PLUG IN AMPLIMITE SERIES & COMPLIES WITH AMP SPEC 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, BLACK.  
SHELL: STEEL.  
CONTACTS: PHOSPHOR BRONZE.  
EYELETS: BRASS.  
SCREWLOCKS: ZINC.  
INSERTS: ZINC.
- SHELL: BRIGHT TIN.  
CONTACTS: .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON SOLDER POST, ALL OVER .000050 NICKEL.  
EYELETS: TIN.  
SCREWLOCKS: CLEAR CHROMATE.  
INSERTS: CLEAR CHROMATE.

FEMALE SCREWLOCKS	5745988-6
THREADED INSERTS	5745988-4
MOUNTING HARDWARE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0. PLC ± -	1. PLC ± -	2. PLC ± -	3. PLC ± .005	4. PLC ± -	ANGLES ± °
MATERIAL	FINISH	CUSTOMER DRAWING					

DIN	A. FERNANDEZ-DOCKS 04-08-05	APVD	M. WALMSLEY 04-08-05	NAME	RCPT ASSY, SIZE 1, RTANG, W/FRONT METAL SHELL, .026 DIA POSTS, AMPLIMITE HD-20 (.590 FOOTPRINT) SHORT LEG
CHK	J. GERACE 04-08-05	PRODUCT SPEC	108-40025	APPLICATION SPEC	114-40010
SIZE	A1	SCALE	4:1	SHEET	1 OF 1
WEIGHT	-	DRAWING NO	00779	DRAWING NO	5745988

TE Connectivity

**COPYRIGHT 2005 TE CONNECTIVITY CORP ALL RIGHTS RESERVED**