



RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 THICK P.C. BOARD

3.81	.150		
2.54	.100	44.32	1.745
2.03	.080	33.78	1.330
1.91	.075	26.67	1.050
1.57	.062	19.05	.750
1.52	.060	17.27	.680
1.27	.050	12.83	.505
0.25	.015	12.70	.500
0.13	.005	9.14	.360
0.08	.003	7.37	.290
0.00127	.000050	6.35	.250
0.000762	.000030	4.06	.160
MM	IN	MM	IN

CONVERSION TABLE

- 1 PARTS COMPLY WITH AMP SOLDERABILITY SPECIFICATION 109-11-5.
- 2 0.00076 GOLD OVER 0.00127 MIN NICKEL WITH MATTE TIN LEAD ON SOLDER TAIL.
- 3 CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAMMIES BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.
- 4 0.00076 GOLD OVER 0.00127 MIN NICKEL WITH MATTE TIN ON SOLDER TAIL.
- 5 SUPERSEDED BY 3-643230-0
- 6 DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION HUMIDITY ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

PH BRZ.	A	NYLON UL 94V-0	3-643230-0
PH BRZ.	A	NYLON UL 94V-0	643230-2
PH BRZ.TIN		NYLON UL 94V-0	643230-1
CONTACT		HOUSING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DATE: 01/07/79
 DRAWN BY: [Signature]
 CHECKED BY: [Signature]
 APPROVED BY: [Signature]

TE Connectivity Ltd.

SOCKET HEADER ASSEMBLY, RIGHT ANGLE MOUNT (A POSITION), UNIVERSAL, WTE-N-(LON)TM

643230

REV 1