



REV B DRC26-40S*-L011

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
NC	NEW RELEASE PER E.O. A14575	3-30-34	J.A.
A	REVISED PER E.O. A14773	12-2-94	R.D.R.
B	REDRAWN & REVISED PER E.O. P18865	3-31-05	RDR

DRC26-40SA-L011



DRC26-40SB-L011



DRC26-40SC-L011



DRC26-40SD-L011



CONTACT SIZE	MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE RANGE [mm ²] REF ONLY
20	.040 [1.016]	.095 [2.413]	16-20 AWG [1.0-0.5]

5. THIS PLUG MATES WITH DRC23-40P*-**** RECEPTACLE. (* = A,B,C,D KEYS; **** = ALL MODIFICATIONS)
- 4 FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.
3. PLUG IS SUPPLIED WITH DUST CAP (NOT SHOWN).
2. DIMENSION TOLERANCE: ±.025 [.635]
1. DIMENSIONS ARE IN INCHES [mm].
- NOTES: UNLESS OTHERWISE SPECIFIED

- 8 PART MODIFICATION: WIRE ROUTER ONTO PLUG.
7. MATERIAL: HOUSING: PLASTIC (BLACK); BOLT: STAINLESS STEEL; CLIP: STEEL; GROMMET: RUBBER.
6. RECOMMENDED RETAINING BOLT TORQUE: 25-28 IN-LB [2.82-3.16 NM].

SIGNATURE & DATE		PLUG 40 CONTACTS, SIZE 20 -L011 MOD DRC SERIES	CP	MATL. CODE
DR	J. APOSTOL 17MAR2005		The Deutch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545	
CHK	R. Meier 3/28/05		B DRC26-40S*-L011	
PE	D. Meyer 3/28/05			
APPD	R. Reed 3-31-05	ENVELOPE	DWG SIZE	CODE 11139
SCALE	NONE	WT	SHEET OF	