

NT
Flexible, Flame Retarded,
Modified Elastomer,
Heat - Shrinkable Tubing




Table 1: Dimensions

Size	As Supplied		Recovered							
	Inside Diameter		Inside Diameter		Wall Thickness (W)					
	Minimum (D)		Maximum (d)		Minimum		Maximum		Nominal	
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
1/8	.125	3.18	.061	1.55	.019	0.48	.035	0.91	.027	0.69
3/16	.187	4.75	.100	2.54	.023	0.58	.043	1.09	.033	0.83

Properties:

Except as specified above, this tubing shall meet the requirements of Raychem Specification RT-510.

Specification Control Drawing

tyco <i>Electronics</i>	Tyco Electronics Corporation 300 Constitutional Drive Menlo Park, CA 94025 USA		Raychem	Title: NT Flexible, Flame Retarded, Modified Elastomer, Heat - Shrinkable Tubing		
	Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application			Document No : NT		
Cage Code: 06090	Scale: None	Size: A	Rev. Date: 30-Oct-96	Rev.: C	Sheet: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.