

Phantom[®] 800 MHz-5.8GHz Antennas



PHANTOM[®] ANTENNA IS IDEAL FOR CELL, GSM, PCE, WIFI, 802.11 AND BLUETOOTH WIRELESS APPLICATIONS

Laird's unique patented Phantom^{*} is a tough low-profile antenna for outdoor or indoor applications. Measuring only 2.7" tall, the Phantom 800 MHz to 5.8 GHz antenna models' revolutionary design features field diversity with both vertical and horizontal polarization components. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Laird Technolgies' magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

The Phantom[®] patented technology is beneficial when high performance is desired and extreme ruggedness and low profile is required.


FEATURES **Rohs**

- True Field Diversity design ensures uninterrupted transmissions in urban canyons and rural drop off areas
- Phantom[®] outperforms a 3dB whip in many applications
- U.S. Patent Nos. 5,977,931 6,292,156 and 7,209,096


MARKETS

- Cell
- GSM and PCS
- WiFi
- 802.11
- Bluetooth wireless applications

ANTENNA PATTERNS



Elevation Pattern (Y, Z, or H-plane)



Azimuth Pattern (X,Y, or E-plane)

Americas: +1.847 839.6925 IAS-AmericasEastSales@lairdtech.com Europe: +44.1628.858941

IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Smart Technology. Delivered.

Phantom[®] 800 MHz-5.8GHz Antennas

SPECIFICATIONS

ELECTRICAL	
VSWR	< 2.1
Nominal Gain	3 dB-M.E.G.
Maximum Power	100 W
Nominal Impedance	50 Ω
Polarization	Vertical
Pattern	Omnidirectional
Half-Power Beamwidth (Elevation° x Azimuth°)	130° x 360°
Coaxial Cable Length & Type	None
Terminations	NMO Socket or, type N-female

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION	
TRA8063	806-870 MHz 3 dB-MEG Phantom [®] ¾ NMO, White Radome	
TRA8213	821-896 MHz 3 dB-MEG Phantom [®] ¾ NMO, White Radome	
TRA8903	890-960 MHz 3 dB-MEG Phantom [®] ¾ NMO, White Radome	
TRA9023	902-928 MHz 3 dB-MEG Phantom [®] ¾ NMO, White Radome	
TRA18503	1.85 - 1.99 GHz 3dB-MEG Phantom® ¾ NMO, White Radome	
TRA24003	2.4 – 2.5 GHz 3 dB-MEG Phantom [®] ¾ NMO, White Radome	
TRA58003	4.9 – 6.0 GHz 3 dB-MEG Phantom® 3/4 NMO, White Radome	
TRADCAGP	TRADCAGP G - Drop ceiling antenna adaptor for P-mount Phantom w/ 6"x6"x0.016" ground plane	
Sealtube3	Heat shrink tubing 3"x1"DIA install (use for jaw protector on installation wrench)	

Add "B" to model number for black radome. Example: TRAB8063 Add "P" to model number for Permanent Mount. Example: TRA8063P

MECHANICAL	
Color	Black or White
Height (initially)	23/4"
Diameter	1.438″
Weight	0.173 lb
Material	ABS
Mounting Information	NMO (PN: MB8, MAB8) Sold Separately
Noise Suppressor	BlackHawk NS1535 1-35 VOLT, 15 Amp Noise Suppessor (Sold Separately)

Permanent Mounting Option:

Please order by antenna model and insert letter "P" to indicate permanent mounting option (TRA8063P).

ANT-DS-PHANTOM 800-5800 MHz 1214

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks of or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.