

# 74ALVCH16501

18-bit universal bus transceiver; 3-state

Rev. 5 — 10 July 2012

Product data sheet

## 1. General description

---

The 74ALVCH16501 is an 18-bit transceiver featuring non-inverting 3-state bus compatible outputs in both send and receive directions. Data flow in each direction is controlled by output enable (OEAB and  $\overline{\text{OEBA}}$ ), latch enable (LEAB and LEBA), and clock (CPAB and CPBA) inputs. For A-to-B data flow, the device operates in the transparent mode when LEAB is HIGH. When LEAB is LOW, the A data is latched if CPAB is held at a HIGH or LOW logic level. If LEAB is LOW, the A-bus data is stored in the latch/flip-flop on the LOW-to HIGH transition of CPAB. When OEAB is HIGH, the outputs are active. When OEAB is LOW, the outputs are in the high-impedance state.

Data flow for B-to-A is similar to that of A-to-B but uses  $\overline{\text{OEBA}}$ , LEBA and CPBA. The output enables are complimentary (OEAB is active HIGH, and  $\overline{\text{OEBA}}$  is active LOW).

To ensure the high-impedance state during power-up or power-down,  $\overline{\text{OEBA}}$  should be tied to  $V_{CC}$  through a pull-up resistor and OEAB should be tied to GND through a pull-down resistor; the minimum value of the resistor is determined by the current-sinking/current-sourcing capability of the driver.

Active bus hold circuitry is provided to hold unused or floating data inputs at a valid logic level.

## 2. Features and benefits

---


- Wide supply voltage range from 1.2 V to 3.6 V
- Complies with JEDEC standard JESD8-B
- CMOS low power consumption
- Direct interface with TTL levels
- Current drive  $\pm 24$  mA at  $V_{CC} = 3.0$  V
- Universal bus transceiver with D-type latches and D-type flip-flops capable of operating in transparent, latched or clocked mode
- All inputs have bus hold circuitry
- Output drive capability 50  $\Omega$  transmission lines at 85 °C
- 3-state non-inverting outputs for bus-oriented applications

3. Ordering information

Table 1. Ordering information

| Type number     | Package           |         |  |          |
|-----------------|-------------------|---------|--|----------|
|                 | Temperature range | Name    | Description  | Version  |
| 74ALVCH16501DGG | −40 °C to +85 °C  | TSSOP56 | plastic thin shrink small outline package; 56 leads; body width 6.1 mm | SOT364-1 |
| 74ALVCH16501DL  | −40 °C to +85 °C  | SSOP56  | plastic shrink small outline package; 56 leads; body width 7.5 mm      | SOT371-1 |

4. Functional diagram






Fig 3. Bus hold circuit




Fig 4. Logic diagram

5. Pinning information

5.1 Pinning




Fig 5. Pin configuration

5.2 Pin description

Table 2. Pin description

| Symbol          | Pin   | Description                |
|-----------------|---|----------------------------|
| OEAB            | 1   | output enable A-to-B input |
| LEAB            | 2   | latch enable A-to-B input  |
| A0 to A17       | 3, 5, 6, 8, 9, 10, 12, 13, 14, 15, 16, 17, 19, 20, 21, 23, 24, 26 | data inputs or outputs     |
| GND             | 4, 11, 18, 25, 29, 32, 39, 46, 53, 56                             | ground (0 V)               |
| V <sub>CC</sub> | 7, 22, 35, 50   | positive supply voltage    |
| OEBA            | 27  | output enable B-to-A       |
| LEBA            | 28  | latch enable B-to-A        |

Table 2. Pin description ...continued

| Symbol    | Pin  | Description            |
|-----------|--|------------------------|
| CPBA      | 30   | clock input B-to-A     |
| B0 to B17 | 54, 52, 51, 49, 48, 47, 45, 44, 43, 42, 41, 40, 38, 37, 36, 34, 33, 31 | data inputs or outputs |
| CPAB      | 55   | clock input A-to-B     |

## 6. Functional description

### 6.1 Function table

Table 3. Function table<sup>[1]</sup>

| Inputs |      |        |    | Output | Operating mode         |
|--------|------|--------|----|--------|------------------------|
| OEAB   | LEAB | CPAB   | An | Bn     |                        |
| L      | X    | X      | X  | Z      | disabled               |
| H      | H    | X      | H  | H      | transparent            |
| H      | H    | X      | L  | L      |                        |
| H      | ↓    | X      | h  | H      | latch data and display |
| H      | ↓    | X      | l  | L      |                        |
| H      | L    | ↑      | h  | H      | clock data and display |
| H      | L    | ↑      | l  | L      |                        |
| H      | L    | H or L | X  | H      | hold data and display  |
| H      | L    | H or L | X  | L      |                        |

[1] A-to-B data flow is shown; B-to-A flow is similar but uses  $\overline{\text{OEBA}}$ , LEBA and CPBA.

H = HIGH voltage level;

h = HIGH voltage level one set-up time prior to the enable or clock transition;

L = LOW voltage level;

l = LOW voltage level one set-up time prior to the enable or clock transition;

X = don't care;

Z = high-impedance OFF-state;

↓ = HIGH-to-LOW clock transition;

↑ = LOW-to-HIGH clock transition.

## 7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol   | Parameter               | Conditions                    | Min                 | Max            | Unit |
|----------|-------------------------|-------------------------------|---------------------|----------------|------|
| $V_{CC}$ | supply voltage          |                               | -0.5                | +4.6           | V    |
| $I_{IK}$ | input clamping current  | $V_I < 0$ V                   | -50                 | -              | mA   |
| $V_I$    | input voltage           | control inputs                | <sup>[1]</sup> -0.5 | +4.6           | V    |
|          |                         | data inputs                   | <sup>[1]</sup> -0.5 | $V_{CC} + 0.5$ | V    |
| $I_{OK}$ | output clamping current | $V_O > V_{CC}$ or $V_O < 0$ V | -                   | ±50            | mA   |
| $V_O$    | output voltage          |                               | <sup>[1]</sup> -0.5 | $V_{CC} + 0.5$ | V    |
| $I_O$    | output current          | $V_O = 0$ V to $V_{CC}$       | -                   | ±50            | mA   |
| $I_{CC}$ | supply current          |                               | -                   | 100            | mA   |

**Table 4.** Limiting values ...continued

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol           | Parameter               | Conditions   | Min   | Max  | Unit |
|------------------|-------------------------|--|-------|------|------|
| $I_{\text{GND}}$ | ground current          |  | -100  | -    | mA   |
| $T_{\text{stg}}$ | storage temperature     |  | -65   | +150 | °C   |
| $P_{\text{tot}}$ | total power dissipation | $T_{\text{amb}} = -40\text{ °C to }+125\text{ °C}$ |       |      |      |
|                  |                         | SSOP package                                       | [2] - | 850  | mW   |
|                  |                         | TSSOP package                                      | [3] - | 600  | mW   |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] Above 55 °C the value of  $P_{\text{tot}}$  derates linearly with 11.3 mW/K.

[3] Above 55 °C the value of  $P_{\text{tot}}$  derates linearly with 8 mW/K.

## 8. Recommended operating conditions

**Table 5.** Recommended operating conditions

| Symbol              | Parameter                           | Conditions                                     | Min | Typ | Max             | Unit |
|---------------------|-------------------------------------|--|-----|-----|-----------------|------|
| $V_{\text{CC}}$     | supply voltage                      | maximum speed performance                      |     |     |                 |      |
|                     |                                     | $C_L = 30\text{ pF}$                           | 2.3 | -   | 2.7             | V    |
|                     |                                     | $C_L = 50\text{ pF}$                           | 3.0 | -   | 3.6             | V    |
|                     |                                     | low-voltage applications                       | 1.2 | -   | 3.6             | V    |
| $V_I$               | input voltage                       |  | 0   | -   | $V_{\text{CC}}$ | V    |
| $V_O$               | output voltage                      |  | 0   | -   | $V_{\text{CC}}$ | V    |
| $T_{\text{amb}}$    | ambient temperature                 | in free air                                    | -40 | -   | +85             | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{\text{CC}} = 2.3\text{ V to }3.0\text{ V}$ | 0   | -   | 20              | ns/V |
|                     |                                     | $V_{\text{CC}} = 3.0\text{ V to }3.6\text{ V}$ | 0   | -   | 10              | ns/V |

## 9. Static characteristics

**Table 6. Static characteristics**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol                                    | Parameter                       | Conditions  | Min                   | Typ <sup>[1]</sup>     | Max  | Unit |
|---|---------------------------------|---|-----------------------|------------------------|------|------|
| <b>T<sub>amb</sub> = –40 °C to +85 °C</b> |                                 |   |                       |                        |      |      |
| V <sub>IH</sub>                           | HIGH-level input voltage        | V <sub>CC</sub> = 2.3 V to 2.7 V  | 1.7                   | 1.2                    | -    | V    |
|   |                                 | V <sub>CC</sub> = 2.7 V to 3.6 V  | 2.0                   | 1.5                    | -    | V    |
| V <sub>IL</sub>                           | LOW-level input voltage         | V <sub>CC</sub> = 2.3 V to 2.7 V  | -                     | 1.2                    | 0.7  | V    |
|   |                                 | V <sub>CC</sub> = 2.7 V to 3.6 V  | -                     | 1.5                    | 0.8  | V    |
| V <sub>OH</sub>                           | HIGH-level output voltage       | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>   |                       |                        |      |      |
|   |                                 | I <sub>O</sub> = –100 µA;<br>V <sub>CC</sub> = 2.3 V to 3.6 V   | V <sub>CC</sub> – 0.2 | V <sub>CC</sub>        | -    | V    |
|   |                                 | I <sub>O</sub> = –6 mA; V <sub>CC</sub> = 2.3 V   | V <sub>CC</sub> – 0.3 | V <sub>CC</sub> – 0.08 | -    | V    |
|   |                                 | I <sub>O</sub> = –12 mA; V <sub>CC</sub> = 2.3 V  | V <sub>CC</sub> – 0.6 | V <sub>CC</sub> – 0.26 | -    | V    |
|   |                                 | I <sub>O</sub> = –12 mA; V <sub>CC</sub> = 2.7 V  | V <sub>CC</sub> – 0.5 | V <sub>CC</sub> – 0.14 | -    | V    |
|   |                                 | I <sub>O</sub> = –12 mA; V <sub>CC</sub> = 3.0 V  | V <sub>CC</sub> – 0.6 | V <sub>CC</sub> – 0.09 | -    | V    |
|   |                                 | I <sub>O</sub> = –24 mA; V <sub>CC</sub> = 3.0 V  | V <sub>CC</sub> – 1.0 | V <sub>CC</sub> – 0.28 | -    | V    |
| V <sub>OL</sub>                           | LOW-level output voltage        | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>   |                       |                        |      |      |
|   |                                 | I <sub>O</sub> = 100 µA;<br>V <sub>CC</sub> = 2.3 V to 3.6 V  | -                     | GND                    | 0.20 | V    |
|   |                                 | I <sub>O</sub> = 6 mA; V <sub>CC</sub> = 2.3 V  | -                     | 0.07                   | 0.40 | V    |
|   |                                 | I <sub>O</sub> = 12 mA; V <sub>CC</sub> = 2.3 V   | -                     | 0.15                   | 0.70 | V    |
|   |                                 | I <sub>O</sub> = 12 mA; V <sub>CC</sub> = 2.7 V   | -                     | 0.14                   | 0.40 | V    |
|   |                                 | I <sub>O</sub> = 24 mA; V <sub>CC</sub> = 3.0 V   | -                     | 0.27                   | 0.55 | V    |
| I <sub>I</sub>                            | input leakage current           | V <sub>I</sub> = V <sub>CC</sub> or GND;<br>V <sub>CC</sub> = 2.3 V to 3.6 V  | -                     | 0.1                    | 5    | µA   |
| I <sub>OZ</sub>                           | OFF-state output current        | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ;<br>V <sub>O</sub> = V <sub>CC</sub> or GND;<br>V <sub>CC</sub> = 2.7 V to 3.6 V | -                     | 0.1                    | 10   | µA   |
| I <sub>CC</sub>                           | supply current                  | V <sub>CC</sub> = 2.3 V to 3.6 V;<br>V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A                                    | -                     | 0.2                    | 40   | µA   |
| ΔI <sub>CC</sub>                          | additional supply current       | per data I/O pin; V <sub>CC</sub> = 2.3 V to 3.6 V; V <sub>I</sub> = V <sub>CC</sub> – 0.6 V; I <sub>O</sub> = 0 A                    | -                     | 150                    | 750  | µA   |
| I <sub>BHL</sub>                          | bus hold LOW current            | V <sub>CC</sub> = 2.3 V; V <sub>I</sub> = 0.7 V   | [2]                   | 45                     | -    | µA   |
|   |                                 | V <sub>CC</sub> = 3.0 V; V <sub>I</sub> = 0.8 V   | [2]                   | 75                     | 150  | µA   |
| I <sub>BHH</sub>                          | bus hold HIGH current           | V <sub>CC</sub> = 2.3 V; V <sub>I</sub> = 1.7 V   | [2]                   | –45                    | -    | µA   |
|   |                                 | V <sub>CC</sub> = 3.0 V; V <sub>I</sub> = 2.0 V   | [2]                   | –75                    | –175 | µA   |
| I <sub>BHLO</sub>                         | bus hold LOW overdrive current  | V <sub>CC</sub> = 3.6 V   | [2]                   | 500                    | -    | µA   |
| I <sub>BHHO</sub>                         | bus hold HIGH overdrive current | V <sub>CC</sub> = 3.6 V   | [2]                   | –500                   | -    | µA   |
| C <sub>I</sub>                            | input capacitance               |   | -                     | 4.0                    | -    | pF   |
| C <sub>I/O</sub>                          | input/output capacitance        |   | -                     | 8.0                    | -    | pF   |

[1] All typical values are measured at T<sub>amb</sub> = 25 °C.

[2] Valid for data inputs of bus hold parts only.

## 10. Dynamic characteristics

**Table 7. Dynamic characteristics**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V); test circuit [Figure 10](#).

| Symbol                                    | Parameter         | Conditions   | Min                     | Typ <sup>[1]</sup> | Max | Unit |
|---|-------------------|--|-------------------------|--------------------|-----|------|
| <b>T<sub>amb</sub> = –40 °C to +85 °C</b> |                   |  |                         |                    |     |      |
| f <sub>max</sub>                          | maximum frequency | see <a href="#">Figure 8</a>                       |                         |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 150 | 333                | -   | MHz  |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 150 | 340                | -   | MHz  |
|   |                   | V <sub>CC</sub> = 2.7 V                            | 150                     | 333                | -   | MHz  |
| t <sub>pd</sub>                           | propagation delay | An to Bn; Bn to An; see <a href="#">Figure 6</a>   | <a href="#">[4]</a>     |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.0 | 2.8                | 5.1 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.0 | 3.0                | 4.2 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 3.0                | 4.6 | ns   |
|   |                   | LEAB, LEBA to Bn, An; see <a href="#">Figure 8</a> |                         |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.1 | 3.5                | 6.1 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.3 | 3.4                | 4.8 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 3.6                | 5.3 | ns   |
|   |                   | CPAB, CPBA to Bn, An; see <a href="#">Figure 8</a> |                         |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.0 | 3.3                | 6.1 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.4 | 3.3                | 4.9 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 3.4                | 5.6 | ns   |
|   |                   | OEBA to An; see <a href="#">Figure 7</a>           | <a href="#">[4]</a>     |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.3 | 2.8                | 6.3 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.1 | 2.5                | 5.0 | ns   |
| t <sub>en</sub>                           | enable time       | V <sub>CC</sub> = 2.7 V                            | -                       | 3.3                | 6.0 | ns   |
|   |                   | OEAB to Bn; see <a href="#">Figure 7</a>           |                         |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.0 | 2.5                | 5.8 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.0 | 2.4                | 4.6 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 2.7                | 5.3 | ns   |
|   |                   | OEBA to An; see <a href="#">Figure 7</a>           | <a href="#">[4]</a>     |                    |     |      |
|   |                   | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.3 | 2.5                | 5.3 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.3 | 3.1                | 4.2 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 3.3                | 4.6 | ns   |
|   |                   | OEAB to Bn; see <a href="#">Figure 7</a>           |                         |                    |     |      |
| t <sub>dis</sub>                          | disable time      | V <sub>CC</sub> = 2.3 V to 2.7 V                   | <a href="#">[2]</a> 1.5 | 2.5                | 6.2 | ns   |
|   |                   | V <sub>CC</sub> = 3.0 V to 3.6 V                   | <a href="#">[3]</a> 1.4 | 2.9                | 5.0 | ns   |
|   |                   | V <sub>CC</sub> = 2.7 V                            | -                       | 3.6                | 5.7 | ns   |




**Table 7. Dynamic characteristics ...continued**At recommended operating conditions. Voltages are referenced to GND (ground = 0 V); test circuit [Figure 10](#).

| Symbol   | Parameter                     | Conditions   | Min                | Typ <sup>[1]</sup> | Max | Unit |
|----------|-------------------------------|--|--------------------|--------------------|-----|------|
| $t_W$    | pulse width                   | LEAB, LEBA HIGH; see <a href="#">Figure 8</a>        |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 3.3 | 0.8                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 3.3 | 0.9                | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 3.3                | 0.7                | -   | ns   |
|          |                               | CPAB, CPBA HIGH or LOW; see <a href="#">Figure 8</a> |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 3.3 | 2.0                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 3.3 | 1.1                | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 3.3                | 1.4                | -   | ns   |
| $t_{su}$ | set-up time                   | An, Bn to CPAB, CPBA; see <a href="#">Figure 9</a>   |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 1.7 | 0.1                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 1.3 | -0.3               | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 1.4                | -0.1               | -   | ns   |
|          |                               | An, Bn to LEAB, LEBA; see <a href="#">Figure 9</a>   |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 1.1 | 0.1                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 1.0 | 0.3                | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 1.0                | -0.2               | -   | ns   |
| $t_h$    | hold time                     | An, Bn to CPAB, CPBA; see <a href="#">Figure 9</a>   |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 1.7 | 0.3                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 1.3 | 0.4                | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 1.6                | 0.3                | -   | ns   |
|          |                               | An, Bn to LEAB, LEBA; see <a href="#">Figure 9</a>   |                    |                    |     |      |
|          |                               | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$           | <sup>[2]</sup> 1.6 | 0.3                | -   | ns   |
|          |                               | $V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$           | <sup>[3]</sup> 1.2 | 0.1                | -   | ns   |
|          |                               | $V_{CC} = 2.7 \text{ V}$                             | 1.5                | 0.1                | -   | ns   |
| $C_{PD}$ | power dissipation capacitance | per buffer; $V_I = \text{GND to } V_{CC}$            | <sup>[5]</sup>     |                    |     |      |
|          |                               | outputs enabled                                      | -                  | 21                 | -   | pF   |
|          |                               | outputs disabled                                     | -                  | 3                  | -   | pF   |


[1] All typical values are measured at  $T_{amb} = 25 \text{ }^\circ\text{C}$ .[2] Typical values are measured at  $V_{CC} = 2.5 \text{ V}$ .[3] Typical values are measured at  $V_{CC} = 3.3 \text{ V}$ .[4]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ . $t_{en}$  is the same as  $t_{PZL}$  and  $t_{PZH}$ . $t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ .[5]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ). $P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \sum (C_L \times V_{CC}^2 \times f_o)$  where: $f_i$  = input frequency in MHz; $f_o$  = output frequency in MHz; $C_L$  = output load capacitance in pF; $V_{CC}$  = supply voltage in Volts; $N$  = total load switching outputs; $\sum (C_L \times V_{CC}^2 \times f_o)$  = sum of outputs.

11. Waveforms




Measurement points are given in [Table 8](#).  
 $V_{OL}$  and  $V_{OH}$  are typical output levels that occur with the output load.

Fig 6. Propagation delay, data input (An, Bn) to data output (Bn, An)




Measurement points are given in [Table 8](#).  
 $V_{OL}$  and  $V_{OH}$  are typical output levels that occur with the output load.

Fig 7. 3-state output enable and disable times



Measurement points are given in [Table 8](#).  
 $V_{OL}$  and  $V_{OH}$  are typical output levels that occur with the output load.

**Fig 8.** Propagation delay, latch enable input (LEAB, LEBA) and clock pulse input (CPAB, CPBA) to data output, and pulse width




Measurement points are given in [Table 8](#).

**Fig 9.** Data set-up and hold times (An, Bn inputs to LEAB, LEBA, CPAB and CPBA inputs)

**Table 8.** Measurement points

| Supply voltage             | Input    |                     | Output              |                           |                           |
|----------------------------|----------|---------------------|---------------------|---------------------------|---------------------------|
| $V_{CC}$                   | $V_I$    | $V_M$               | $V_M$               | $V_X$                     | $V_Y$                     |
| 2.3 V to 2.7 V and < 2.3 V | $V_{CC}$ | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ | $V_{OL} + 0.15 \text{ V}$ | $V_{OH} - 0.15 \text{ V}$ |
| 2.7 V                      | 2.7 V    | 1.5 V               | 1.5 V               | $V_{OL} + 0.3 \text{ V}$  | $V_{OH} - 0.3 \text{ V}$  |
| 3.0 V to 3.6 V             | 2.7 V    | 1.5 V               | 1.5 V               | $V_{OL} + 0.3 \text{ V}$  | $V_{OH} - 0.3 \text{ V}$  |

12. Test information



Test data is given in [Table 9](#).  
Definitions for test circuit:  
 $R_L$  = Load resistance.  
 $C_L$  = Load capacitance includes jig and probe capacitance.  
 $R_T$  = Termination resistance should be equal to  $Z_o$  of pulse generator.  
 $V_{EXT}$  = External voltage for measuring switching times.

Fig 10. Load circuit for measuring switching times

Table 9. Test data

| Supply voltage | Input    |               | Load  |              | $V_{EXT}$          |                    |                    |
|----------------|----------|---------------|-------|--------------|--------------------|--------------------|--------------------|
| $V_{CC}$       | $V_I$    | $t_r, t_f$    | $C_L$ | $R_L$        | $t_{PLH}, t_{PHL}$ | $t_{PLZ}, t_{PZL}$ | $t_{PHZ}, t_{PZH}$ |
| 2.3 V to 2.7 V | $V_{CC}$ | $\leq 2.0$ ns | 30 pF | 500 $\Omega$ | open               | $2 \times V_{CC}$  | GND                |
| 2.7 V          | 2.7 V    | 2.5 ns        | 50 pF | 500 $\Omega$ | open               | $2 \times V_{CC}$  | GND                |
| 3.0 V to 3.6 V | 2.7 V    | 2.5 ns        | 50 pF | 500 $\Omega$ | open               | $2 \times V_{CC}$  | GND                |

13. Package outline

TSSOP56: plastic thin shrink small outline package; 56 leads; body width 6.1 mm

SOT364-1




Fig 11. Package outline SOT364-1 (TSSOP56)

SSOP56: plastic shrink small outline package; 56 leads; body width 7.5 mm

SOT371-1




Fig 12. Package outline SOT371-1 (SSOP56)

## 14. Abbreviations

Table 10. Abbreviations

| Acronym | Description                             |
|---------|---|
| CMOS    | Complementary Metal-Oxide Semiconductor |
| DUT     | Device Under Test                       |
| TTL     | Transistor-Transistor Logic             |

## 15. Revision history

Table 11. Revision history

| Document ID      | Release date                  | Data sheet status     | Change notice | Order number | Supersedes       |
|------------------|-------------------------------|-----------------------|---------------|--------------|------------------|
| 74ALVCH16501 v.5 | 20120710                      | Product data sheet    | -             | -            | 74ALVCH16501 v.4 |
| Modifications:   | • Table 8 corrected (errata). |                       |               |              |                  |
| 74ALVCH16501 v.4 | 20111117                      | Product data sheet    | -             | -            | 74ALVCH16501 v.3 |
| Modifications:   | • Legal pages updated.        |                       |               |              |                  |
| 74ALVCH16501 v.3 | 20100402                      | Product data sheet    | -             | -            | 74ALVCH16501 v.2 |
| 74ALVCH16501 v.2 | 19980929                      | Product specification | -             | -            | 74ALVCH16501 v.1 |
| 74ALVCH16501 v.1 | 19980929                      | Product specification | -             | -            | -                |

## 16. Legal information

### 16.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>

### 16.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 16.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms> unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.



**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond

Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

## 16.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 17. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

## 18. Contents

---

|           |   |           |
|-----------|---|-----------|
| <b>1</b>  | <b>General description</b> .....              | <b>1</b>  |
| <b>2</b>  | <b>Features and benefits</b> .....            | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....             | <b>2</b>  |
| <b>4</b>  | <b>Functional diagram</b> .....               | <b>2</b>  |
| <b>5</b>  | <b>Pinning information</b> .....              | <b>4</b>  |
| 5.1       | Pinning .....                                 | 4         |
| 5.2       | Pin description .....                         | 4         |
| <b>6</b>  | <b>Functional description</b> .....           | <b>5</b>  |
| 6.1       | Function table .....                          | 5         |
| <b>7</b>  | <b>Limiting values</b> .....                  | <b>5</b>  |
| <b>8</b>  | <b>Recommended operating conditions</b> ..... | <b>6</b>  |
| <b>9</b>  | <b>Static characteristics</b> .....           | <b>7</b>  |
| <b>10</b> | <b>Dynamic characteristics</b> .....          | <b>8</b>  |
| <b>11</b> | <b>Waveforms</b> .....                        | <b>10</b> |
| <b>12</b> | <b>Test information</b> .....                 | <b>12</b> |
| <b>13</b> | <b>Package outline</b> .....                  | <b>13</b> |
| <b>14</b> | <b>Abbreviations</b> .....                    | <b>15</b> |
| <b>15</b> | <b>Revision history</b> .....                 | <b>15</b> |
| <b>16</b> | <b>Legal information</b> .....                | <b>16</b> |
| 16.1      | Data sheet status .....                       | 16        |
| 16.2      | Definitions .....                             | 16        |
| 16.3      | Disclaimers .....                             | 16        |
| 16.4      | Trademarks .....                              | 17        |
| <b>17</b> | <b>Contact information</b> .....              | <b>17</b> |
| <b>18</b> | <b>Contents</b> .....                         | <b>18</b> |