

5

4

3

2

1

受控 CONTROLLED DOCUMENT

编号 P/N	25-7500-CUST	版本 Rev	01	日期 Rel'd Date	May8,09
-----------	--------------	-----------	----	------------------	---------

DRAWING NO.

25-7500-CUST

REVISIONS

01 OFFICIAL RELEASE

03-11-09

J

J

T

T

T

T

T

 Thomas Chow
 2009.05.07
 09:29:40
 +0800

D

Description: F female to BNC male adapter

Part No: 25-7500

Application: Adapter

Crimp Tool: N/A

Impedance: N/A

Frequency Range: 0-750 MHz

Material: Body Brass Nickel plated

Contact Beryllium Nickel plated

Insulator Delrin

Nut Zinc Nickel plated

RoHS Compliance: Yes

Technical Detail: F End Refer to Emerson Document P/N 25-0000

BNC End Refer to Emerson Document P/N 27-0000

C

B

11
(.433in) HEX

REF. \varnothing 14.5
(.571in)

\varnothing 1.30
(.051in)

3/8-32 UNEF

2.0
(.079in)

10.5
(.413in)

14.8
(.583in)

36
(1.417in)

DIM OUTLINE

A

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY	DATE
DECIMALS	mm	JEAN.JIN	03-11-09
X	± 0.5	CHECKED BY	DATE
X.X	± 0.3	TERRY.W	03-11-09
X.XX	± 0.1	APPROVED BY	DATE
ANGLES	± 0.5°	THOMAS	03-12-09
		U/M	mm

CUSTOMER COPY

TITLE
F FEMALE TO BNC MALE ADAPTERSHEET
1 OF 1DRAWING NO.
25-7500-CUSTSIZE
ATHIS DRAWING WAS PRODUCED BY COMPUTER.
DO NOT SCALE DRAWING OR UPDATE MANUALLY.

5

4

3

2

1

D

C

B

A