

# P2N2222A

## Amplifier Transistors

### NPN Silicon

#### Features

- Pb-Free Packages are Available\*

#### MAXIMUM RATINGS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic  | Symbol                            | Value          | Unit             |
|---|-----------------------------------|----------------|------------------|
| Collector - Emitter Voltage   | V <sub>CEO</sub>                  | 40             | Vdc              |
| Collector - Base Voltage  | V <sub>CBO</sub>                  | 75             | Vdc              |
| Emitter - Base Voltage  | V <sub>EBO</sub>                  | 6.0            | Vdc              |
| Collector Current - Continuous  | I <sub>C</sub>                    | 600            | mA <sub>dc</sub> |
| Total Device Dissipation @ T <sub>A</sub> = 25°C<br>Derate above 25°C | P <sub>D</sub>                    | 625<br>5.0     | mW<br>mW/°C      |
| Total Device Dissipation @ T <sub>C</sub> = 25°C<br>Derate above 25°C | P <sub>D</sub>                    | 1.5<br>12      | W<br>mW/°C       |
| Operating and Storage Junction<br>Temperature Range                   | T <sub>J</sub> , T <sub>stg</sub> | -55 to<br>+150 | °C               |

#### THERMAL CHARACTERISTICS



| Characteristic                          | Symbol           | Max  | Unit |
|---|------------------|------|------|
| Thermal Resistance, Junction to Ambient | R <sub>θJA</sub> | 200  | °C/W |
| Thermal Resistance, Junction to Case    | R <sub>θJC</sub> | 83.3 | °C/W |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.




ON Semiconductor®

<http://onsemi.com>



TO-92  
(T0-226AA)  
CASE 29-11  
STYLE 17

#### MARKING DIAGRAM



P2N2 = Device Code  
222A = Specific Device  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

| Device       | Package            | Shipping†          |
|--------------|--------------------|--------------------|
| P2N2222A     | TO-92              | 5000 Units / Bulk  |
| P2N2222AG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| P2N2222ARL1  | TO-92              | 2000 / Tape & Ammo |
| P2N2222ARL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Ammo |
| P2N2222AZL1  | TO-92              | 2000 / Tape & Reel |
| P2N2222AZL1G | TO-92<br>(Pb-Free) | 2000 Units / Tube  |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## P2N2222A

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic   | Symbol        | Min    | Max        | Unit            |
|--|---------------|--------|------------|-----------------|
| <b>OFF CHARACTERISTICS</b>   |               |        |            |                 |
| Collector – Emitter Breakdown Voltage<br>( $I_C = 10\text{ mAdc}$ , $I_B = 0$ )  | $V_{(BR)CEO}$ | 40     | –          | Vdc             |
| Collector – Base Breakdown Voltage<br>( $I_C = 10\text{ }\mu\text{Adc}$ , $I_E = 0$ )  | $V_{(BR)CBO}$ | 75     | –          | Vdc             |
| Emitter – Base Breakdown Voltage<br>( $I_E = 10\text{ }\mu\text{Adc}$ , $I_C = 0$ )  | $V_{(BR)EBO}$ | 6.0    | –          | Vdc             |
| Collector Cutoff Current<br>( $V_{CE} = 60\text{ Vdc}$ , $V_{EB(off)} = 3.0\text{ Vdc}$ )  | $I_{CEX}$     | –      | 10         | nAdc            |
| Collector Cutoff Current<br>( $V_{CB} = 60\text{ Vdc}$ , $I_E = 0$ )<br>( $V_{CB} = 60\text{ Vdc}$ , $I_E = 0$ , $T_A = 150^\circ\text{C}$ ) | $I_{CBO}$     | –<br>– | 0.01<br>10 | $\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{EB} = 3.0\text{ Vdc}$ , $I_C = 0$ )  | $I_{EBO}$     | –      | 10         | nAdc            |
| Collector Cutoff Current<br>( $V_{CE} = 10\text{ V}$ )   | $I_{CEO}$     | –      | 10         | nAdc            |
| Base Cutoff Current<br>( $V_{CE} = 60\text{ Vdc}$ , $V_{EB(off)} = 3.0\text{ Vdc}$ )   | $I_{BEX}$     | –      | 20         | nAdc            |

### ON CHARACTERISTICS

|   |               |   |                                   |     |
|---|---------------|---|-----------------------------------|-----|
| DC Current Gain<br>( $I_C = 0.1\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ )<br>( $I_C = 1.0\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $T_A = -55^\circ\text{C}$ )<br>( $I_C = 150\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ ) (Note 1)<br>( $I_C = 150\text{ mAdc}$ , $V_{CE} = 1.0\text{ Vdc}$ ) (Note 1)<br>( $I_C = 500\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ ) (Note 1) | $h_{FE}$      | 35<br>50<br>75<br>35<br>100<br>50<br>40 | –<br>–<br>–<br>–<br>300<br>–<br>– | –   |
| Collector – Emitter Saturation Voltage (Note 1)<br>( $I_C = 150\text{ mAdc}$ , $I_B = 15\text{ mAdc}$ )<br>( $I_C = 500\text{ mAdc}$ , $I_B = 50\text{ mAdc}$ )   | $V_{CE(sat)}$ | –<br>–                                  | 0.3<br>1.0                        | Vdc |
| Base – Emitter Saturation Voltage (Note 1)<br>( $I_C = 150\text{ mAdc}$ , $I_B = 15\text{ mAdc}$ )<br>( $I_C = 500\text{ mAdc}$ , $I_B = 50\text{ mAdc}$ )  | $V_{BE(sat)}$ | 0.6<br>–                                | 1.2<br>2.0                        | Vdc |

### SMALL-SIGNAL CHARACTERISTICS

|  |           |             |             |                  |
|--|-----------|-------------|-------------|------------------|
| Current – Gain – Bandwidth Product (Note 2)<br>( $I_C = 20\text{ mAdc}$ , $V_{CE} = 20\text{ Vdc}$ , $f = 100\text{ MHz}$ )C   | $f_T$     | 300         | –           | MHz              |
| Output Capacitance<br>( $V_{CB} = 10\text{ Vdc}$ , $I_E = 0$ , $f = 1.0\text{ MHz}$ )  | $C_{obo}$ | –           | 8.0         | pF               |
| Input Capacitance<br>( $V_{EB} = 0.5\text{ Vdc}$ , $I_C = 0$ , $f = 1.0\text{ MHz}$ )  | $C_{ibo}$ | –           | 25          | pF               |
| Input Impedance<br>( $I_C = 1.0\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )           | $h_{ie}$  | 2.0<br>0.25 | 8.0<br>1.25 | k $\Omega$       |
| Voltage Feedback Ratio<br>( $I_C = 1.0\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )    | $h_{re}$  | –<br>–      | 8.0<br>4.0  | $\times 10^{-4}$ |
| Small-Signal Current Gain<br>( $I_C = 1.0\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ ) | $h_{fe}$  | 50<br>75    | 300<br>375  | –                |
| Output Admittance<br>( $I_C = 1.0\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )<br>( $I_C = 10\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )         | $h_{oe}$  | 5.0<br>25   | 35<br>200   | $\mu\text{Mhos}$ |
| Collector Base Time Constant<br>( $I_E = 20\text{ mAdc}$ , $V_{CB} = 20\text{ Vdc}$ , $f = 31.8\text{ MHz}$ )  | $rb'C_c$  | –           | 150         | ps               |
| Noise Figure<br>( $I_C = 100\text{ }\mu\text{Adc}$ , $V_{CE} = 10\text{ Vdc}$ , $R_S = 1.0\text{ k}\Omega$ , $f = 1.0\text{ kHz}$ )  | $N_F$     | –           | 4.0         | dB               |

1. Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .
2.  $f_T$  is defined as the frequency at which  $|h_{fe}|$  extrapolates to unity.

# P2N2222A

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

| Characteristic                   |   | Symbol | Min | Max | Unit |
|----------------------------------|---|--------|-----|-----|------|
| <b>SWITCHING CHARACTERISTICS</b> |   |        |     |     |      |
| Delay Time                       | $(V_{CC} = 30\text{ Vdc}, V_{BE(\text{off})} = -2.0\text{ Vdc}, I_C = 150\text{ mA}, I_{B1} = 15\text{ mA})$ (Figure 1) | $t_d$  | -   | 10  | ns   |
| Rise Time                        |   | $t_r$  | -   | 25  | ns   |
| Storage Time                     | $(V_{CC} = 30\text{ Vdc}, I_C = 150\text{ mA}, I_{B1} = I_{B2} = 15\text{ mA})$ (Figure 2)                              | $t_s$  | -   | 225 | ns   |
| Fall Time                        |   | $t_f$  | -   | 60  | ns   |

### SWITCHING TIME EQUIVALENT TEST CIRCUITS




Figure 1. Turn-On Time

Figure 2. Turn-Off Time




Figure 4. DC Current Gain




Figure 3. Collector Saturation Region

# P2N2222A




Figure 5. Turn-On Time




Figure 6. Turn-Off Time




Figure 7. Frequency Effects




Figure 8. Source Resistance Effects




Figure 9. Capacitances




Figure 10. Current-Gain Bandwidth Product

# P2N2222A




Figure 11. "On" Voltages






Figure 12. Temperature Coefficients

# P2N2222A

## PACKAGE DIMENSIONS

TO-92 (TO-226)  
CASE 29-11  
ISSUE AL



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.175  | 0.205 | 4.45        | 5.20  |
| B   | 0.170  | 0.210 | 4.32        | 5.33  |
| C   | 0.125  | 0.165 | 3.18        | 4.19  |
| D   | 0.016  | 0.021 | 0.407       | 0.533 |
| G   | 0.045  | 0.055 | 1.15        | 1.39  |
| H   | 0.095  | 0.105 | 2.42        | 2.66  |
| J   | 0.015  | 0.020 | 0.39        | 0.50  |
| K   | 0.500  | ---   | 12.70       | ---   |
| L   | 0.250  | ---   | 6.35        | ---   |
| N   | 0.080  | 0.105 | 2.04        | 2.66  |
| P   | ---    | 0.100 | ---         | 2.54  |
| R   | 0.115  | ---   | 2.93        | ---   |
| V   | 0.135  | ---   | 3.43        | ---   |

### STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85062-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.