

SERIES 2000 ANTENNAS

Check for Samples: [RI-ANT-G01E](#), [RI-ANT-G02E](#), [RI-ANT-S01C](#), [RI-ANT-S02C](#)

FEATURES

- **Best in Class Performance Through Patented HDX Technology**
- **Protection Class IP 65 and Higher**
- **Four Form Factors Available**
- **Proven in Harsh Industrial Environments**
- **Easy to Install and Use**

APPLICATIONS

- **Access Control**
- **Vehicle Identification**
- **Container Tracking**
- **Asset Management**
- **Waste Management**

DESCRIPTION

These antenna products connect to radio frequency modules (RFM) and reader/writers to form the interface to the low-frequency (LF) 134.2-kHz Texas Instruments transponders. In combination with a reader/writer, they transmit energy and signals to the transponder and receive the response from the tag. There are two standard gate antennas and two standard stick antennas with 1-meter or 3-meter cable length. Each antenna generates a specific size and shape of read zone to meet the requirements of the target application. In general, the gate antennas generate a large read zone with greater distance, while the stick antennas provide a more focused read zone and an ability to discriminate between transponders.

The antennas are well suited for use in a broad range of applications including access control, vehicle identification, container tracking, asset management, and waste management applications.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Gate Antennas – Specifications

Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)

	RI-ANT-G01E	RI-ANT-G02E	UNIT
Operating Temperature	–30 to +60	–30 to +60	°C
Storage Temperature	–40 to +70	–40 to +70	°C

Operating Characteristics

over operating free-air temperature range (unless otherwise noted)

PARAMETER	RI-ANT-G01E	RI-ANT-G02E	UNIT
Inductance (typical), at 134.2 kHz	27	27	μH
Protection Class	IP 65	IP 65	
Vibration	Mil-Std-810E, Test 514.4 (Category 1, Procedure 1; Basic transportation)		
Case Material	UVSHIPS (UV-Stabilized High Impact Polystyrol)		
Dimensions	715 ± 5 × 270 ± 3 × 25 ± 1	200 ± 3 × 200 ± 3 × 25 ± 1	mm
Weight (typical)	745	425	g
Cable Length	1	1	m
Connection Terminals	Spade and tongue, stud hole 3.5 mm, width 7.5 mm		
Mounting	Use nonmetallic clamps, standard screws, and washers through 6.5-mm predrilled holes, so that the screw hole is flush with the mounting. Mounting material is not supplied with the antenna.		

Stick Antennas – Specifications

Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)

	RI-ANT-S01C	RI-ANT-S02C	UNIT
Operating Temperature	–30 to +70	–30 to +70	°C
Storage Temperature	–40 to +85	–40 to +85	°C

Operating Characteristics

over operating free-air temperature range (unless otherwise noted)

PARAMETER	RI-ANT-S01C	RI-ANT-S02C	UNIT
Inductance (typical), at 134.2 kHz	27	27	μH
Protection Class	IP 66	IP 66	
Vibration	Mil-Std-810E, Test 514.4 (Category 1, Procedure 1; Basic transportation)		
Case Material	Glass reinforced epoxy (gray)		
Dimensions	140 ± 2 × 21 ± 2 (dia.)	140 ± 2 × 21 ± 2 (dia.)	mm
Weight (typical)	134	185	g
Cable Length	1	3	m
Connection Terminals	Ring lugs: 3.5-mm inside diameter 7.5-mm outside diameter	Ring lugs: 3.5-mm inside diameter 7.5-mm outside diameter	
Mounting	Use nonmetal clamps. Mounting material is not supplied with the antenna.		

Readout Pattern of Ferrite Rod (Stick) and Gate Antennas




Figure 1. Readout Pattern of Antennas

REVISION HISTORY

REVISION	CHANGES
SCBS845	First release
SCBS845A	Removed all information about RI-ANT-G04E and RI-ANT-P02A (obsolete)

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
RI-ANT-G01E-30	ACTIVE			0	1	TBD	Call TI	Call TI	-30 to 60		Samples
RI-ANT-G02E-30	ACTIVE			0	1	TBD	Call TI	Call TI	-30 to 60		Samples
RI-ANT-S02C-30	ACTIVE			0		TBD	Call TI	Call TI	-30 to 70		Samples
TRPGP40TGC	ACTIVE	RFIDT	TGC	0		TBD	Call TI	Call TI	-25 to 70		Samples
TRPGR30ATGA	ACTIVE	RFIDT	TGA	0	2000	Pb-Free (RoHS)	Call TI	N / A for Pkg Type	-25 to 70		Samples
TRPGR30ATGB	ACTIVE	RFIDT	TGB	0	2000	Pb-Free (RoHS)	Call TI	N / A for Pkg Type	-25 to 70		Samples
TRPGR30ENATGA	ACTIVE	RFIDT	TGA	0	2000	Pb-Free (RoHS)	Call TI	N / A for Pkg Type	-25 to 70		Samples
TRPGR30ENATGB	ACTIVE	RFIDT	TGB	0	2000	Pb-Free (RoHS)	Call TI	N / A for Pkg Type	-25 to 70		Samples
TRPGR30TGC	ACTIVE	RFIDT	TGC	0		TBD	Call TI	Call TI	-25 to 85		Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE FOR TI DESIGN INFORMATION AND RESOURCES

Texas Instruments Incorporated ("TI") technical, application or other design advice, services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using any particular TI Resource in any way, you (individually or, if you are acting on behalf of a company, your company) agree to use it solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources.

You understand and agree that you remain responsible for using your independent analysis, evaluation and judgment in designing your applications and that you have full and exclusive responsibility to assure the safety of your applications and compliance of your applications (and of all TI products used in or for your applications) with all applicable regulations, laws and other applicable requirements. You represent that, with respect to your applications, you have all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. You agree that prior to using or distributing any applications that include TI products, you will thoroughly test such applications and the functionality of such TI products as used in such applications. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

You are authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING TI RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY YOU AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You agree to fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of your non-compliance with the terms and provisions of this Notice.

This Notice applies to TI Resources. Additional terms apply to the use and purchase of certain types of materials, TI products and services. These include; without limitation, TI's standard terms for semiconductor products (<http://www.ti.com/sc/docs/stdterms.htm>), [evaluation modules](#), and [samples](http://www.ti.com/sc/docs/sampterm.htm) (<http://www.ti.com/sc/docs/sampterm.htm>).

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2017, Texas Instruments Incorporated