



- 1 NYLON, UL 94V-0 RATED, BLACK.
- 2 2.54µm [0.000100] MIN TIN-LEAD OVER 1.27µm [0.000050] MIN NICKEL.
- 3 TIN PLATING PER MIL-T-10727, NICKEL PLATING PER QQ-N-290.
- 4 ACCEPTS #2 SELF-TAPPING SCREW, .250 LONG REF.
- 5 MATES WITH 8 POSITION SHIELDED DIN PLUG 212437-4.
- 6 BRASS PER ASTM B36.

REV	DATE	BY	APP'D	DESCRIPTION
1				
2				
3				
4				
5				
6				REDRAWN

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN MM (INCHES) TOLERANCES ON: 1. 2 PLC DEC ±0.13(.005) 3. PLC DEC ±0.30° ANGLES MATERIAL		DR 8/12/91 A. STUBBS	1/2-26-91	<p>AWP Incorporated Harrisburg, PA 17105-3608</p>
HOUSING, CONTACTS, GROUND CONTACT, FINISH, CONTACTS, GROUND CONTACT		App'd: <i>[Signature]</i> 11-26-91	NAME: <i>[Signature]</i> 11-26-91	
PRODUCT SPEC: 108-10047 APPLICATION SPEC: 114-40025		DR 8/12/91 A. STUBBS	11-26-91	RECEPTACLE ASSY, RIGHT ANGLE, 8 POSITION, CIRCULAR DIN
SCALE: 4:1		SIZE: C CAGE CODE: 00779	DRAWING NO: 211511	PART NUMBER: 211511-1